

M. P. MÖLLER Organ Factory

Pipe Organ No. 7885 Date June 1, 1948
 For DUTCH REFORMED CHURCH, SOMERSET STRAND, CAPE PROVINCE, SOUTH AFRICA
 Action Electro-pneumatic Console Detached, ALL ELECTRIC
 Casing No. Case Work Finish Oak or Walnut
 Decorations None Motor blower & generator by purchaser
 Width of Key-bed Standard Stop Controls Stop Keys
 No. Manuals Two Wind Pressure 5-1/2"
 To be Completed Soon as possible Blower Pipe furnished by Moller

PITCH

A-440

SPECIFICATIONS

Great Organ

(*unenclosed*)
 1 16' Bourdon..t.c.....from #3.....49 notes
 2 8' Open Diapason.....43.....18-19-1/2.....17 Zinc...C.M.....61 pipes
 3 8' Hohlflöte (Unit).....Reg. Hohlflöte, ~~Mel. Bass~~ *ST. Bass*.....85 pipes
 4 8' Dulciana.....56.....12 Zinc...C.M.....61 pipes
 5 4' Principal.....56.....18-19-1/2.....C.M.....73 pipes
 6 4' Flute.....from #3.....61 notes
 7 2' Fifteenth.....from #5.....61 notes
 8 2' Piccolo.....from #3.....61 notes
 9 8' Trumpet.....4-1/2".....Hooded.....61 pipes

Swell Organ

10 16' Lieblich Bourdon (Unit).....97 pipes
(1-12) #2 Ped. Bdn., (13-24) *L.M.B.*, #25 up Reg. Stpd. Flt.....
 11 8' Open Diapason.....46.....17 Zinc...C.M.....73 pipes
 12 8' Gedact.....from #10.....61 notes
 13 8' Dulciana.....from #4.....61 notes
 14 8' Gamba.....56.....12 Zinc...S.M.....61 pipes
 15 8' Voix Celeste..t.c...58.....S.M.....49 pipes
 16 4' Octave.....from #11.....61 notes
 17 4' Lieblichflöte.....from #10.....61 notes
 18 2-2/3' Nazard.....from #10.....61 notes
 19 2' Flautina.....from #10.....61 notes
 20 8' Oboe.....3-1/2".....61 pipes
 21 Tremulant

Pedal Organ

22 16' Open Diapason.....Reg. Db1. Open.....44 pipes
 23 16' Bass Flute.....from #10.....32 notes
 24 8' Diapason.....from #22.....32 notes
 25 8' Flute.....from #3.....32 notes
 26 8' Dulciana.....from #4.....32 notes
 27 8' Trumpet.....from #9.....32 notes

Couplers

28	Swell 4'	33	Great 4'
29	Swell 16'	34	Great 16'
30	Swell to Great 4'	35	Swell to Pedal
31	Swell to Great	36	Swell to Pedal 4'
32	Swell to Great 16'	37	Great to Pedal

Adjustable Combinations

Pistons No. 1-2-3-4	Affecting Great and Pedal Stops (Duplicated by toe studs)
Pistons No. 1-2-3-4	Affecting Swell and Pedal Stops
Pistons No. 1-2-3-4	Affecting Full Organ
General Cancel Piston	

Pedal Movements

Great to Pedal, Reversible
Sforzando Reversible
Balanced Expression Pedal for Swell Organ
Balanced Crescendo Pedal

Accessories

Crescendo Indicator lights
Organist's Bench
Starter Buttons, silent in operation
Concave, Radiating Pedal Clavier

General

ALL-ELECTRIC DETACHED CONSOLE: 50ft. cable
STOPKEYS for all stops and couplers
CONSOLE case in either oak or walnut - to be decided later
CASEWORK included; design to follow
BLOWER AND GENERATOR not included
SUPPLY sufficient wind conduit for connecting blower to organ, as will be shown
on plan

CASES TO BE ADDRESSED:

Cooper, Gill & Tomkins, (Pty.) Ltd.
Dutch Reformed Church,
THE STRAND, Cape Province, South Africa

SHIP TO CAPE TOWN

JHH: jr
12/6/48