Möller Organ Factory 2/4

Pine Organ No.	11854	Date	March 25, 1991	
	ST. LUKE'S LUTHERAN			
			isting - With Rollto	
	sting - No Change			
	None	Motor Existin	g - 1 HP, Style 3P27	
	Standard	Tracker Touch	Yes No	
Keys to be	Existing		Implex Tilting Tabl	
	TWO AND PEDAL			
To be Completed	August 1, 1992	Blower Pipe F	urnished by Existin	
	Complet	ed by Wicki		
		7		
	SPECI	FICATIONS FOR		
	REBUILDING PRE	ESENT MÖLLER ORGAN		
		339 - 1952		
CONSOLE	Reuse present co	onsole, rebuilding	as follows:	
			1-1-3-1	
		keys with tiltin	ig tablets and	
	contacts.		.~	
		oination pneumatio maries and install		
	new armatures.			
Recover all reversible actions. Replace crescendo and expression pedal pads and				
	edgings. Replace burrs and felt washers on manual keys.			
	Install new key			
	Refelt action as			
	Refelt pedal keyboard and install new insulating tips			
	Recover reservoi			
	Recover roll top).		
	Refinish console	e cabinet, bench a	nd pedal keys.	
MANUAL & OFFSET		lowing actions and	I install new	
CHESTS	armatures.			
	Great	8 Diapaso	on 73 notes	
	Great	8 Gedackt		
	Great	8 Salicio		
	Great	8 Dulcian		
	22343			
	Recover all prim	maries for offset	chests.	
PEDAL ORGAN	Recover the foll	lowing actions and	l install new	
	armatures.			
*			10	
	16 Bou	irdon	12 notes	
	Pogovor all aria	marine for modal a	sheete	
	kecover all prin	maries for pedal o	.Heses.	

11854	ST. LUKE'S LUTHERAN CHURCH, FEAGAVILLE, MARYLAND PAGE
CHIMES	Install new electric actions. Reuse present bells.
SWITCHES	Install new solid state switches as required.
EXPRESSION	Refelt shades. Install new electric action with trace rods.
RESERVOIR	Recover the following reservoirs and install new curtain valves.
	One 1-4 x 1-9 One 1-6 x 2-0 One 2-0 x 4'0
TREMULANT	Install new electric tremulant for entire organ.
PIPES	Revoice all pipes being reused. Repack all wood pipe stoppers. Install slide tuners as required.
CABLES	Install new plastic covered cables between console an organ. Install new action current wires between console, organd DC organ power unit.
ACTION CURREN	Install new 11-15 volts, 35 amperes DC organ power un with air switch.
BLOWER	Reuse present 1 HP, Style 3P-2722 motor and blower without change. Install new motor-blower coupling leather. Install new 10" diameter flexible connection with drabands.
GENERAL	All parts specified above to be rebuilt to be returne to the factory of M. P. Möller, Inc. at Hagerstown, Maryland.
	All parts from present instrument not required to complete this contract are to be removed by and become the property of M. P. Möller, Inc.

1.

2.

3.

17.

18.

23.

24.

27.

8

8

2 2/3

2

8

SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS	CC to C4, bl notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	Great 4", Swell 5", Pedal 4" and 5"
PITCH	A-440 @ 70° F.

Note: Present pipes and action unless indicated.

GREAT ORGAN - Enclosed

Flute......85 pipe

4.	8	Dulciana
5.	4	Octave
6.	4	Flute
7.	4	Dulcianafrom #461 not
	2 2/3	Dulciana
9.	2	Dulciana

i		
		SWELL ORGAN - Enclosed
10.	16	Dulciana TCfrom #461 note
11.	8	Flute
12.	8	Salicionalfrom #361 note
13.	8	Dulciana
14.	4	Flute
15.	4	Salicionalfrom #361 note
16.	4	Dulciana

19.		Tremulant
**		PEDAL ORGAN
20.	16	Bourdon12 present pipes; 20 from #232 note
21.	8	Diapason32 note
22.	8	Flute32 note

RS

				COUPLER
25.	Great	to	Pedal	
26.	Swell	to	Pedal	

Swell to Great

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4

Affecting Full Organ

REVERSIBLES

Great to Pedal - toe lever

PEDAL MOVEMENTS

Balanced Expression Pedal - Entire Organ Balanced Crescendo Pedal with indicator light

ACCESSORIES

Concave, radiating pedal clavier
Presetn organ bench with music shelf
Present music rack with light
Present pedal light
Present motor and blower to be reused without change
New DC organ power unit

dmm 1-24-92

Salesman: John Holland