

M. P. MÖLLER Organ Factory

2/19

Pipe Organ No. 10769 Date January 14, 1971
 For FIRST BAPTIST CHURCH, RICHMOND, KENTUCKY
 Action Moller's Electro-Pneumatic Console Detached
 Casing No. None Finish As Per Sample
 Decorations None Motor 2 H.P. Style 3-P-3025
 Width of Key-bed Standard Stop Controls By Draw Knobs
 No. Manuals TWO Ivory Keys Wind Pressure 4"
 To be Completed August 15, 1971 Blower Pipe furnished by Purchaser

SPECIFICATIONS

PITCH: A-440

The organ is to be the distinctive work of M. P. Moller, Inc., not an assembled product.

Quotation includes all freight and installation in the church.

GREAT ORGAN

1.	8'	Principal.....45.....18-1/2.....12 Zinc S.M...61 pipes
2.	8'	Rohrflöte.....54.....21-1/2.....12 Zinc S.M...61 pipes
3.	8'	Gemshorn.....52-1/3...17-1/2.....12 Zinc S.M...61 pipes
4.	4'	Octave.....58.....18-1/2.....S.M...61 pipes
5.	2'	Waldflöte.....68-3/4...20-1/2.....S.M...61 pipes
6.	IV Rks.	Mixture.....Formula "A"..18-1/2.....S.M...244 pipes
7.		Chimes
8.		Tremulant....present Deagan Class K tubes, new electro-pneumatic action A to F, #22 to #42.....21 tubes

SWELL ORGAN

9.	8'	Holzgedeckt....Reg. Stopped Flute Bass & Treble..Wood.....61 pipes
10.	8'	Viola Pomposa.....52.....18-1/2.....12 Zinc S.M...61 pipes
11.	8'	Viola Celeste T.C..54.....18-1/2.....S.M...49 pipes
12.	4'	Koppelflöte.....64.....20-1/2.....S.M...61 pipes
13.	2'	Principal.....70.....18-1/2.....S.M...61 pipes
14.	1-1/3'	Quinte.....78-2/3...18-1/2.....S.M...61 pipes
15.	8'	Trompette...1-18 half length CC 2-1/4" TC 1-5/8"..42-1/2..61 pipes
16.		Tremulant

PEDAL ORGAN

17.	16'	Subbass.....Reg. Ped. Bdn.....Wood.....32 pipes
18.	16'	Gedeckt....Reg. Man. Bdn...12 pipes, 20 from #9.....32 notes
19.	8'	Principal.....44.....18-1/2.....12 Zinc S.M...32 pipes
20.	4'	Spitzflöte.....58-2/3...19-1/2.....S.M...32 pipes
21.	16'	Contre Trompette (1/2 L)..3-1/2"..12 pipes, 20 from #15....32 notes

39446

COUPLERS

- 22. Great to Pedal 8'
- 23. Swell to Pedal 8'
- 24. Swell to Great 8'

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great Organ
Pistons No. 1-2-3	Affecting Swell Organ
Toe Studs No. 1-2-3	Affecting Pedal Organ
Pistons No. 1-2-3-4-5	Affecting Full Organ
General Cancel Piston	

PEDAL MOVEMENTS

Great to Pedal Reversible (duplicated by manual piston)
Swell to Pedal Reversible (duplicated by manual piston)
Sforzando Reversible (duplicated by manual piston)
Balanced Expression Pedal - Great Organ
Balanced Expression Pedal - Swell Organ
Balanced Crescendo Pedal

ACCESSORIES

Concave, radiating pedal clavier
Organ bench with music shelf
Crescendo indicator light
Sforzando indicator light
Music rack light
Pedal board light
Momentary contact starter switch mounted in console
Motor, blower and action current power unit of ample capacity
Supply and install in the console a safety switch that will cut off blower motor when roll top is closed.

GENERAL

M. P. Müller, Inc. to dismantle and remove the present organ from the church, at no expense to the church. M. P. Müller, Inc. has the privilege of retaining any portion of the organ for scrap value.

JHH/mr
6/21/71

Salesman: R. J. Talbert

ORGAN NO. 10769

FIRST BAPTIST CHURCH, RICHMOND, KENTUCKY

MIXTURE FORMULAS

GREAT ORGAN
IV Rks. Mixture Formula "A"

19	15	12	8	8
22	19	15	12	12
26	22	19	15	15
29	26	22	19	15
1-12	13-24	25-36	37-48	49-61

Unison	47 @ 8' CC	18-1/2	1/4 mouth	S.M.
Quint	48 @ 8' CC	18-1/2	2/9 mouth	S.M.