# M. P. MÖLLER Organ Factory Variels

		10 manufactura de constitución	
Pipe Organ No	R-794 West 7	Millipate December 6, 1967	
For	HOLY TRINITY CHURCH	PENNSYLVANIA	
Action	Electro-Pneumatic	Console Detached	
Casing No	None	Finish To customer's selection	
Decorations	None	Motor New motor, blower & power unit	
Width of Key-bed_	Standard	Stop Controls Tilting Tablets	
No. Manuals	One and Pedal	Wind Pressure 3-3/4"	
	December 20, 1969 1970	Blower Pipe furnished by Purchaser	
	SPECIFIC	CATIONS	
	FOR		
	REBUILDING PRESENT MOLLER	ORGAN OPUS 2273 - 1916	
CONSOLE	Install new one manual detached all electric tilting tablet type console, pedal keyboard and organ bench.		
MANUAL CHEST	Discard Great Organ chest Releather 1800 manual pipe of Install 1200 new stop action Install 61 new duplex shift Install 6 new single stop Install 1 new duplex stop Install 1 new duplex stop Install new bottom boards. Unify 61 note 8 Holzgedack Releather and electrify 8 Releather and electrify on	couches.  n checks and eyelets.  ters.  action rails.  action rail.  t action.  stop action primaries.	
OFFSET ACTION	Releather and electrify 8	Trompette action #1 to #7 incl.	
CONTACT DOX	Install New 62 note Contac	₩ DOR.	
SWITCHES	Install the following new stop actions:	electro-pneumatic switches with	
· · · · · · · · · · · · · · · · · · ·	8 Holzgedackt - 61 N	otes Station Cutout - 6/Notes tes	
PEDAL ORGAN	Releather and electrify 16	Bourdon action #1 to #44 incl. Gedackt action #1 to #12 incl.	
EXPRESSION	Discard existing swell box	, shades and action.	
RESERVOIRS	Releather the following re	servoirs:	
	One (1) 2'-6" x 4'-6"	Manual Reservoir	

Add the following reservoir

One (1) 1'-6" x 2'-6" Pedal Reservoir

PIPFS

Install the following new pipes:

8 Principal - 61 Pipes 4 Octave - 61 Pipes 2 Super Octave - 61 Pipes II Mixture - 122 Pipes 8 Trompette - 61 Pipes

Install modern tuning slides on the following pipes:

8 Dulciana - 61 Slides

4 Flute Harmonique - 73 Slides

CABLES

Install new plastic covered cables between console and organ. Install new action current wires between console, blower and organ power unit.

BLOWER

Install new Meidinger Style 140-5 blower and motor.

ACTION CURRENT

Install new organ power unit of ample capacity.

GENERAL

Entire organ to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md. for rebuilding as specified. All organ parts not required in revised specifications to be discarded.

#### SPECIFICATIONS

FOR

#### CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH CC to Ch, 61 Notes CCC to G, 32 Notes 3-3/4" A-hh0 @ 70° F

# MANUAL (unenclosed)

1	8	Principalnew pipes; present Swell 8 Horn Diapason action
2	8	Holzgedacktpresent Swell 8 Bourdon pipes; present Swell
		8 Bourdon action
3	8	Dulcianapresent pipes; present Swell 8 Viole D'Orchestre action. El Pipes
4	4	Octavenew pipes; present Swell 8 Salicional action
5	4	Flute Harmoniquepresent pipes; present action
6	2	Super Octavenew pipes; present Swell 8 Oboe D'Orchestre action. 61 Pipes
7	2	Piccolo
8	II	Mixturenew pipes; present Swell 8 Stopped Diapason action122 Pipes
9	8	Trompettenew pipes; present Swell 8 Cornopean action

# PEDAL ORGAN (\*)

10	16	Bourdonpresent pipes; present action	Pipes
11	16	Gedackt#1 to #12 present pipes, present action; 20 from #232	Notes
12	8	Flöte	Notes
13	8	Holzgedacktfrom #232	Notes

(\*) Pedal Organ playable thru slides in console.

# COUPLERS

ll Manual to Pedal

# ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4

Affecting Full Organ

# PEDAL MOVEMENTS

Balanced Crescendo Pedal with indicator light (green jewel)

# ACCESSORIES

Music rack light.
Pedal light.

Motor starter switch.

Concave and radiating pedal keyboard. Organ bench with music shelf.

New Meidinger blower. New organ power unit of ample capacity.

Blower enclosure