

THE REUTER ORGAN COMPANY

LAWRENCE, KANSAS

PROPOSES A BETTERMENT PROGRAM FOR REUTER OPUS # 1409

INSTALLED IN 3/24

BETHANY LUTHERAN CHURCH OF LAKEWOOD

LONG BEACH, CALIFORNIA

JUNE 1, 1995

Roger Begley – Reuter Representative
1363 Donlon Street, # 3, Ventura, CA 93003

50185

Op. 1409

GENERAL SPECIFICATION

CONSOLE

Cabinet
Detached
Movable

New. 3 Manual cabinet
Oak, matched to sample provided. Walnut interior.
Yes.

Roll top
Manuals

Recessed wheels in base of console and
Pedal Board. With cable storage facility.
Yes, with lock.

Pedal

2, Compass CC to c4, 61 notes. (3rd Man. prepared for)
Naturals and sharps surfaced with plastic.
Simulated tracker touch.

Registration

Compass CCC to G, 32 notes. A.G.O standard, with
light. Maple naturals with plastic sharps.
Controlled by Drawknobs. The intramanual
couplers are controlled by drawknobs placed with
their respective grouping, and the intermanual,
manual to pedal couplers and the MIDI stops
are controlled by tilting tablets placed
above the top manual.

Music rack
Bench
Solid State System

Safety glass music rack with fluorescent light.
Oak, curved bench seat with crank for adjustment.
Matters "Micro Pipe Organ Processor".
This Micro Organ Processor switching/combination
action combines 9 levels of memory, digital player,
transposer, MIDI in and out and RS-280 port, digital
readout for current, crescendo and full organ.

Midi sequencer

Yamaha MDF sequencer

Existing Console

The existing console shall remain the property of
the Purchaser.

ACTION

Chests

The existing Reuter electro-pneumatic chests will
be reused. All chests, primaries shall be releathered.

The new chests will be the Reuter electro-pneumatic
type.


Swell motors

The existing swell motors will be completely
releathered and reused.

Shutter fronts

The existing four (4) shutter fronts will be refurbished
and reused.

Two (2) each for the Great and Swell divisions.



Reservoirs

The existing reservoirs and curtain valves will be completely releathered and reused.
Two (2) additional reservoirs for the 16' Subbass and the 16' Posaune will be new.

Tremolo

A new reservoir mounted tremolo will be installed for the Swell division.

Wind and Power

The present organ blower will be reused. The present blower reservoir will be completely releathered. All other wind conveyances will be reused and new as needed.

3-5-96
new blower
to be provided
take present
blower on
trade.

Wiring/Cabling/Switching

All new to comply with N.E.C. codes.
50 ft of extra cable stored in console base.

ORGAN CHAMBERS

Suitable organ space and chambers to be furnished by the Purchaser. Drawings and details to be provided by the Builder within 90 days of the signing of the contract.

A see letter
6/18/95

FACADE / CASE

~~None provided by the Builder~~ TO BE DETERMINED WITHIN 30
DAYS OF SIGNING (Per FAX DATED 4-20-95 to ARCH) RB

TRANSPORTATION

All dismantling, packing and loading of the present organ by Builder. All transportation from and to the site by Builder. REMOVAL WILL OCCUR AFTER JAN 6, 1996 RB RB

J

TONAL REGULATION

On site tonal regulation will be performed by the Builder.

WARRANTY

The Reuter Organ Company warranty (specimen attached) will apply.

J

GREAT ORGAN (expressive)

		Pipes	
1	16'	Gedeckt (Sw)	— New playing position.
2	8'	Principal	61 Existing
3	8'	Waldflute	61 Existing
4	8'	Dolcan	61 Existing
5	4'	Octave	61 Existing
6	4'	Spillflute	61 New pipes and chest addition.
7	2'	Fifteenth	61 Existing
8	2'	Gedeckt (Sw)	24 Existing
9	IV	Fourniture	244 New toe brd + pipes added to present—
10	8'	Krummhorn	61 New pipes and chest addition. [III Mixture
11	8'	Oboe (Sw)	— New playing position.
12		Chimes	existing

Couplers to Great

13		Great to Great	16'	
14		Great unison off		
15		Great to Great	4'	
16		Swell to Great	16'	
17		Swell to Great	8'	
18		Swell to Great	4'	
19		Choir to Great	16'	Console space prepared for only
20		Choir to Great	8'	Console space prepared for only
21		Choir to Great	4'	Console space prepared for only

SWELL ORGAN (expressive)

		Pipes	
22	16'	Gedeckt	12 Ext. # 23 New playing position.
23	8'	Gedeckt	68 Existing
24	8'	Viola	68 Existing
25	8'	Viola Celeste	56 Existing
26	4'	Principal	68 Existing
27	4'	Rohrflute	68 New pipes and chest addition.
28	2 2/3'	Nasard	61 New pipes and chest addition.
29	2'	Blockflute	61 New pipes and chest addition.
30	1 3/5'	Tierce	61 New pipes and chest addition.
31		Blank	
32	8'	Trumpet	68 Existing
33	8'	Oboe	12 Ext. # 34 New pipes and chest addition.
34	4'	Oboe	68 Existing
35		Tremolo	

Couplers to Swell

36		Swell to Swell	16'
37		Swell unison off	
38		Swell to Swell	4'

*Added:
Swell to Choir 16', 8', 4'*

g

PEDAL ORGAN

		Pipes	
39	32'	Resultant	— New playing position.
40	16'	Principal	32 Existing
41	16'	Subbass	32 New pipes and chest addition.
42	16'	Gedeckt (Sw)	—
43	8'	Octave	12 Ext. #40 Existing
44	8'	Subbass	12 New pipes and chest addition.
45	8'	Gedeckt (Sw)	—
46	4'	Super Octave	12 Ext. # 40 Existing
47	4'	Gedeckt (Sw)	—
48		Blank	
49	16'	Posaune	32 New pipes and chest addition.
50	8'	Posaune	12 Ext. # 49 New pipes and chest addition.
51	4'	Oboe (Sw)	— New playing position.
<u>Couplers to Pedal</u>			
52		Great to Pedal	8'
53		Great to Pedal	4'
54		Swell to Pedal	8'
55		Swell to Pedal	4'
56		Choir to Pedal	8' Console space prepared for only.
57		Choir to Pedal	4' Console space prepared for only.

MIDI

58	Midi 1
59	Midi 2
60	Midi 3
61	Midi 4
62	Midi 5
63	Midi 6
64	Midi 7
65	Midi 8



GENERAL COMBINATION

Pistons adjustable at the keyboard and visibly affecting stop controls.

Eight (8) thumb pistons affecting the Great stops and intramanual couplers.

Eight (8) thumb pistons affecting the Swell stops and intramanual couplers.

Eight (8) toe pistons affecting the Pedal stops only.

Twelve (12) thumb pistons affecting all stops and couplers of the entire organ, duplicated on toe pistons.

General cancel thumb piston.

Setter thumb piston.

REVERSIBLES

Great to Pedal thumb and toe pistons.

Swell to Pedal thumb and toe pistons.

Choir to Pedal toe piston. (Toe piston provided only)

Full Organ thumb and toe pistons.

Cymbelstern toe piston.

PEDAL MOVEMENTS

Register Crescendo Pedal.

Balanced shutter Pedal, for Swell Organ.

Balanced shutter Pedal, for Great and Choir Organ.

MIDI ACCESSORIES

Memory up / Memory down, thumb piston.

Transposer up / down thumb piston.

Pedal to Great thumb piston.

Crescendo read out, thumb piston.

Player, thumb piston.

