

M. P. MOLLER Organ Factory

3124

Pipe Organ No. 9445 Date October 13, 1959
 For FAITH EVANGELICAL LUTHERAN CHURCH, ARLINGTON HEIGHTS, ILLINOIS
 Action Moller's pitman electro-pneumatic Console Detached, electro-pneumatic open level manuals, multiple contact in hardwood to match church furniture
 Casing No. None Finish in hardwood to match church furniture
 Decorations None Motor 3 H.P. - Style 3-P-3027
 Width of Key-bed Standard Stop Controls Draw Knob
 No. Manuals Three Wind Pressure Gt. 3 1/2", Sw., Ch. & Ped. 4"
 To be Completed April 1, 1961 Blower Pipe furnished by Purchaser

PITCH: A-440

SPECIFICATIONS

GENERAL: The organ shall be a distinctive work of the builder, a product of his factory, and in no way an assembled instrument.

GREAT ORGAN (Unenclosed)

1.	16"	Quintade.....	44.....	20 1/2.....	24 zinc.....	S.M..73	pipes
2.	8"	Rohrflöte.....	54.....	21 1/2.....	12 zinc.....	S.M..61	pipes
3.	8"	Salicional.....	50.....	17 1/2.....	12 zinc.....	S.M..61	pipes
4.	8"	Quintaton.....	from #1.....			61 32	notes
5.	4"	Principal.....	58.....	18 1/2.....		S.M..61	pipes
6.	2"	Nachthorn.....	68.....	20 1/2.....		S.M..61	pipes
7.	III Rks.	Fourniture.....	Formula "A".....	17 1/2.....		S.M..183	pipes
8.		Chimes (present Deagan Class "M" with Deagan action and volume control -- in Choir chamber) A to F #22 to #42.....				21	bells
9.		Tremolo					

SWELL ORGAN (Enclosed)

10.	16"	Bourdon.....	42.....	21 1/2.....	24 zinc.....	S.M..73	pipes
11.	8"	Viola.....	54.....	18 1/2.....	12 zinc.....	S.M..61	pipes
12.	8"	Viola Celeste (GG).....	56 @ 8" CC.....	18 1/2.....	5 zinc.....	S.M..54	pipes
13.	8"	Bourdon.....	from #10.....			61	notes
14.	4"	Spitzflöte.....	58-2/3.....	20 1/2.....		S.M..61	pipes
15.	III Rks.	Plein Jeu.....	Formula "B".....	18 1/2.....		S.M..183	pipes
16.	8"	Trompette.....	2-3/4".....	42 1/2.....		61	pipes
17.	4"	Schalmei.....	1-1/4".....			61	pipes
18.		Tremolo					

CHOIR ORGAN (Enclosed)

19.	8"	Gedeckt.....	56.....	20 1/2.....	12 zinc.....	S.M..61	pipes
20.	8"	Erzähler.....	52 1/2.....	17 1/2.....	12 zinc.....	S.M..61	pipes
21.	4"	Koppelflöte.....	64.....	20 1/2.....		S.M..61	pipes
22.	2"	Doublette.....	72.....	18 1/2.....		S.M..61	pipes
23.	II Rks.	Sesquialtera.....	Formula "C".....	halvings as specified...		S.M..122	pipes
24.		Tremolo					

PEDAL ORGAN (Unenclosed)

25.	16°	Violone.....	CCC 38.....	CC 48.....	18 ⁷	29 zinc..	S.M..	56 pipes
26.	16°	Quintade.....	from #1.....					32 notes
27.	16°	Bourdon.....	from #10.....					32 notes
28.	8°	Geigen Principal.....	from #25.....					32 notes
29.	8°	Quintade (Great).....	from #1.....					32 notes
30.	8°	Bourdon (Swell).....	from #10.....					32 notes
31.	4°	Octave.....	from #25.....					32 notes

COUPLERS

32.	Great to Pedal	8°	43.	Swell to Choir	8°
			44.	Swell to Choir	4°
33.	Swell to Pedal	8°			
34.	Swell to Pedal	4°	45.	Great Unison Off	
			46.	Great	4°
35.	Choir to Pedal	8°			
36.	Choir to Pedal	4°	47.	Swell	16°
			48.	Swell Unison Off	
37.	Swell to Great	16°	49.	Swell	4°
38.	Swell to Great	8°			
39.	Swell to Great	4°	50.	Choir	16°
			51.	Choir	4°
40.	Choir to Great	16°			
41.	Choir to Great	8°			
42.	Choir to Great	4°			

ADJUSTABLE COMBINATIONS

(Divisions to be operated independently)

Pistons No. 1-2-3-4-5	Affecting Great Organ
Pistons No. 1-2-3-4-5-6	Affecting Swell Organ
Pistons No. 1-2-3-4-5	Affecting Choir Organ
Toe Studs No. 1-2-3-4	Affecting Pedal Organ, at right
Pistons No. 1-2-3-4-5	General, affecting entire Organ
	(Duplicated by toe studs, at left)
General cancel piston	

ACCESSORIES

Swell expression pedal
 Choir expression pedal
 Crescendo pedal for entire organ, with indicator light
 Great to Pedal Reversible piston, duplicated to pedal
 Swell to Pedal Reversible piston, duplicated to pedal, affecting Swell to Pedal 4° in "off movement" only
 Choir to Pedal Reversible piston, affecting Choir to Pedal 4° in "off movement" only
 Tutti Reversible piston, duplicated to pedal, with indicator light
 Tremolo-celeste-Chimes cut-out for Tutti and Crescendo
 Imported heavy English ivory manual keys
 Castlight for music rack, pedal light

ACCESSORIES (Cont'd)

Separate reservoirs for each wind chest

Swellbox partitions, swellshade actions with separate reservoir wind supply, as required
Electric motor, steel slow-speed Kinetic blower, Orgelectra action current rectifier
of ample capacity

INSTALLATION

The organ shall be assembled and tested at the factory, delivered, installed and finished
in the Church by Moller staff

Great III Rks. Fourniture - Formula "A"

15	12	8
19	15	12
22	19	15
1-24	25-48	49-61

Unison	46	@	8"	CC	17-1/2	1/4	mouth	S. M.
Quint	47	@	8"	CC	17-1/2	1/4	mouth	S. M.

Swell III Rks. Plein Jeu - Formula "B"

22	19	15	12	8
26	22	19	15	12
29	26	22	19	15
1-18	19-30	31-42	43-54	55-61

Unison	47	@	8"	CC	18-1/2	1/4	mouth	S. M.
Quint	48	@	8"	CC	18-1/2	1/4	mouth	S. M.

Choir II Rks. Sesquialtera - Formula "C"

12	12
17	15
1-51	52-61

12th	66-2/3	20-1/2	2/9	mouth	S.M.
17th	73-1/2	18-1/2	1/5	mouth	S.M.
15th	72 @ 8"	CC18-1/2	2/9	mouth	S.M.