

# GENERAL SPECIFICATIONS

## CONSOLE

Attached and built into case, with organist's bench with blocks for adjustment and solid music rack and lockable key desk cover. *FM*

## MANUALS -1

Compass GG, AA, AA#, BB, C1 and F54,58 notes. Naturals surfaced with rosewood, sharps of maple.

## PEDAL

A permanently coupled pedal board, detachable, will be provided by The Reuter Organ Company. Compass CC to G, 32 notes, American Guild of Organists standard, with light.

## REGISTRATION

Controlled by drawknobs made of turned hardwood.

## ACTION

Slider and pallet chests with mechanical key and stop action.

## PITCH

A-440 Hz at 70° F.

## CASEWORK

Casework to enclose the organ as well as cosmetic casework for the facade to be provided by The Reuter Organ Company.

## ORGAN AREA

Suitable, finished area to be furnished by the purchaser.

## WIND AND POWER

An organ blower with motor of ample capacity and a wind muffler device will be provided by The Reuter Organ Company.

## TRANSPORTATION

All transportation of the completed instrument to the purchaser's installation site will be provided by the Purchaser.

## TONAL REGULATION

On-site tonal regulation of the organ will be performed by the tonal staff of The Reuter Organ Company. The Purchaser agrees to provide access to the room and an atmosphere of complete quiet for the period of time required for this work. The Builder will notify the Purchaser of the proposed scheduling of this final procedure.

MANUAL - Unenclosed

Pipes

8' Stopped Flute	(bass)	<del>28</del> 58
	(treble)	<del>30</del>
* 4' Principal	(bass)	28
	(treble)	30
4' Chimney Flute	(bass)	<del>28</del> 58
	(treble)	<del>30</del>
* 2 2/3' Twelfth	(bass)	28
	(treble)	30
* 2' Fifteenth	(bass)	28
	(treble)	30

\* Echo Pedal hitch-down toe lever for stops marked with an asterisk to be located on left side.

PEDAL - Permanently coupled.

