SAME.

TREMOLO

M. P. MÖLLER Organ Factory

1	C) medicazatelaja ikin politikasi kerilandaksi kerilandak		
Pipe Organ No.	R=667	Date September 8, 1960	
For	THE FIRST PRESBYTERIAN CHURCH,	EDINBURG, INDIANA	
Action	Electro-Pneumatic	Console Detached = RSWO	
Casing No.	Supply Case Panel only	Finish To Customer's Selection	
Decorations		Motor Present Motor & Blower. New DC Organ Power Unit	
Width of Key-bed	Standard	_Stop ControlsTilting Tablets	
No. Manuals		Wind Pressure by Sw. 3 " Ted Bourdon 3 2"	
To be Completed.	March 15, 1961	Blower Pipe furnished by Purchaser	
	SPECIFICAT	IONS	
	FOR		
	REBUILDING PRESENT MOLLER ORG	MAN OPUS 2536 - 1918	
CONSOLE	Install new two manual electro-	pneumatic detached tilting tablet	
	type console, or gan bench and p		
MANUAL CHEST	Releather 337 manual pipe pouches. Install 598 new stop action checks and eyelets. Install 244 new duplex shifters. Install two new single stop action rails. Install four new duplex stop action rails. Install new manual chest groove boards. Releather and electrify two 61 note primary stations. Releather and electrify 10 stop action controls.		
OFFSET ACTION	Releather and electrify Great & (front pipe action). Provide p		
CONTACT BOX	Install one new 17 note single 8 Open Diapason #1 to #17 incl.	finger contact box for Great	
CHIMES	Install one set Deagan Class Depneumatic action.	21 Tube Chimes complete with electro-	
PEDAL ORGAN	Releather and electrify 16 Bour Install new pipes and action for		
EXPRESSION	Install new accordian type expr	ession action.	
RESERVOIRS	Releather one 2º-6" x 4º-0" Man Releather one Pedal reservoir (

Install one new electro-pneumatic tremolo.

R=667	THE FIRST PRESBYTERIAN CHURCH, EDINBURG, INDIANA	SHEET 2	
PIPES	Install new tuning slides on the following pipes:		
	Great 8 Gamba - #1 to #12 incl 12 slides		
CABLES	Install new asbestos covered cables between console and organ (12:-O" from (x) in console to (x) in organ).		
CASE PANEL	Install new case panel to enclose present console opening.		
BLOWER	Present blower to be used without change. Supply two new pieces blower base felt 6%-6% long. Supply one set leather couplings. Supply one 8% diam. flexible rubber connection.		
ACTION CURRENT	Install new DC organ power unit of ample capacity.		
CENERAL M. P. Moller, Inc. to supply all labor, materials and necessary to do the work as specified above. Organ i dismantled and all action parts to be returned to the of M. P. Moller, Inc. at Hagerstown, Md. for complete Entire organ to be cleaned, retone regulated and returned.			

	SPECIFICATIONS FOR CONSOLE AND ORGAN		
MANUAL COMPASS PEDAL COMPASS WIND PRESSURE	CC to Ch, 61 notes CCC to G, 32 notes		
PITCH	А-ЦЦО @ 70°F		
	GREAT ORGAN		
1 8 2 8 3 8 4 8	Open Diapasonpresent pipes, present action	Pipes Pipes	
5 4	Flute Traversopresent pipes, present action	Pipes	
	SWELL ORGAN		
7 8 8 8 9 8 10 8 11 4	Gedeckt	Notes Notes Pipes	

R-667

THE FIRST PRESBYTERIAN CHURCH, EDINBURG, INDIANA

SHEET 3

PEDAL ORGAN *

13	16	Bourdon present pipes, present action #1 to
		#30, new pipes, new action #31 & #3232 Pipes
14	16	Lieblich Gedecktfrom #1332 Notes

(*) Pedal Organ playable thru slides in console

COUPLERS

Great to Pedal
Great to Pedal 4
Swell to Pedal
Swell to Pedal L
Swell to Great 16
Swell to Great
Swell to Great 4
Great 16
Great 4
Swell 16
Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3

Pistons No. 1-2-3

Affecting Great and Pedal Stops
Affecting Swell and Pedal Stops
Pistons No. 1-2-3

Affecting Full Organ

PEDAL MOVEMENTS

1 - Great to Pedal Reversible

2 - Balanced Expression Pedal (8 contacts, reverse system)

3 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Action current indicator light (white jewel)

Concave and radiating pedal keyboard

Organ bench with music shelf

Present motor and blower. New DC organ power unit of ample capacity.