M. P. MÖLLER Organ Factory

Rev. 5/6/71 Rev. 4/10/71

Pine Organ No.	R-823	Date May 26, 1969 Rev. 1/28/70
For	SECOND PRESBYTERIAN CHURCH,	
Action	Electro-Pneumatic	Console Present - Detached
Casing No	None	Finish No Change
	None	Motor Pres. motor & blower. New DC Organ
Width of Key-bed	Standard	Stop Controls Draw Knobs & Tilting Tablets
		Wind Pressure
To be Completed		Blower Pipe furnished by Purchaser
	CONTRACTOR A F	M7A 9.7A

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 8156 - 1950

CONSOLE

Rebuild present three manual draw knob console, pedal keyboard and organ bench as follows:

Install new engraved draw knobs as necessary to conform to revised specification dated 4/10/71.

Install new silver contacts on all stops and couplers. Provide extra contacts for station cutouts. Regulate and clean all coupler contacts. Clean crescendo and expression contacts. Recover 24 coupler pneumatics. Recover 5 master combination pneumatics and primaries.

Recover 5 master combination pieumatics and primaries. Recover 6 reversible pneumatics.

Recover o reversible pneumatics.

Releather 30 note primary station.

Clean, rebush and regulate combination action.

Refelt and adjust manual keys to four ounce touch.

Refelt console action.

Install new plexiglas music rack with fluorescent light.

Install new pedal light

Install back gest on organ bench.

Install new pedal key caps.

Rework Swell and Choir expression shoes for 7 contacts, reverse system.

Refelt pedal keyboard completely.

Refinish console cabinet, pedal keyboard, organ bench, etc. according to color block to be supplied.

MANUAL CHESTS

Discard present four rank Great Organ main chest. Install three new Great Organ exposed main chests. Rework present 8 Diapason action for 2 Flute - 61 pipes. Rework present 8 Viola action for II Zimbel - 122 pipes. Rework present Swell 8 Oboe action to play 16 Fagot TC. Releather 1216 manual pipe pouches. Install 1266 new stop action checks and eyelets. Install 128 new duplex shifters. Releather three 73 note primary stations. Releather 19 stop action primaries. Releather 44 note Pedal Rohrflöte primary. Releather 32 note Pedal Trompette primary. Install 314 new magnet plugs and armatures.

OFFSET ACTIONS Releather Swell 16 Rohrbourdon action #1 to #12 and install new magnet plugs and armatures. Releather Swell 2 Flute action #1 to #6 and install new magnet plugs and armatures.

CONTACT BOXES

Releather 73 note Contact Box for Swell Organ and install new silver wire contact blocks.

RELAYS

Install one new 61 note relay for Great Organ.

SWITCHES

Releather 13 switch pneumatics.

Releather 13 switch primaries and install new magnet plugs and armatures.

Install 6 new switches with stop actions for Great Organ. Install 1 new switch with stop action for Choir Organ.

PEDAL ORGAN

Releather 16 Principal action #1 to #56 and install new magnet plugs and armatures, Releather 16 Subbass action #1 to #44 and install new magnet plugs and armatures.

Releather 16 Contre Trompette action #1 to #12 and install new magnet plugs and armatures. Releather 10 pedal relay switch pneumatics.

EXPRESSION

Install new expression shades and actions as required for Swell Organ.

Install new expression shades and actions as required for Choir Organ.

RESERVOIRS

Recover the following reservoirs and install new curtain valves as required.

One (1) 3'-6" x 3'-6" Blower Reservoir

One (1) 2'-0" x 4'-0" Great Manual Reservoir

One (1) 3'-0" x 6'-0" Swell Manual Reservoir

One (1) 3'-0" x 4'-0" Choir Manual Reservoir

Three (3) l'-6" x 2'-6" Pedal Reservoirs

One (1) 2'-0" x 3'-0" Pedal Reservoir

One (1) 1'-6" x 2'-0" Pedal Reservoir

One (1) Console Reservoir

Install two new electro-pneumatic tremolos. TREMOLOS

Install the following new pipes: PIPES

	Great	. 8	Principal	esh	61	pipes
	Great	8	Spitzflöte	cro	61	pipes
	Great	4	Octave	639	61	pipes
	Great	4	Spillflöte	CO	61	pipes
	Great	2	Flachflöte	•	61	pipes
	Great	8	Trompete (1/2 length)	•		pipes
	Great	III-IV	Mixture	-	220	pipes
	Great	II	Sesquialtera TC	00	98	pipes
CM	Swell	2	Principal	600		pipes
Cy	Swell	II	Zimbel	0		pipes
	Pedal	16	Principal	-	56	pipes

Revoice the following pipes:

Swell	16	Fagot TC -	61	present 8 Oboe pipes
Swell	8	Trompette	•	73 pipes
Swell	4	Clarion	420	73 pipes
Pedal	16	Contre Trompette	40	12 pipes
Choir	1-1/3	Quintflöte - 49	pre	sent 2-2/3 Nasard pipes 13-61

CABLES

Install new plastic covereicables between console and organ.

Install new action current wires between console, organ and power unit.

BLOWER

Present blower and motor to be used without change.

ACTION CURRENT Install newcorgan power unit of ample capacity.

GENERAL

Entire organ to be returned to the factory of M. P. Moller, Inc. at Hagerstown, Maryland for rebuilding as specified above. M. P. Möller, Inc. to supply necessary support work for exposed work; case paneling by customer. Present Great 2-2/3 Twelfth and Great 2 Fifteenth pipes are to be carefully crated and stored at church for future use as Pedal II Rauschquinte.

* * * * * * * * * *

SPECIFICATIONS FOR CONSOLE AND ORGAN

WIND PRESSURE PITCH

MANUAL COMPASS CC to C4, 61 notes
PEDAL COMPASS CCC to G, 32 notes

A-440 @ 70°F

GREAT ORGAN (exposed)			
1	8	Principal	
2	8	Spitzflöte	
3	4	Octave	
4	4	Spillflöte	
5	2	Flachflöte	
6	II	Sesquialtera TCnew pipes; new action98 pipes	
7	III-IV	Mixturenew pipes; new action	
8 8a	8	Trompete (1/2 Lgth) new pipes; new action Couble Trebles	
		SWELL ORGAN	
9	16	Rohrbourdon	
10	8	Rohrflötefrom #9	
11	8	Gamba73 pipes	
12	8	Gamba Celeste TCpresent pipes; present action61 pipes	
13	4	Principal	
14	4	Flute Triangulairepresent pipes; present action73 pipes	
15	2	Place. f./29eo/etpresent Flautino pipes; present	
		Diapason action	
16	III	Plein Jeupresent pipes; present action183 pipes	
17	16	Fagott TCpresent 8 Oboe pipes; present 8 Oboe	
		action	
18	8	Trompettepresent pipes; present action73 pipes	
19	4	Clarion73 pipes	
20		Blank Draw Knob	
21		Tremolo	
		CHOIR ORGAN	
22	8	Gedecktpresent pipes; present action73 pipes	
23	8	Dulciana73 pipes	
24	8	Unda Maris TCpresent pipes; present action61 pipes	
25	4	Spitzflöte73 pipes	
26	2	Principal	
27	1-1/3	Quintflötepresent 2-2/3 Nazard pipes #13 to #61; present 2-2/3 Nazard action	
28	II	Zimbell22 pipes	
29	8	Clarinetpresent pipes; present action73 pipes	
30		Blank Draw Knob	
31		Tremolo	
		Zmbelstern	
		16 10	
		g .	

PEDAL ORGAN (*)

32	16	Principalnew pipes; present 16 Diapason action, #1-12, present 8 Principal action
33	16	Subbasspresent 16 Bourdon pipes; present
		16 Bourdon action
34	16	Rohrbourdonfrom #9
35	8	Octave
36	8	Bassflötefrom #33
37	8	Rohrflötefrom #9
38	4	Choralbassfrom #3232 notes
39	4	Flutefrom #9
40	III	Mixtureprepared for in console only
41	16	Contre Trompette1-12 present pipes, present action,
		20 from #18
42	8	Trompettefrom #18

(*) Pedal Organ playable thru present Pedal Relay and Switches

				COUPLERS	(no change)	
43	Great t	o Pedal		55	Great	16
44		o Pedal	4	56	Great	Unison Off
45	Swell t	o Pedal		57	Great	4
46	Swell t	o Pedal	4	58	Swell	16
47	Choir t	o Pedal		59	Swell	Unison Off
48	Choir t	o Pedal	4	60	Swell	4
49	Swell t	o Great	16	61	Swell	to Choir 16
50	Swell t	o Great		62	Swell	to Choir
51	Swell t	o Great	4	63	Swell	to Choir 4
52	Choir t	o Great	16	64	Choir	16
53	Choir t	o Great		65	Choir	Unison Off
54	Choir t	o Great	4	66	Choir	4

ADJUSTABLE COMBINATIONS (no change)

Pistons No	. 1-2-3-4-5-6	Affecting Great Organ
Pistons No	. 1-2-3-4-5-6	Affecting Swell Organ
Pistons No	. 1-2-3-4-5-6	Affecting Choir Organ
Pistons No	. 1-2-3-4-5-6	Affecting Pedal Organ
Pistons No	. 1-2-3-4-5-6	Affecting Full Organ (duplicated by toe studs)

PEDAL MOVEMENTS (no change)

1 - Great to Pedal Reversible (duplicated by manual piston)
2 - Swell to Pedal Reversible duplicated by manual piston)
3 - Choir to Pedal Reversible (duplicated by manual piston)
4 - Balanced Expression Pedal - Swell Organ with indicator light (7 contacts, reverse system)
5 - Balanced Expression Pedal - Choir Organ with indicator light (7 contacts, reverse system)
6 - Balanced Crescendo Pedal with indicator light
7 - Sforzando Reversible (duplicated by manual piston) with indicator light
8 - Jimbelstein Reversible (by the stud only) with visible sotating star

ACCESSORIES

Plexiglas music rack with fluorescent light Pedal light

Present concave and radiating pedal keyboard
Present organ bench with music shelf with new back rest

Present motor and blower
New DC organ power unit of ample capacity

RHM/mr 10-17-69 Revised 2/6/70 Revised 2/18/71 Revised 4/20/71 Revised 5/6/71