

M. P. MOLLER Organ Factory

2/6

H6N

Pipe Organ No. R-194 Date February 2, 1988
For ST. PAUL'S LUTHERAN CHURCH, LEITERSBURG, MARYLAND
Action Electro-Pneumatic Console Present-Detached
Casing Present-Case & Grilles Finish Present
Decorations None Motor Present $\frac{1}{2}$ HP, Style 2P 1716
Width of Key-bed Standard Tracker Touch Yes No X
Keys to be Present Stop Controls Stop Keys
No. Manuals TWO AND PEDAL Wind Pressure 4"
To be Completed September 1, 1988 Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN

OPUS 6677 - 1938 33174
U

CONSOLE

Reuse present console rebuilding as follows:

Install new manual Key jambs and Key slips.

Install new stop keys and contacts.

Replace all piston buttons and springs.

Recover combination pneumatic and primary and
install new magnet armatures.

Replace crescendo and expression pedal pads and
edging. *Replace existing contacts with new under Key contacts*

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating
tips.

Recover reservoir.

Recover rolltop.

Clean and polish console cabinet, bench and pedal
keys.

MANUAL CHESTS

Recover all manual pipe pouches.

Recover primaries and install new magnet armatures.

OFFSET CHESTS

Recover 12 note 8 Principal action and install new
magnet armatures.

Install new actions as required for additions.

CHIMES

Install new electric actions and canopy for present
bells.

SWITCHES

Install new solid state switches as required.

PEDAL ORGAN

Recover 12 note 16 Bourdon action and install new
magnet armatures.

EXPRESSION

Recover one 8 note and one 4 note action and
install new magnet armatures.

Recover all shade pneumatics.

Replace all shade jacks and connecting rods.

Refelt shades.

Paint swell enclosure Charcoal Brown.

RESERVOIR Recover the following reservoirs and install new curtain valves.

One 2-6 x 4-0 manual
One 1-6 x 2-0 pedal
One expression

TREMOLO Install new electro-pneumatic tremolo.

PIPES Install new pipes as indicated by organ specifications.
Revoice all pipes being reused.
Repack all wood pipe stoppers.
Install slide tuners as required.

CABLES Install new plastic covered cables between console and organ.
Install new action current wires between console, organ, and DC organ power unit.

ACTION CURRENT Install new 10-15 volts DC organ power unit.

BLOWER Reuse present _ HP, Style ____ motor and blower without change.
Install new 6" diameter flexible connection with draw bands.

ORGAN CASE Reuse present organ case and grilles without change.
Replace present fabric with aluminum screen.
Extend display pipe feet for better appearance.

GENERAL All parts specified above to be rebuilt to be returned to the factory of M. P. Moller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Moller, Inc.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS	CC to C4, 61 notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	4"
PITCH	A-440 @ 70 degrees F

GREAT ORGAN - Enclosed with Swell

1.	8	Principal.....#1-73 present Open Diapason pipes & action, #74-85 new pipes & action.....85 pipes
2.	8	Holzgedackt.....from #10.....61 notes
3.	8	Viole.....from #11.....61 notes
4.	4	Octave.....from #1.....61 notes

GREAT ORGAN (Continued)

5.	4	Lieblich Flote.....from #10.....61 notes
6.	2	Waldflote.....from #10.....61 notes
7.	II	Sesquialtera TC....console only
8.	8	Schalmei.....from #19.....61 notes
9.		Chimes....present Deagan "M" bells, new electric action with canopy, transformer, relay & volume control; A to F, #22-42.....21 bells

SWELL ORGAN - Enclosed

10.	8	Holzgedackt...present Lieblich Gedeckt pipes & action.....85 pipes
11.	8	Viole.....present Viole Dolce pipes & action.....73 pipes
12.	8	Viole Celeste TC...(inventory pipes & action)..49 pipes
13.	4	Lieblich Flote.....from #10.....61 notes
10.	4	Octave Viole.....from #11.....61 notes
15.	2	Principal.....from #1.....61 notes
16.	1-1/3	Quintflote....from #10...(repeat top notes)....61 notes
17.	1	Zimbel.....from #10...(repeat top octave)....61 notes
18.	16	Bassoon TC.....from #19.....49 notes
19.	8	Schalmei.....present Oboe pipes & action.....61 pipes
20.	4	Clairon.....from #19...(repeat top octave)....61 pipes <i>notes</i>
21.		Tremolo (jamb switch)

*PEDAL ORGAN

22.	16	Bourdon.....12 present pipes & action; 20 from #10.....32 notes
23.	8	Principal.....from #1.....32 notes
24.	8	Gedackt.....from #10.....32 notes
25.	4	Octave.....from #1.....32 notes

*Pedal Organ playable thru solid state
switches in organ.

COUPLERS - no change

26.	Great to Pedal
27.	Swell to Pedal
28.	Swell to Great

ADJUSTABLE COMBINATIONS - no change

Pistons No. 1-2-3-4

Affecting Full Organ

PEDAL MOVEMENTS - no change

Balanced Expression Pedal - Entire Organ

Balanced Crescendo Pedal with indicator light

ACCESSORIES

Concave, radiating pedal clavier
Organ bench with music shelf
Present music rack with light
Pedal light
New DC organ power unit
Present motor and blower

JH/jm
4-6-88