M. P. MÖLLER Organ Factory

Pipe	Organ No	7508	Date October 10, 1946		
For_		FIRST BAPTIST CHURCH,	BAXLEY, GEORGIA		
Actio	n	ectro-pneumatic	Console_Detached - Walnut		
Casing No. None Finish None Model As per Sample Finish H.P., Style 3-P-2724					
Decorations Motor H.P., Style 3-P.					
Width of Key-bedStandardStop Controls_Stopkeys					
NT.	N / 1	Two	Wind Pressure 4½"		
To b	e Comple	As soon as possible	Blower Pipe furnished by Purchaser		
PITCH: A-440 SPECIFICATIONS The church is to provide suitable space for the organ. The existing space is satisfactory, except that the height must be raised from the present of 9'7" to 10'7" flat ceiling. As this increased height will place the organ chamber ceiling close to the roof of the church, it will be necessary for the church to install double heavy insulation above the ceiling, to protect the organ from heat and cold. All preparations to be made at the church's expense from plans by M. P. Moller, Inc.					
		GREAT ORGAN	V (Enclosed with Swell)		
1 2 3 4 5 6 7 8	8' 8' 8' 4' 4' 2-2/3'	Viol Dolce (Unit)56. Flute HarmonicFrom # Viol Dolce OctaveFrom # Viol TwelfthFrom #	.12 Zinc S.M		
		SWELL ORGAN	(Enclosed)		
9 10 11 12 13 14 15 16	8' 8' 4' 2-2/3' 2' 8'	Concert Flute	.12 ZincS.M73 Pipes nsole only) #2		
		PEDAL ORGAN			
17 18 19 20 21	16' 16' 8' 8' 4'	FluteFrom # GambaFrom #	#17		

COUPLERS

22	Great to Pedal	29	Swell 16'
23	Great to Pedal 4'	30	Swell Unison
24	Swell to Pedal	31	Swell 4'
25	Swell to Pedal 4'	32	Great 16'
26	Swell to Great 16'	33	Great Unison
27	Swell to Great	34	Great 4'
28	Swell to Great 4'		

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4 Pistons No. 1-2-3-4 Affecting Swell and Pedal Stops Affecting Great and Pedal Stops

PEDAL MOVEMENTS

Balanced Expression Pedal Balanced Crescendo Pedal Great to Pedal Reversible

ACCESSORIES

Crescendo Indicator (light)
Organ Bench with Music Compartment
Concave, Radiating Pedal Clavier
Electric motor, blower and action current generator of ample capacity.

JHH:DH 6/18/47