W. Zimmer & Sons



Exhibit A

SPECIFICATION

2/7/78

of new tracker organ for First United Presbyterian Church, Elgin, Illinois

Great: 65mm	2. 3. 4. 5. 6. 7.	Principal Gedackt Octave Koppelflöte Flachflöte Sesquialter II I Mixture III-IV Trompete	8' 8' 4' 4' 2'	56 56 56 56 56 88 212 56	Pipes. " " " " " " "	
Swell:		Rohrflöte	81		Pipes.	
		Streichflöte	8 •	44		from #9
60mm		Hohlflöte	4 1	56	11	
		Principal	2'	56		
		Nasat	1 1/3'	56	t)	
		Zimbel III		168	f)	
	-15.	Chalumeau	16'	56	99.7	
	16.	Hautbois	81	56	11	
	17.	Tremolo				
Pedal:	18.	Subbass	16'	30	Pipes.	•
		Offenbass	8'	30	11	
70mm	20.	Choralbass	4'	30	61	
	21.	Rauschpfeife II		60	H	
		Fagott	16'	30	H	
Couplers:	24.	Swell to Great Swell to Pedal Great to Pedal				

Action:

Fully mechanical note and stop action with slider chests and built-in console.

Casework:

Complete free-standing organ case. A design drawing will be submitted for consideration and approval.

Accessories:

- 1. Balanced Swell Pedal.
- 2. Key-switch for blower.
- 3. Pedalboard illumination.
- 4. Organist's bench with height adjustment blocks, and backrest.
- 5. Existing chime tubes to be used again but with entirely new electric action, playable from Great manual, and 5-stage volume switch.
- 6. Organ casework of oak to match church pew finish.