# M. P. MÖLLER Organ Factory

	с наширия пер наменя принципания дене пре
Pipe Organ No	R-699 Date October 10, 1962 Rvd. Jan.1, 196
	T ÛNITED PRESBYTERIAN CHURCH, BUTLER, PENNA.
THE RESERVE OF THE PROPERTY OF	Pneumatic Console Detached-Present Rebuilt
	mge To Gustomer's Selection
Decorations No Ch	
Width of Key-bed_	마이크리아 아이들은 아이들의 아이들의 아이들의 아이들의 아이들의 아이들의 아이들의 아이들의
No. Manuals Th	
To be Completed	April 7, 1963 Blower Pipe furnished by Present
	SPECIFICATIONS
	FOR
	7: 17: 7 - 1 3/37 - 0 20-0 70-6
	Rebuilding Present Moller Organ Opus 7440 - 1946
CONSOLE	Rebuild existing console as follows:
	Recover 21 coupler pneumatics.
	Recover 6 reversible pneumatics.
	Recover switch pneumatics.
	Recover 5 Master Combination pneumatics and primaries.
	Releather 27 note primary and install new magnet plugs & armatures. Clean silver contacts and replace as required.
	Dismantle combination action, clean and reinstall.
	Burnish present manual keys and draw knobs.
	Refelt manual keys.
	Refelt console action.
	Clean console mechanism and replace fire damaged parts as required
	Install new roll top.
	Install new music rack.
	Install new veneer on cheeks.
	Repair console cabinet as required and refinish.
	Refinish organ bench.
	Refelt pedal keyboard. Refinish pedal key frame and keys.
	Supply new console reservoir.
	Supply 6 lin ft 4" diam flexaust for console.
MANUAL CHEST	Releather 1125 manual pipe pouches.
LIVINOVI OUEDI	Install 1021 new stop action checks and eyelets.
	Install 61 new duplex shifters.
	Releather 16 stop action primaries.
	Releather 159 unit primaries.
	Releather one 61 note and two 73 note primary stations.
	Install 414 new magnet plugs and a rmatures.

OFFSET ACTIONS

Releather the following offset actions and install new magnet plugs and armatures:

Gre	at 8	Diapason - #1 to #9 incl.	-	Notes	
Gre	at 8	Gemshorn - #1 to #6 incl.	6	Notes	
Swe	11 16	Lieblichbourdon - #1 to #97 incl.	97	Notes	
Cho	ir 8	Harmonic Flute - #1 to #5 incl.		Notes	
Cho	ir 8	Dulciana - #1 to #5 incl.	5	Notes	
Cho		Nazard - #1 to #6 incl.	6	Notes	

CONTACT BOXES

Releather 61 note contact box for Great Organ and install new silver wire contact blocks. Releather 73 note contact box for Swell Organ and install new silver wire contact blocks. Releather 73 note contact box for Choir Organ & install new silver wire contact blocks.

SWITCHES

Install the following new electro-pneumatic switches with stop action:

0 1	0	D.	119 4	- 400	dwall .	20	Notes
Great	8	Diapason			incl.	100	
Great	8	Gemshorn			incl.		Notes
Great	4	Harmonic Flute	#1 t	0 #61	incl.	61.	Notes
Great		Chimes	#1 t	o #21	incl.	21	Notes
Swell	16	Lieblichbourdon	#1 t	o #73	incl.	73	Notes
Swell.	8	Stopped Flute	#1 t	0 #73	incl.	73	Notes
Swell	4	Lieblichflöte	#1 t	o #73	incl.	73	Notes
Swell	2	Flautino	#1 t	io #61	incl	61	Notes
Swell	4	Schalmei	#1 t	o #61	incl.	61	Notes
Choir	8	Harmonic Flute	#1 t	o #73	incl.		Notes
Choir	8	Dulciana	#1 1	to #73	incl.	73	Notes
Choir	4	Flute Harmonic	#1 1	io #73	incl.	73	Notes
Choir	4	Dulciana	#1 t	o #73	incl.	73	Notes
Choir	2-2/3	Nazard	#1 1	to #6	incl.	61	Notes
Choir	2-2/3	Dulciana	#1 1	to #61	incl	61	Notes
Choir	2	Dulciana	#1 1	to #61	incl.	61	Notes

CHIMPS

Releather and refelt 21 note action and install new magnet plugs and armatures. Install 21 new chime pneumatics. Install 21 new chime mallets.

PEDAL ORGAN

Releather 16 Diapason action #1 to #12 incl. & install new magnet plugs and armatures. Releather 16 Bourdon action #1 to #hh incl. and install new magnet plugs and armatures. Releather 8 Octave action #1 to #www incl. and install new magnet plugs and armatures. Install new 32 note Pedal Relay with eight 32-note switches.

EXPRESSION

Releather 24 note Great-Choir expression action and install new magnet plugs and armatures.
Releather 18 note Swell expression action and install new magnet plugs and armatures.
Recover 42 shade and bumper pneumatics.
Install 42 new sets shade jacks and connecting rods.
Supply additional swell box as required.

RESTRVOIRS

Recover the following reservoirs and install new curtain valves as required:

One (1) 2:-0" x h:-0" Great Manual Reservoir
One (1) 2:-6" x h:-0" Swell Manual Reservoir
One (1) 2:-6" x h:-0" Choir Hanual Reservoir
Two (2) 1:-6" x 2:-0" Pedal Reservoir
One (1) 1:-6" x 2:-6" Pedal Reservoir

Two (2) Expression Reservoirs

One (1) Chime Reservoir

One (1) 3'-6" x 3'-6" Blower Reservoir

TREMOLOS

Install there new electro-pneumatic tremolos.

PIPES

Install the following new pipes:

	•	".	10	7.1
Great	g	Rohrflote		Pipes
Great	4	Octave		Pipes
Great	II	Rauschquinte	122	Pipes
Swell	16	Lieblichbourdon	97	Pipes
Swell	III	Scharf	183	Pipes
Swell	8	Trompette	73	Pipes
Swell	4	Schalmei	61	Pipes
Choir	2-2/3	Nazard	61	Pipes
Pedal	16	Bourdon	Lik	Pipes

Revoice present Choir 8 Clarinet 73 Pipes
Install modern tuning slides on all present pipes.

CABLES

Install new plastic covered cables between console and organ.

BLOWER

Present motor and blower to be used without change.
Install four new coupling leathers on present blower.

ACTION CURRENT

Install new 50 ampere DC organ power unit with air mercury switch.

GENERAL

The entire organ to be returned to factory of M.P.M, Inc. in Hagerstown. Md. for rebuilding as specified above.

# SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH	CC to Ch, 61 Notes CCC to G, 32 Notes Gr. & Ch. h", Sw. 5", Ped. h" A-hho @ 70°F
	CREAT ORGAN 6
1 8 8 8 8 4 4 5 4 5 7 II	Diapasonpresent pipes; present action
	SWELL ORGAN 9
10 16 11 8 12 8 13 8 14 4 15 4 16 2 17 III 18 8 19 4 20	Lieblichbourdon (unit)new pipes; present action
	CHONE ORGAN 5
21 8 22 8 23 8 24 4 25 4 26 2-2/3 27 2-2/3 28 2 29 8	Harmonic Flute (unit)present pipes; present action

# PEDAL ORGAN (\*) 2

31	16	Diapasonpresent pipes; present action #1 to #12;
32	16	Bourdon
33	16	Lieblichbourdonfrom #10
34	8	Octavepresent pipes; present action
35	8	Bourdon32 Notes
36	8	Stopped Flute32 Notes
37	4	Super Octavefrom #3432 Notes
38	4	Flute Harmonic32 Notes

(\*) Pedal Organ playable thru new Pedal Relay and switches being supplied by MPM. Inc.

## COUPLERS

39	Great					51	Great			
40	Great	to	Pedal	4		52	Great	4		
41			Pedal			53	Swell	16		
42			Pedal			54	Swell	h		
43			Pedal			55			Choir	16
14			Pedal			56	Swell.	to	Choir	
45			Great	- 1750 -		57	Swell	to	Choir	4
46	Swell	to	Great			50	Choir	16		
47	Swell	to	Great	4		59	Choir	4		
48			Great							
49			Great							

### ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5-6	Affecting Great Stops
Pistons No. 1-2-3-4-5-6	Affecting Swell Stops
Pistons No. 1-2-3-4-5-6	Affecting Choir Stops
Pistons No. 1-2-3-4-5-6	Affecting Pedal Stops
Pistons No. 1-2-3-4-5-6	Affecting Full Organ (duplicated by toe studs)
General Cancel Piston	

### REDAL MOVEMENTS

1- Great to Pedal Reversible

Choir to Great L

50

- 2- Swell to Pedal Reversible
- 3- Choir to Pedal Reversible
- 4- Balanced Expression Pedal for Great-Choir Organ (24 contacts, regular system)
  5- Balanced Expression Pedal for Swell Organ (18 contacts, regular system)
- 6- Balanced Crescendo Pedal with indicator light (green jewel)
- 7- Sforzando Reversible (duplicated by manual piston) with indicator light (red jewel)

### ACCESSORIES

Present signal lights and buttons for East Hall, Narthex and A.V.Room On-Off switch for Chancel shades.

Present Music rack light.

Present pedal light. Present electric clock.

Present concave and radiating pedal keyboard.

Present organ bench with music shelf.

Present motor & blower. New DC organ power unit with air mercury switch.

10/18/62 Rev. 1/4/63 RHM/bw