M. P. MÖLLER Organ Factory

Pipe Organ No	R-171	DateMay 30, 1985
For	FIRST BAPTIST CHURCH, LANCASTER,	
Action	Electro-Pneumatic	Console Present - Detached
		Finish No change
Decorations	None	Motor Present 3 H.P., Style 3-P-3027
Width of Key-bed		Stop ControlsTilting Tablets
No. Manuals	TWO AND PEDAL	Wind Pressure See Scale Sheet
To be Completed_	March 15, 1986	Blower Pipe furnished by Purchaser
10 be completed.		. Dio not 1 ipo tatitonea oj

SPECIFICATIONS

FOR

REBUILDING, CHANGING TONALLY, AND ADDING TO PRESENT MOLLER ORGAN OPUS 8678 - 1954 36093

CONSOLE

Reuse present console rebuilding same as follows:

Replace all stop and coupler controls and contacts.

Replace all piston buttons and springs.

Recover all coupler pneumatics. Recover combination pneumatic.

Recover all primaries and install new magnet armatures.

Recover reversible actions.

Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating tips.

Recover reservoir. Recover roll top.

Install toe levers to duplicate Full Organ pistons.

Install jamb switch for Great 4 coupler.

Install new markers.

Clean and polish cabinet, bench and pedal keyboard.

PITMAN CHESTS

Recover all manual pipe pouches.

Replace stop action checks and eyelets.

Recover two 61 note primary stations and install new magnet armatures Recover stop action primaries and install new magnet armatures.

Recover pedal primary for Swell Trompette #1-44.

Rework and/or install new toeboard/rackboard assemblies as required

for tonal changes.

Install new actions as required for additions.

R-171 FIRST BAPTIST CHURCH, LANCASTER, SOUTH CAROLINA,

PAGE 2

OFFSET & UNIT ACTIONS

Recover the following actions and install new magnet armatures:

Great 8 Principal #6-9 Swell 8 Rohrflöte #1-73

Rework and/or install new toeboard/rackboard assemblies as required for tonal changes.

Install new actions as required for additions.

SWITCHES

Install new electro-pneumatic switches with diodes as required.

PEDAL ORGAN

Recover the following actions and install new magnet armatures:

16 Subbass44 notes16 Gedacktbass12 notes16 Posaune12 notes

Install new electro-pneumatic switches with diodes as required.

EXPRESSION

Recover one 4 note and one 12 note action and install new magnet armatures.

Recover all shade pneumatics.

Replace all shade jacks and connecting rods.

Refelt shades.

Eliminate shades and action from Great Organ.

RESERVOIRS

Recover the following reservoirs and install new curtain valves as required:

Two 2-6 x 4-0 manual
One 1-6 x 2-6 pedal
Two 1-6 x 2-0 pedal
One expression
One 3-0 x 3-0 blower

TREMOLOS

Install new electro-pneumatic tremolos.

PIPES

Install new pipes as indicated by organ specifications. Revoice all pipes being reused.

Repack all wood pipe stoppers.
Install slide tuners as required.

CABLES

Install new plastic covered cables between console and organ. Install new action current wires between console, organ, and DC organ power unit.

ACTION CURRENT

Install new 10-15 volts, 30 amperes DC organ power unit.

BLOWER

Reuse present 3 HP, Style 3-P-3027 motor and blower without change.

Install new motor-blower coupling leathers.

Install new 12" diameter flexible connection with draw bands.

GENERAL

All parts specified above to be rebuilt to be returned to the factory

of M. P. Moller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Moller. Inc.

SPECIFICATIONS FOR CONSOLE AND ORGAN

GREAT ORGAN - Unenclosed

1	8	Principalnew pipes, #1-5 new action, #6 up		
2	0	present Diapason action		
2,	8	Gedacktpresent Sw. Gedeckt pipes; present Rohrflöte action		
3	8	Gemshorn#1-12 present Dulciana pipes, #13 up present		
		Unda Maris TC pipes; present action61 pipes		
4	8	Gemshorn Celeste TCpresent Dulciana #13 up pipes;		
		present action49 pipes		
5	4 4	Octavenew pipes; present action		
6 7		Rohrflöte		
8	2-2/3 2	Nasat		
9	1-3/5	Blockflötenew pipes and action		
10	III-IV	Terz TC49 pipes		
		Mixturenew pipes; present III Mixture action214 pipes		
11 12	8	Trompete61 pipes		
13		Tremolo(by jamb switch)		
13		Chimespresent bells and action (by volume control)25 bells		
SWELL ORGAN - Enclosed				
14	8	Rohrflötepresent Gr. Rohrflöte pipes; present		
7.7	0	Gedeckt action		
15	8	Viole de Combe procent pines and action 61 pines		
16	8	Viole de Gambepresent pipes and action		
17		Viole Celeste TCpresent pipes and action		
18	4 2	Spitzflötenew pipes; present Octave Geigen action61 pipes		
10	2	Principal#1-48 present 4 Octave Geigen pipes #13-60,		
19	1-1/3	#49 up new pipes; new action		
20	III-IV	Quint		
21		Scharf213 pipes		
	16	Dulziannew pipes and action		
22	8	Trompettepresent pipes and action		
23	8	Dulzianfrom #21 (playable by 16 - Both - 8 switch)61 notes		
24		Tremolo		
		* PEDAL ORGAN		
		I LIDAL ORGAN		
25	16	Subbass44 pipes		
26	16	Gedacktbass12 present Lieblich Gedeckt pipes		
		and action; 20 from #1432 notes		
27	10-2/3	Quintfrom #26 & 14		
28	8	Principalpresent Gr. 8 Diapason pipes #1-12,		
		present Gr. 4 Octave pipes #13 up; new action44 pipes		
29	8	Subbassfrom #25		
30	4	Octavefrom #28		
31	v	Mixturepresent Gr. 8 Diapason & III Mixture pipes;		
-		new action		
32	16	Posaune12 present Sub Trompette pipes and action;		
J-		20 from #22		
1		20 210/11 22 110 000		

(continued)

R-171 FIRST BAPTIST CHURCH, LANC	ASTER, SOUTH CAROLINA PAGE 4			
* PEDA	L ORGAN (continued)			
of the state of th				
* Pedal Organ playable thru new switches.				
COU	PLERS			
Great to Pedal Swell to Pedal Swell to Great 16 Swell to Great Swell to Great	41 Great 4 (by jamb switch) 42 Swell 16 43 Swell Unison Off 44 Swell 4			
ADJUSTABLE COMBINATIONS				
Pistons No. 1-2-3-4-5 Pistons No. 1-2-3-4-5 Pistons No. 1-2-3-4-5	Affecting Great and Pedal Affecting Swell and Pedal Affecting Full Organ (duplicated by new toe levers)			
General Cancel				

PEDAL MOVEMENTS

Great to Pedal reversible (duplicated by manual piston) Swell to Pedal reversible (duplicated by manual piston) Tutti reversible (duplicated by manual piston) with indicator light Balanced Expression Pedal with indicator light - Swell Organ Balanced Expression Pedal with indicator light - Unused Balanced Crescedndo Pedal with indicator light

ACCESSORIES

Concave, radiating pedal clavier Organ bench with music shelf Music rack with light Present motor and blower New DC organ power unit Nave shades "On-Off" pistons

RVK/mr 12/3/85