

M. P. MÖLLER Organ Factory

2/19

Pipe Organ No. 11285 Date December 22, 1977
 For ST. PAUL'S R. C. CHURCH, BLOOMER, WISCONSIN
 Action Moller's Pitman Electro-Pneumatic Console Detached
 Casing No. None Finish As Per Sample
 Decorations None Motor Present motor & blower shall be
 Width of Key-bed Standard Stop Controls Tilting Tablets
 No. Manuals TWO Wind Pressure 3"
 To be Completed July 15, 1978 Blower Pipe furnished by Purchaser

PITCH: A-440

SPECIFICATIONS

Style M-5200 C

GENERAL: The organ shall be a distinctive work of the builder, a custom product of his factory, in no way a stock instrument nor assembled from outside parts.
~~Present organ shall be removed by and become property of M. P. Möller, Inc. without charge, if desired (excepting blower and motor).~~

GREAT ORGAN (Unenclosed)

1.	8'	Principal.....45.....17-1/2.....19 Zinc S.M....61 pipes
2.	8'	Bourdon.....56.....20-1/2.....17 Zinc C.M....61 pipes
3.	4'	Octave.....58.....18-1/2.....7 Zinc S.M....61 pipes
4.	2'	Waldflöte.....66-1/2...18-1/2.....S.M....61 pipes
5.	III-IV Rks.	Mixture..... Formula "A"220 pipes

SWELL ORGAN (Enclosed)

6.	8'	Rohrflöte.....54.....21-1/2.....17 Zinc C.M....61 pipes
7.	8'	Viole de Gambe52.....18-1/2.....19 Zinc S.M....61 pipes
8.	8'	Viole Celeste T.C..54.....18-1/2.....7 Zinc S.M....49 pipes
9.	4'	Flachflöte.....56-2/3...18-1/2.....7 Zinc S.M....61 pipes
10.	2'	Principal.....70.....17-1/2.....S.M....61 pipes
11.	1-1/3'	Larigot.....77.....17-1/2.....S.M....61 pipes
12.	8'	Trompette.....3"42-1/2.....Zinc & S.M....61 pipes
13.		Tremolo

PEDAL ORGAN (Unenclosed)

14.	16'	Subbass.....#2 Bdn.....Wood.....32 pipes
15.	8'	Principal.....44.....17-1/2.....19 Zinc S.M....32 pipes
16.	4'	Choralbass56.....18-1/2.....7 Zinc S.M....32 pipes
17.	16'	Fagott...1/2 L.. COC 3" ...Open Oboe.....Zinc & S.M....32 pipes

COUPLERS

18.	Great to Pedal 8'	24.	Swell to Pedal 4'
19.	Swell to Great 16'	25.	Swell 16'
20.	Swell to Great 8'	26.	Swell 4'
21.	Swell to Great 4'		
22.	Great 4'		
23.	Swell to Pedal 8'		

ADJUSTABLE COMBINATIONS

General Pistons No. 1-2-3-4-5-6

Affecting Entire Organ, placed beneath
Swell center.ACCESSORIESCrescendo Pedal for entire organ, with light indicator, Tremolo-Celeste cut-out
Great to Pedal Reversible toe stud

Swell Expression Pedal, swellbox and shade actions as required

Circuit breakers for organ action protection, 15 ampere maximum per circuit

Transparent music rack with light; light for pedal board

Lockswitch for motor to be mounted in console

Action current rectifier with wind switch, as required, mounted within organ

*Motor & Blower of ample capacity.*GENERAL~~Present electric motor and blower shall be reused, though are not covered in
usual guarantee.~~The organ shall be assembled and tested at the factory, then delivered, installed
and finished (receive final voicing and tonal regulation) in the Church by Moller staff,
presented ready for use.

Any necessary hoisting of large parts shall be provided by the church.

MIXTURE FORMULA

GREAT ORGAN

III-IV Rks. Mixture Formula "A"				220 pipes	S.M.	3"
22	19	15	12	12	8	
26	22	19	15	15	12	
29	26	22	19	19	15	
	29	26	22			
1-12	13-18	19-24	25-49	50-54	55-61	
Unison	47 Sc. @ 8'	17-1/2	1/4 mouth			
Quint	50 Sc. @ 8'	17-1/2	1/4 mouth			