M. P. MÖLLER Organ Factory

Pine Organ No.	R=134	Date March 23, 1982
	FIRST UNITED PRESBYTERIAN CHURC	
Action	Electro-Pneumatic	Console Present - Detached
Casing No.		Finish No change
Decorations		Motor Present 5 HP, Style 3-P-3328
Width of Nev-bed.	Standard	Stop Controls Draw Knobs & Tilting Tablets
No. Manuals	THREE AND PEDAL	Win'l Pressure See Scale Sheet
	September 24, 1982	Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING, CHANGING TONALLY & ADDING TO 34084 PRESENT MOLLER ORGAN OPUS 7498 - 1948

CONSOLE

Reuse present console rebuilding same as follows:

Replace drawknobs and contacts.

Replace combination piston buttons and springs.

Recover all stop and coupler pneumatics.

Recover combination pneumatics.

Recover all primaries and install new magnet armatures.

Recover reversibles.
Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating bushings.

Recover reservoir. Recover roll top.

Clean and polish cabinet, bench and pedal keyboard.

MANUAL CHESTS

Recover all manual pipe pouches.

Replace stop action checks and eyelts.

Replace duplex shifters.

Recover four 61 note primary stations and install new magnet armatures.

Recover stop action primaries and install new magnet armatures.

Recover pedal primaries and install new magnet armatures.

Rework Swell 2-2/3' Rohrflöte borrow to 2'.

Rework and/or install new toeboard/rackboard assemblies as required for tonal changes.

OFFSET & UNIT ACTIONS

Recover the following actions and install new magnet armatures:

Great	8 Principal	8	notes	
Great	8 Bourdon	85	notes	
Great	III-IV Fourniture	6	notes	
Swell	8 Salicional	12	notes	
Swell.	8 Trumpet	4	notes	

FIRST UNITED PRESBYTERIAN CHURCH, FAIRMONT, WEST VIRGINIA

PAGE 2

SWITCHES

R-134

Install new electro-pneumatic switches with diodes as required.

PEDAL ORGAN

Recover the following actions and install new magnet armatures:

16 Principal

32 notes (#13-44)

16 Subbass 16 Kohrflöte 32 notes 12 notes

Install the following new actions:

16 Principal

48 notes (#1-12 & 45-80

16 Contre Bombarde

56 notes

Install new electro-pneumatic switches with diodes as required.

EXPRESSION

Recover two 24 note and two 10 note expression actions and install new magnet armatures.

Recover all shade and bumper pneumatics.
Replace all shade jacks and connecting rods.

Refelt shades.

Install Nave shades 'On-Closed' control.

RESERVOIRS

Recover the following reservoirs and install new curtain valves as required:

One $3 - 0 \times 5 - 0$ manual

One 3 - 0 x 4 - 0 manual

One 1 - 6 x 2 - 6 offset

One 1 - 6 x 2 - 0 offset

Two expression

One 3 - 6 x 3 - 6 blower

TREMOLOS

Install new electro-pneumatic tremolos.

PIPES

Install new pipes as indicated by organ specifications. Revoice all pipes being reused.
Repack all wood pipe stoppers.

CABLES

Install new plastic covered cables between console and organ. Install new action current wires between console, organ and DC organ power unit.

ACTION CURRENT

Install new 10-15 volts, 30 amperes DC organ power unit.

BLOWER

Reuse present 5 HP, Style 3-P-3328 motor and blower without change. Install new motor-blower coupling leathers.
Install new 14" diameter flexible connection with draw bands.

GENERAL

All parts specified above to be rebuilt to be returned to the factory of M. P. Moller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Moller, Inc.

Echo Organ to be reused without rebuild or guarantee.

SPECIFICATIONS FOR CONSOLE AND ORGAN

PED	UAL COMPASS AL COMPASS D PRESSURE CH	CC to C4, 61 notes CCC to G, 32 notes See scale sheet A-440 @ 70°F	
		GREAT ORGAN - Enclosed with Choir 7	
1 2 3 4 5 6 7 8 9	8 8 4 4 2 III-IV	Principalnew pipes; present Diapason action	
		5WELL ORGAN - Enclosed II	
11 12	8	Rohrflöte	
13	8	Voix Celeste TCpresent pipes and action	
14	4	Principal	
15	2-2/3	Nazardpresent Gr 4 Octave pipes #8 im;#8-56 new to pactare	1
16 17	2 1-3/5	Rohrilote	61
18	III-IV	Plein Jeunew pipes; present 4 Fl. Triangulaire	
19 20 21	8	action	
		CHOIR ORGAN - Enclosed 4	
22	8	Concert Flute73 pipes	
23	8	Gemshornpresent Great pipes; present Dulciana	
24	8	action	
25	4	Snitzminging 1 Seem 427	
	4	Spitzprincipalfrom #23	
26 27 28 29	8	Clarinet	
85		Tremolo	
29	16	Festival Trumpet TCprepared for	
50	8	Trumpetprepared for	

ECHO ORGAN - Enclosed 3

		12020
33	4	Flöte 12
34	4	Viole IZ
35	8	Vox Humana 61
36		Chimes
37		Tremolo
38		Blank
,		* PEDAL ORGAN 3
** 39	32	ResultantQuint from #42, Unison from #4132 notes
40	16	Principal#1-12 new pipes & action, #13-80 present Sw. 8 Leigen Super Pupes #16-68
		octane action 1-32 City Disposer pipes #45 up, new action80 pipes
41	16	Subbass
42	16	Rohrflöte12 present Rohrbourdon pipes and action,
		20 from #11

** Controlled by toe stud only

Viole

31 32

43

44

45

46

47

48

88

4

III

4

16

COUPLERS - no change

Rohrflöte......32 notes Super Octave.....from #40......32 notes

49	Great to Pedal	61	Swell to Choir 16
50	Great to Pedal 4	62	Swell to Choir
51	Swell to Pedal	63	Swell to Choir 4
52	Swell to Pedal 4	64	Echo-Both-Choir (by jamb switch)
53	Choir to Pedal	65	Great 16
54	Choir to Pedal 4	66	Great Unison
55	Swell to Great 16	67	Great 4
56	Swell to Great	68	Swell 16
57	Swell to Great 4	69	Swell Unison
58	Choir to Great 16	70	Swell 4
59	Choir to Great	71	Choir 16
60	Choir to Great 4	72	Choir Unison
		73	Choir 4

^{*} Playable thru new switches and diodes

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-0
Pistons No. 1-2-3-4-0
Pistons No. 1-2-3-4-5-6-7-0
Pistons No. 1-2-3-4-0

Affecting Great
Affecting Swell
Affecting Choir and Echo
Affecting Pedal

Pistons No. 1-2-3-4-0
Pistons No. 1-2-3-4-5-0

Affecting Full Organ (duplicated by new toe studs)

General Cancel

PEDAL MOVEMENTS

Great to Pedal reversible Swell to Pedal reversible Choir to Pedal reversible 32 Resultant reversible wi

32 Resultant reversible with indicator light - amber

Balanced Expression Pedal - Great and Choir

Balanced Expression Pedal - Swell Balanced Expression Pedal - Echo

Concave, radiating pedal clavier

Balanced Crescendo Pedal with 5 indicator lights - green

Sforzando reversible - duplicated by manual piston - with indicator light - red

ACCESSORIES

Organ bench with music shelf
Present motor and blower
New DC organ power unit
Expression indicator lights - White
Current indicator light - White
Electric clock
New transparent music rack with light
New Nave shades "On - Closed" jamb switch
New key operated motor starter switch

Accepted Delal Light