

#1073
February 6, 1953

1954

3/28
SPECIFICATIONS

OF A

REUTER PIPE ORGAN

FOR

PORTSMOUTH
THE PORT NORFOLK BAPTIST CHURCH, NORFOLK, VIRGINIA

THREE MANUALS & PEDAL

MANUALS	Compass CC to Ch, 61 Notes.
PEDALS	Compass CCC to G, 32 Notes.
ACTION	Electro-Pneumatic.
REGISTRATION	Controlled by Draw Knobs (or Stop Keys, as preferred by purchaser.) <i>Draw Knobs</i>
CONSOLE	Detached. <i>A.G.S.</i>
CASEWORK OR GRILLE	None, except console case.
ORGAN CHAMBERS	Suitable, finished chambers to be furnished by the purchaser.

20885
U S

GREAT ORGAN
(Enclosed with Choir)

1.	8 ft.	Diapason	Metal	73 pipes.
2.	8 ft.	Hohl Flute	Wood	73 pipes.
3.	8 ft.	Gemshorn	Metal	73 pipes.
4.	4 ft.	Octave	Metal	73 pipes.
5.	2 2/3 ft.	Twelfth	Metal	61 pipes.
6.	2 ft.	Fifteenth	Metal	61 pipes.
7.		Chimes	Console Preparation	

Couplers to Great:

8. Great to Great 4 ft.
9. Great Unison Off.
10. Great to Great 16 ft.
11. Swell to Great 4 ft.
12. Swell to Great 8 ft.
13. Swell to Great 16 ft.
14. Choir to Great 4 ft.
15. Choir to Great 8 ft.
16. Choir to Great 16 ft.

SWELL ORGAN
(Enclosed)

17.	16 ft.	Rohrgedeckt	Wood, extension #19	12 pipes.
18.	8 ft.	Geigen Principal	Metal	73 pipes.
19.	8 ft.	Rohrflöte	Metal	85 pipes.
20.	8 ft.	Viole de Gambe	Metal	73 pipes.
21.	8 ft.	Viole Celeste	Metal	61 pipes.
22.	4 ft.	Spitz Principal	Metal	73 pipes.
23.	4 ft.	Rohrflöte	From #19	73 notes.
24.	2 2/3 ft.	Rohrnasat	From #19	61 notes.
25.	2 ft.	Rohrflöte	From #19	61 notes.
26.	III rk.	Mixture (15-19-22)	Metal	183 pipes.
27.	8 ft.	Trumpet	Metal, reeds	73 pipes.
28.	8 ft.	Vox Humana	Metal, reeds	61 pipes.
29.	4 ft.	Hautbois	Metal, reeds	73 pipes.
30.		Tremolo		73 pipes.

Couplers to Swell:

31. Swell to Swell 4 ft.
32. Swell Unison Off.
33. Swell to Swell 16 ft.

CHOIR ORGAN
(Enclosed)

34.	8 ft.	Viola (broad scale)	Metal	73 pipes
35.	8 ft.	Bourdon	Metal	73 pipes
36.	8 ft.	Dulciana	Metal	73 pipes
37.	8 ft.	Viola Maris	Metal	61 pipes
38.	4 ft.	Nachthorn	Metal	73 pipes
39.	2 2/3 ft.	Nasard	Metal	61 pipes
40.	2 ft.	Blockflöte	Metal	61 pipes
41.	8 ft.	Clarinet	Metal, reeds	73 pipes
42.		Tremolo		

Couplers to Choir:

43. Choir to Choir 4 ft.
44. Choir Unison Off.
45. Choir to Choir 16 ft.
46. Swell to Choir 4 ft.
47. Swell to Choir 8 ft.
48. Swell to Choir 16 ft.

PEDAL ORGAN

49.	16 ft.	Diapason	Metal	32 pipes.
50.	16 ft.	Bourdon	Wood	32 pipes.
51.	16 ft.	Rohrgedeckt	From Swell #17 and #19	32 notes.
52.	10 2/3 ft.	Quinte	From #50 and #54	32 notes.
53.	8 ft.	Octave	Metal, Extension #49	12 pipes.
54.	8 ft.	Bourdon	Wood, Extension #50	12 pipes.
55.	8 ft.	Rohrflöte	From Swell #19	32 notes.
56.	4 ft.	Choral Bass	Metal, Extension #53	12 pipes.
57.	16 ft.	Trombone	Metal, reeds	32 pipes.
58.	8 ft.	Tromba	Metal, reeds Extension #57	12 pipes.

Couplers to Pedal:

- 59. Great to Pedal 8 ft.
- 60. Great to Pedal 4 ft.
- 61. Swell to Pedal 8 ft.
- 62. Swell to Pedal 4 ft.
- 63. Choir to Pedal 8 ft.
- 64. Choir to Pedal 4 ft.

ADJUSTABLE COMBINATIONS

Operated by Pistons under their respective Manuals.
Adjustable at Keyboard and visibly affecting Stop Controls.

- 65-69. Five, thumb pistons affecting Great Organ and its Couplers.
- 70-74. Five, thumb pistons affecting Swell Organ and its Couplers.
- 75-79. Five, thumb pistons affecting Choir Organ and its Couplers.
- 80-84. Five, toe pistons affecting Pedal Organ and its Couplers.
- 85-89. Five, thumb pistons affecting all stops and couplers of the entire organ.
- 90. General Cancel, thumb piston.

COMBINATION COUPLERS

- 91. Pedal Combinations to Great Pistons, On and Off.
- 92. Pedal Combinations to Swell Pistons, On and Off.
- 93. Pedal Combinations to Choir Pistons, On and Off.

REVERSIBLES

- 94. Great to Pedal, toe piston.
- 95. Sforzando, toe and thumb pistons

PEDAL MOVEMENTS

- 96. Balanced Register Crescendo Pedal.
- 97. Balanced Great & Choir Expression Pedal.
- 98. Balanced Swell Expression Pedal.

ACCESSORIES

- 99. Sforzando Indicator Light.
- 100. Register Crescendo Indicator Light.
- 101. Music Rack.
- 102. Music Rack Fluorescent Light.
- 103. Organist's Bench.
- 104. Concave Radiating Pedal Keyboard, A.G.O. Model.
- 105. Blower and Motor of Ample Capacity.
- 106. Action Current Power Unit.
- 107. Static Pressure Control Reservoir on Blower.

NOTE:

If the draw knob type console is used, the Intra-manual couplers will be controlled by draw knobs placed with their respective stop groups, and affected by the combination pistons of that division. The inter-manual and Manual to Pedal Couplers will be controlled by tilting tablets placed in a single row above the Swell Manual, and will be affected by the General Pistons only.