### M. P. MOLLER ORGAN FACTORY

2/8

Pipe Organ No. R-183 Date February 17, 1987 For ST. PAUL'S UNITED CHURCH OF CHRIST, WOODSTOCK, VIRGINIA Action <u>Electro-Pneumatic</u> Console Present - Rolltop Casing Present Grille Finish No change Decorations None Motor Present 1HP, Style 3 DXM Width of Key-bed Standard Stop Controls Tilting Tablets No. Manuals Two and Pedal Wind Pressure 5" To be Completed September 1, 1987 Blower Pipe furnished by Purchaser

#### SPECIFICATIONS

FOR

REBUILDING, CHANGING TONALLY AND ADDING TO PRESENT MOLLER ORGAN OPUS 5551 - 1929 31880

CONSOLE

Reuse present console rebuilding same as follows:

Install new tilting tablets on new nameboard.

Install new piston buttons and springs.

Recover all coupler pneumatics. Recover combination pneumatic.

Recover all primaries and install new magnet caps and

Replace crescendo and expression pedal pads and edging.

Recover reversible action.

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating tips.

Recover reservoir. Recover rolltop.

Rework combination action to yield all generals.

Install new music rack and pedal lights. Refinish cabinet, bench and pedal keyboard.

PITMAN CHESTS

Recover all manual pipe pouches.

Install stop action checks and eyelets.

Recover two 61 note primary stations and install new magnet caps and armatures.

Recover stop action primaries and install new magnet caps and armatures.

Replace duplex shifters.

OFFSET AND UNIT CHESTS

Recover the following actions and install new magnet caps and armatures:

Great 8 Principal 6 notes Great 8 Oboe TC 49 notes Swell Holzgedackt 85 notes

Install new actions as required by specification.

CHIMES

Install new electric action.

Reuse present bells.

electro-preumatic SWITCHES

Install new solid state switches as required.

235 S Main St 22664

R-183 ST. PAUL'S UNITED CHURCH OF CHRIST, WOODSTOCK, VIRGINIA

PEDAL ORGAN Recover 16' Subbass action and install new magnet caps with diades

and armatures.

Install new solid state switches as required.

dectio preumatic

EXPRESSION Recover one 10 note shade action and install new magnet

caps and armatures.

Recover all shade pneumatics.

Install new shade jacks and connecting rods.

Refelt shades.

Recover the following reservoirs and install new curtain RESERVOIRS

valves:

One  $2 - 6 \times 4 - 0$ Manual Two 1 - 4 x 1 - 9 Offset

One Expression

TREMOLO Install new electro-pneumatic tremolo.

PIPES Install new pipes as indicated by specification.

Install slide tuners as required. Revoice all pipes being reused. Repack all wood pipe stoppers.

CABLES Install new plastic covered cables between console and organ

Install new action current wires between console, organ, and

DC organ power unit.

ACTION CURRENT Install new 10 - 15 volts, 30 amperes DC organ power unit.

BLOWER Reuse present 1 HP, Style 3 DXM motor and blower without

change.

Install new motor-blower coupling leathers.

Install new 10" diameter flexible connection with draw bands

GENERAL All parts specified above to be rebuilt to be returned to

the factory of M. P. Moller, Inc., Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Moller, Inc.

> SPECIFICATIONS FOR

ORGAN AND CONSOLE

Manual Compass Pedal Compass Wind Pressure

CC to C4, 61 notes CCC to G, 32 notes

511

Pitch A-444 @ 700 F

R-183	ST. PAUL'S UNITED CHURCH OF CHRIS	T, WOODSTOCK, VIRGINIA	Page 3					
GREAT ORGAN - Enclosed with Swell								
1. 8	#62-73 unified;	#62-73 present Viole #74-85 present Trompett	e					
2. 8 3. 8 4. 8 5. 4 6. 2 7. 8	Holzgedacktfrom #10  Violefrom #11  Dolcefrom #13  Octavefrom #1  Super Octavefrom #1  Oboe TCpresent pipes,	present Vox Humana actio	. 61 notes . 61 notes . 61 notes . 61 notes . 61 notes on 49 pipes					
8. 8	Trompettefrom #18							
	SWELL ORGAN - E	inclosed						
10. 8 11. 8 12. 8 13. 8 14. 4 15. 2 16. 1 1/3 17. 1 18. 8 19.	Holzgedacktpresent Stopped Violepresent Salicic Viole Celeste TCpresent Vox Cel Dolcepresent Dulcian Lochgedacktfrom #10Flachflotefrom #10Icm #10  Larigotfrom #10  Zimbelflotefrom #10  Trompettenew pipes, present Dulcian Prompette	enal pipes and action este pipes and action a pipes and action	61 pipes 49 pipes 61 pipes 61 notes 61 notes 61 notes 61 notes					
	* PEDAL OR	GAN						
20. 16 21. 16 22. 8 23. 4	Subbasspresent Bourdor Holzbordunfrom #20 Principalfrom #1 Choralbassfrom #1		. 32 notes . 32 notes					
COUPLERS								
25. Sw 26. Sw 27. Sw	reat to Pedal well to Pedal well to Great 16 well to Great well to Great 4	29. Great 4 30. Swell 16 31. Swell 4						
ADJUSTABLE COMBINATIONS								
Pistons No. 1-2-3-4-5 General Cancel		Affecting Full Organ						

### PEDAL MOVEMENTS

Great to Pedal Reversible
Balanced Expression Pedal - Entire Organ
Balanced Crescendo Pedal with indicator light

## ACCESSORIES

Concave, radiating pedal clavier Organ bench with music shelf Present music rack with new light New pedal light New DC organ power unit Present motor and blower

DMM/ceh 6/5/87

# PIPE SCALE SHEET

ORGAN NO. R-183			DATE February 17, 1987/Pg 5				
ST. PA	UL'S UNIT	ED CHURCH O	F CHRIST	RIST WOODSTOCK VIRGIN		I A	
Custom	er			Ci	ity		State
STOP	PITCH	PIPES	SCALE	HALVING	MOUTH	REMARKS	W.P.
			GREAT	ORGAN - End	closed wit	h Swell	
Principal	8	85 new 4	4/56/68/	81/94			
				17	1/4	12 Zinc, SM	5 "
Oboe TC	8	49 presen	t				5 "
			`\	SWELL ORGAN	- Enclos	e d	
Holzgedackt	8	85 present	Stopped	Diapason			5 "
Viole	8	61 present	Salicio	nal			
			60	17			5 "
Viole Cel. TC	8	49 present	Vox Cel	este			
			62	17			5 "
Dolce	8	61 present	Dulcian	a			
			56	17			5 "
Trompette	8	61 new	3"	42		Zinc, SM	5 "
						D(F) Esch.	
				PEDAL	ORGAN		
Subbass	16	32 present	Bourdon				5 "

PITCHA-440	a 70o F	COPIES	TO:
COMPLETION	September 1, 1987		

DMM/ceh 6/5/87