Replaced with

3/15

SPECIFICATIONS

OF A

REUTER PIPE ORGAN

FOR

ST. MARY'S SCHOOL AND JUNIOR COLLEGE, RALEIGH, NORTH CAROLINA

THREE MANUALS & PEDAL

MANUALS

Compass CC to C4, 61 Notes.

PEDALS

Compass CCC to G, 32 Notes.

ACTION

Electro-Pneumatic.

REGISTRATION

Controlled by Stop Keys of Draw Knobs, as preferred. Per letter of 3/16/53

1063 Organ Recel 1983 to Springhope,

CONSOLE

Detached, placed to suit purchaser.

CASEWORK OR GRILLE

None, except console case.

DISPLAY PIPES

None.

ORGAN CHAMBERS

Suitable, finished chambers to be furnished by the purchaser.

GREAT ORGAN

1.	,	8 ft.	Diapason	Metal	61 pipes.
2.	•	8 ft.	Hohl Flute	Wood	61 pipes.
3.	4	8 ft.	Gemshorn	Console Preparation	
4.	*	4 ft.	Octave	Metal	61 pipes.
5.	× .	4 ft.	Flute Harmonic	Console Preparation	
6.	Y.I	II Rk.	Mixture (15-19-22)	Metal	183 pipes.
7.	•		Chimes	Console Preparation	

Couplers to Great:

Tremolo

8.

- 9. Great to Great 4 ft.
- 10. Great to Great 16 ft.
- 11. Great Unison Off.
- 12. Swell to Great 4 ft.
- 13. Swell to Great 8 ft.
- 14. Swell to Great 16 ft.
- 15. Choir to Great 4 ft.
- 16. Choir to Great 8 ft.
- 17. Choir to Great 16 ft.

	SWELL ORGAN	2:		
18. 16 ft.	Rohrbourdon From #20 & #50	73 Notes.		
19. 8 ft.	Geigen Diapason Console Preparation			
20. 8 ft.	Rohr Flute W & M	85 Pipes.		
21. % 8 ft.	Viole de Gambe Metal	73 pipes.		
22. 8 ft.	Viole Celeste forsele Properation (t)	61 files		
23. 4 ft.	Spitz Principal Metal	73 pipes.		
24. 4 ft.	Rohr Flute From #20	73 notes.		
25. 2 2/3 ft.	Rohrnasat ' From #20	61 notes		
26. 2 ft.	Rohr Flute From #20	61 notes		
27. 8 ft.	Trumpet Reeds	73 pipes		
28. 4 ft.	Hautbois Console Preparation			
29.	Tremolo			
	Couplers to Swell:			
	30. Swell to Swell 4 ft.			
	31. Swell to Swell 16 ft.			
	32. Swell Unison Off.			
	CUOTE ODCAN			
33. \ 8 ft.	CHOIR ORGAN Viola Metal	73 pipes		
	Spitzflöte Metal	100		
	Flute Celeste (T. C.) Metal	85 pipes		
	Spitzflote From #34	61 pipes		
37. · 2 2/3 ft.		73 notes		
38. 2 ft.		61 notes		
39. v1 3/5 ft.		61 notes		
40. \ 8 ft.		61 notes		
41.	Tremolo			
, book by 127	Couplers to Choir:			
	42. Choir to Choir 4 ft.			
	43. Choir to Choir 16 ft.			
	44. Choir Unison Off.	F 3 1		
	45. Swell to Choir 4 ft.			
	46. Swell to Choir 8 ft.	2 02 1		
*0.				

47. Swell to Choir 16 ft.

PEDAL ORGAN

				-0
48.	. 16 ft.	Bourdon	Wood	32 pipes.
49.	16 ft.	Gemshorn	Console Preparation	
50.	√ 16 ft.	Lieblich Gedeckt	Wood, Extension Swell #20	12 pipes.
51.	8 ft.	Octave	Console Preparation	
52.	8 ft.	Bourdon	Wood Extension #48	12 pipes.
53.	8 ft.	Rohr Flute	From Swell #20	32 notes.
54.	' 8 ft.	Spitzflote	From Choir #34	32 notes.
55.	4 ft.	Choral Bass	Console Preparation	
56.	4 ft.	Rohr Flute	From Swell #20	32 notes.
57.	16 ft.	Trumpet	Console Preparation	

Couplers to Pedal:

- 58. Great to Pedal 8 ft.
- 59. Great to Pedal 4 ft.
- 60. Swell to Pedal 8 ft.
- 61. Swell to Pedal 4 ft.
- 62. Choir to Pedal 8 ft.

ADJUSTABLE COMBINATIONS

Operated by Pistons under their respective Manuals.
Adjustable at Keyboard and visibly affecting Stop Controls.

- 63-67. Five, acting on Great Organ and its Couplers.
- 68-72. Five, acting on Swell Organ and its Couplers.
- 73-77. Five, acting on Choir Organ and 1ts Couplers.
- 78-82. Five, acting on Pedal Organ and its Couplers, Toe Pistons.
- 83-89. Seven, General Pistons, acting on entire organ.
 - 90. General Cancel Piston.

COMBINATION COUPLERS

- 91. Pedal Combinations to Great Pistons, On & Off.
- 92. Pedal Combinations to Swell Pistons, On & Off.
- 93. Pedal Combinations to Choir Pistons, On & Off.

PEDAL MOVEMENTS

- 94. Balanced Great & Choir Expression Pedal.
- 95. Balanced Swell Expression Pedal.
- 96. Balanced Register Crescendo & Diminuendo Pedal.

ACCESSORIES

- Great to Pedal Reversible. 97.
- Sforzando Reversible, Duplicated on Thumb Piston. 98.
- Crescendo Indicator. 99.
- 100. Sforzando Indicator.
- Organ Blower & Motor, 2 H. P. 101.
- 102. Action Current Power Unit.
- 103. Organist's Bench.
- Concave Radiating Pedal Keyboard, A.G.O. Model. 104.
- Music Rack. 105.
- Fluorescent Music Rack Light. 106.
- Concealed Pedal Light. 107.
- 108. Static Control Reservoir Blower.

for table to be ned - for the Stand I the of If the draw knob type console is used, the Intra-manual couplers will be controlled

by draw knobs placed with their respective stop groups, and affected by the combination pistons of that division. The Inter-manual and Manual to Pedal Couplers will be controll by tilting tablets placed in a single row above the Swell Manual, and will be affected by the General Pistons only.