

SPECIFICATIONS  
FOR A  
TWO MANUAL AND PEDAL PIPE ORGAN  
Designed For  
ST. PAUL ROMAN CATHOLIC CHURCH  
WELLESLEY, MASSACHUSETTS  
MANUAL COMPASS C<sub>2</sub> TO C<sub>4</sub> 61 NOTES  
PEDAL COMPASS C<sub>1</sub> TO G 32 NOTES  
SUBMITTED November 27, 1968

2/22

CONSOLE - Stopkey - Built to AGO Specifications

DISPLAY FRONT - Not included - to be determined

48 sq ft

PREPARATION OF ORGAN SPACE - BY PURCHASER

		<u>GREAT (exposed)</u>			
✦	16'	Quintaton	36	1/4	61 Pipes CUT VERY LOW. ZINC + HOYT
✦	8'	Principal	47	1/4	61 Pipes SLOT
	8'	Gedeckt	CUT LOW		61 Pipes WOOD
	8'	Erzdähler	(Swell)		
✦	4'	Prestant	58	1/4	61 Pipes SLOT
✦	4'	Nachthorn	56	3/12 - 1/6	61 Pipes Hoyt
✦	2'	Klein Principal	70	1/4	61 Pipes D.L.
✦	III	Mixture	84-91-96	1/4-3/9	183 Pipes
	8'	Trompette	(Swell)		
		<u>SWELL (enclosed)</u>			
✦	8'	Rohrflöte	50	3/9	61 Pipes * HOYT
	8'	Erzdähler	48		49 Pipes
	8'	Erzdähler Celeste T. C.	48		49 Pipes } SLOT, SLIDE
✦	4'	Spitzprincipal	57	3/4T. 1/4	61 Pipes * D.L.
✦	4'	Koppelflöte	60	1/5	61 Pipes HOYT
	2'	Blockflöte	LIKE WALD. FL. Hoyt Trebles -		61 Pipes * WOOD.
✦	1 1/3'	Quint	75	3/3T. 1/5	61 Pipes * Hoyt
III		Mixture	(Prepared)		
	8'	Trompette	3 1/16" FR.		61 Pipes NAPRON SLOT
	4'	Rohrschalmei	12 eq.		61 Pipes
		Blank			
		Tremulant			
		<u>PEDAL</u>			
	16'	Subbass	#1		32 Pipes
	16'	Quintaton	(Great)		
	8'	Principal	46	1/2	32 Pipes SLOT
	8'	Bassflöte			12 Pipes
	8'	Rohrflöte	(Swell)		
	4'	Gedecktflöte	(Great)		
	4'	Charal bass	(Great) Principal		12 32 Pipes (Prepared) 59 sq. 1/4 D.
	2'	Nachthorn	(Great)		
III		Mixture	(Prepared)		
	16'	Posaune	5" IF EXPOSED 6" IF ENCLOSED		32 Pipes ENGL
	8'	Trompette	(Swell)		
	4'	Rohrschalmei	(Swell)		

\* = exposed pipes

✦ = open toe

29/20 1214

### COUPLERS

4992

Great to Pedal	Swell to Great 4'
Swell to Pedal	Swell to Swell 16'
Swell to Great 16'	Swell Unison Off
Swell to Great 8'	Swell to Swell 4'

### COMBINATION PISTONS

The Preferred Remote Controlled Capture System  
Adjustable at the keyboard and visibly affecting stops  
Three Pistons affecting Great  
Three Pistons affecting Swell  
Three Pistons affecting Pedal - Duplicate Toe Studs  
Five General Pistons affecting entire organ - duplicate toe studs  
General cancel

### ACCESSORIES

Swell expression pedal  
Crescendo pedal  
Crescendo indicator  
Lock on Combination setter  
Wind indicator light  
Music rack light  
Pedal Light  
Organ bench with music compartment  
Great to Pedal reversible - Piston and toe stud  
Sforzando Reversible - Piston and toe stud  
Motor starter key switch in console  
Motor blower and rectifier  
11 sets bronze tuning slides  
Finished swell expression enclosure (interior painted black by request of purchaser)  
Mixture tuning switches  
Choice of console finish  
Silver contacts  
Wicks solid state relay system  
Up to 25' cable from console to organ furnished  
Movable platform and 35' stranded cable