

DESIGNED FOR ST. STEPHEN'S BROADWAY UNITED CHURCH

WINNIPEG, Manitoba

COMPASS OF MANUALS CC TO C 61 KEYS

COMPASS OF PEDAL CCC TO G 32 KEYS FEET PIPES

- GREAT -

1	Quintaden	16	61
2	Prinzipal	8	61
3	Rohrflöte	8	61
4	Oktav	4	61
5	Spitzflöte	4	61
6	Flachflöte	2	61
7	Mixtur IV	1 1/3	244
8	Trompete	8	61

- SWELL - (enclosed)

9	Salizional	8	61
10	Vox coelestis (GG)	8	54
11	Gedacktflöte	8	61
12	Gemshorn	4	61
13	Waldflöte	2	61
14	Scharf III	2/3	183
15	Fagott (L/2)	16	61
16	Oboe	8	61
	Tremulant		

- POSITIV -

17	Gedackt	8	61
18	Prinzipal	4	61
19	Koppelflöte	4	61
20	Oktav	2	61
21	Quintflöte	1 1/3	61
22	Sesquialtera II (TC)	2 2/3	98
23	Zinbel III	1/3	183
24	Krummhorn	8	61
	Tremulant		

- PEDAL -

25	Prinzipal	16	32
26	Subbass	16	32
27	Oktav	8	32
28	Gedacktpommer	8	32
29	Choralbass	4	32
30	Mixtur IV	2	128
31	Posaune (L/2)	16	32

- COUPLERS -

Great to Pedal
 Swell to Pedal
 Positiv to Pedal
 Swell to Great
 Positiv to Great
 Swell to Positiv

- ADJUSTABLE COMBINATION PISTONS - (capture type)

Great 1,2,3,4,5 (thumb)
 Swell 1,2,3,4,5 (thumb)
 Positiv 1,2,3,4,5 (thumb)
 Pedal 1,2,3,4,5 (thumb and toe)
 General 1,2,3,4,5 (toe)

On & off Great & Pedal combination in key cheek

General cancel
 Adjuster

- REVERSIBLE PISTONS -

Great to Pedal (thumb and toe)
 Swell to Pedal (thumb and toe)
 Swell to Great (thumb)
 Full organ (thumb and toe)

- BALANCED PEDALS -

Crescendo on all stops and couplers
 Swell expression (mechanical)

- INDICATOR LIGHTS -

Crescendo
 Wind
 Full organ

The console shall be electro-pneumatic and detached from the organ.

The stops shall be controlled by drawknobs. The couplers shall be controlled by tilting tablets placed above the upper keyboard.

The console case, the organist's bench and the pedalboard shall be of oak, finished to match surrounding woodwork. A sample of the wood and finish shall be furnished by the Purchaser at least six (6) months prior to the date of delivery.

The interior of the console, such as the coupler board, the key cheeks, etc., shall be of mahogany with a hand-rubbed flat finish, in a shade that will afford a harmonious contrast with the exterior casework.

The music rack shall be of tempered plate glass and of the hinged, adjustable type, in coupler board.

There shall be a roll-top to cover the keyboards. The start-and-stop switch for the blower shall be in the console.

The metal pipework shall be made according to the Builder's standard practice; zinc up to 4' (actual length) and spotted metal thereafter.

The organ shall be disposed in one chamber, generally as shown on Builder's drawing D-6527-1, Scheme A, and the Builder shall provide the special length feet and the sills for the façade pipes, as well as the oak facing for the Positiv chest.

There shall be a blower and motor of ample capacity provided by the Builder. The Purchaser shall furnish the electrical current characteristics at least six (6) months prior to the date of delivery.