M. P. MÖLLER Organ Factory

Pipe Organ No	R-784	Date June 17, 1967				
For	ST. JOHN'S UNITED CHURCH OF CHRIST, CINCINNATI, OHIO					
Action	Electro-Pneumatic	Console Detached				
Casing No	None	Finish To customer's selection				
Decorations	None chests, swell box, etc	Motor New blower, motor & organ pover				
Width of Key-bed_	Standard	Stop Controls Draw knobs & Tilting tabl	Lets			
No. Manuals		Wind Pressure				
To be Completed_		Blower Pipe furnished by Purchaser				
CIERTA NETECNA DE CONTO						

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 4398 - 1925 2m

Install new three manual electro-pneumatic detached draw knob CONSOLE type console, pedal keyboard and organ bench.

Install new unenclosed & exposed Great Organ complete for the MANUAL CHESTS following ranks as specified:

> Great 8 Open Diapason - 61 Notes Great 8 Bourdon - 61 Notes Great 8 Dulciana - 61 Notes Great 4 Octave - 61 Notes Great II Grave Mixture - 61 Notes

Releather 126 manual pipe pouches. Install 472 new stop action checks and eyelets.

Install 110 new duplex shifters.

Install two new double stop action rails. Install four new single stop action rails.

Install new bottom boards.

Releather, electrify and install new valves in 8 stop action controls. Releather, electrify and install new valves in one 73 note primary station.

Install new action for Swell 16 Lieblich Gedeckt #1 to #12 incl. OFFSET ACTIONS

Install new 56 note contact box for Swell Organ. CONTACT BOX

Install the following new electro-pneumatic switches with stop actions: SWI TCHES

Swell 16 Lieblich Gedeckt - 56 Notes

Swell 8 Gedeckt - LL Notes

Releather and electrify 16 Bourdon action #1 to #44 incl. PEDAL ORGAN Install new 32 note Pedal Relay with eight 32 note switches.

Install new lh note expression action. EXPRESSION Install 14 new bearing blocks.

1988 merged wishnother bock AJ-Stm va m w/ Carthage VILL + becam Flenny Rd al 1197

RESERVOIRS

Releather the following reservoirs and install new curtain valves as required:

One (1) 3'-0" x 4'-0" Mamual Reservoir

Two (2) Pedal Reservoirs

TREMOLO

Install one new electro-pneumatic tremolos for Swell Organ.

PIPES

Install the following new pipes:

Great 8 Open Diapason - 61 Pipes

Great 8 Bourdon - 61 Pipes Great 8 Dulciana - 61 Pipes Great 4 Octave - 61 Pipes

Great II Grave Mixture - 122 Pipes

Swell 16 Lieblich Gedeckt - #1 to #12 incl - 12 Pipes

Swell & Principal - 73 Pipes Swell 8 Trompette - 73 Pipes

Revoice the following pipes:

Swell 8 Viola - 73 Pipes

Swell 8 Viola Celeste TC - 61 Pipes

CABLE

Install new plastic covered cables between console and organ.

Install new action current wires between console, organ and power unit.

BLOWER

Install new motor and blower of ample capacity.

ACTION CURRENT

Install new organ power unit of ample capacity.

GENERAL.

Entire organ to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md. for rebuilding as specified above. The Great Organ to be entirely new, designed and built as an exposed division, present organ to be completely rebuilt as the new Swell Organ and part of the Redal Organ as specified. Parts of existing organ to be re-used to be cleaned and modernized. M. P. Moller, Inc. to supply all freight and install

rebuilt and new organ in new church building.

SPECIFICATIONS

FOR

CONSOLE AND ORGAN

MANUAL COMPASS PEDAL COMPASS WIND PRESSURE PITCH CCC to Ch, 61 Notes CCC to G, 32 Notes

A-440 € 70° F

^(*) Pedal Organ playable thru new Pedal Relay and Switches to be supplied by M. P. Moller, Inc.

COUPLERS

39	Great to Pedal	50	Great 4
40	Swell to Pedal	51	Swell 16
47	Swell to Pedal 4	52	Swell Unison Off
42	Choir to Pedal	53	Swell 4
43	Choir to Pedal 4	54	Swell to Choir 16
44	Swell to Great 16	55	Swell to Choir
45	Swell to Great	56	Swell to Choir 4
46	Swell to Great 4	57	Choir 16
47	Choir to Great 16	58	Choir Unison Off
48	Choir to Great	59	Choir 4
1,9	Chair to Great h		

ADJUSTABLE COMBINATIONS

Pistons No.	1-2-3-4	A
Pistons No.	1-2-3-4-5	A
Pistons No.	1-2-3-4-5	A
Toe Studs No	0. 1-2-3-4-5	A
Pistons No.	1-2-3-4-5	A
General Can	cel Piston	

Affecting Great Stops Affecting Swell Stops Affecting Choir Stops Affecting Pedal Stops Affecting Full Organ

PEDAL MOVEMENTS

- Great to Pedal Reversible (duplicated by manual piston)Swell to Pedal Reversible (duplicated by manual piston)
- 3- Choir to Pedal Reversible (duplicated by manual piston)
- 4- Balanced Expression Pedal Swell Organ (14 contacts, regular system)
 5- Balanced Expression Pedal Choir Organ (16 contacts, regular system)
- 6- Balanced Crescendo Pedal with indicator light (green jewel)
- 7- Sforzando Reversible (duplicated by manual piston) with indicator light (red jewel)

ACCESSORIES

Motor starter switch.

Plexiglas music rack with fluorescent light.

Pedal light.

Concave and radiating pedal keyboard.
Organ bench with music shelf.
New blower, motor and organ power unit of ample capacity.

8/4/67 RHM/bf