

# M. P. MÖLLER Organ Factory

Pipe Organ No. 7050 Date August 8, 1941  
 For OLIVET PRESBYTERIAN CHURCH, READING, PENNSYLVANIA  
 Action Electric Console Detached  
 Casing No. None Finish \_\_\_\_\_  
 Decorations None Motor Electric  
 Width of Key-bed \_\_\_\_\_ Stop Controls Tilting - Tablets  
 No. Manuals Two Wind Pressure 4"  
 To be Completed November 15, 1941 Blower Pipe furnished by Purchaser

## SPECIFICATIONS

A-440

Entire organ to be new with the exception of the pipes mentioned below. All pipes to be new with the exceptions of the 4' Principal in the Great Organ, 8' Violin Diapason in the Swell Organ, 16' Diapason in the Pedal Organ and the 16' Bourdon in the Pedal Organ. Slide tuners to be furnished for the 4' Principal and 8' Violin Diapason.

2/20

### GREAT ORGAN

1	8'	Open Diapason.....	43 sc., 12 Zinc, C.M.....	73	Pipes
2	8'	Hohl Flute.....	Reg. Wood.....	73	Pipes
3	8'	Gemshorn.....	48-1/3 sc., 12 Zinc, S.M.....	73	"
4	8'	Dulciana.....	56 sc., 12 Zinc, S.M.....	73	"
5	4'	Octavo.....	56 sc., (p) pipes.....	73	"
6	2'	Fifteenth.....	69 sc.....	61	"
7	8'	Trumpet.....	4".....	73	"
8		Chimes.....	Doagan "A" A to F, #22 to #42.....	21	Bells

### SWELL ORGAN

9	8'	Violin Diapason.....	48 sc., 17 Zinc, S.M., (p) pipes..	73	Pipes
10	8'	Stopped Flute.....	Reg.....	73	"
11	8'	Salicional.....	58 sc., 12 Zinc, S.M.....	73	"
12	8'	Voix Celeste.....	58 sc., 12 Zinc, S.M.....	73	"
13	4'	Flute Harmonique.....	60 sc., S.M.....	73	"
14	2'	Flautino.....	72 sc., S.M.....	61	"
15	11l Rks.	Mixture.....	3 P., S.M.....	183	"
16	8'	Oboe.....	3 1/2".....	73	"
17	8'	Vox Humana.....	1 1/2" S.S.B.....	61	"

### PEDAL ORGAN

18	16'	Open Diapason.....	12-3/8" x 14" O.D., 30 (p) pipes...	44	Pipes
19	16'	Bourdon.....	8-1/8 x 9-3/4 O.D., 30 (p) pipes..	56	"
20	16'	Licblich Gedeckt.....	R.M.B.Sc. 1-12, 20 from #10.....	32	Notes
21	8'	Octave.....	From #18.....	32	"
22	8'	Flute (ext. Bourdon)....	From #19.....	32	"
23	4'	Flute (ext. Bourdon)....	From #19.....	32	"
24	8'	Still Gedeckt.....	From #10.....	32	"

### COUPLERS

25	Great to Pedal	31	Swell to Great 4'
26	Great to Pedal 4'	32	Great to Great 16'
27	Swell to Pedal	33	Great Unison Off
28	Swell to Pedal 4'	34	Great to Great 4'
29	Swell to Great 16'	35	Swell to Swell 16'
30	Swell to Great	36	Swell to Swell 4'

37 Swell Unison Off

## COMBINATION PISTONS

Pistons No. 1-2-3-4-5-6	Affecting Great and Pedal Stops
Pistons No. 1-2-3-4-5-6	Affecting Swell and Pedal Stops
Pistons No. 1-2-3-4-5-6	Affecting Entire Organ
Cancellor - Great	
Cancellor - Swell	
Cancellor - Entire Organ	
Cancellor - Pedal	

## PEDAL MOVEMENTS

1	Great to Pedal Reversible - Toe Piston
2	Great Expression Pedal
3	Swell Expression Pedal
	Crescendo Pedal
	Sforzando Pedal, Manual and Toe Pistons

## ACCESSORIES

Swell Tremolo  
 Great Tremolo  
 Wind and Current Indicator Light  
 Crescendo Indicator Lights  
 Sforzando Tablet Indicator  
 Organ bench

## REMARKS

One Electric motor, blower, and generator of ample capacity, to meet all the needs of the organ, will be furnished by the Organ Builder.

All wires, fuses, and conduits for the proper connection of the motor with the power line; the generator wires, with conduits and fuses; the remote control switch with wiring, conduits and fuses; and a proper foundation and housing for the motor, blower and generator, will be furnished and installed by the Purchaser, who will also furnish and install the galvanized iron pipes from blower to organ reservoirs and conduits for the organ cables.

All changes to the building necessary for the proper installation of the organ motor, blower, generator, wiring, conduits, and galvanized iron pipes, to be made by the Purchaser, who shall also provide any openings in walls or floors, etc., so that the organ men will not be called upon to do any carpenter's, stonemason's electrician's or tinsmith's work.