

R-562

# M. P. MÖLLER Organ Factory

Pipe Organ No. R-562 Date February 20, 1956  
For CENTENARY JUNIOR COLLEGE, HACKETTSTOWN, N. J.  
Action Electro-Pneumatic Console Present  
Casing No. - Finish -  
Decorations - Motor -  
Width of Key-bed - Stop Controls -  
No. Manuals - Wind Pressure -  
To be Completed August 31, 1956 Blower Pipe furnished by -

## SPECIFICATIONS

FOR

REBUILDING PRESENT THREE MANUAL ORGAN

### GREAT ORGAN

(1) Install new outside type magnets in the following action -

Primary station	73 magnets
8 Dulciana	73 magnets
4 Nachthorn	73 magnets
8 Trumpet	73 magnets
Stop action station	10 magnets

(2) Install new 73 note relay with the following switches and stop actions -

8	Diapason	1-17
8	Dulciana	1-73
4	Nachthorn	1-73
III	Furniture	1-17
8	Trumpet	1-73
	Chimes	20-44

(3) Install new pipes as follows -

8	Diapason	61 pipes
4	Octave	73 pipes
2	Super Octave	61 pipes
III	Furniture	183 pipes

(4) Install new action as follows -

8	Diapason bass chest	1-17 inc.
III	Furniture chest	1-17 inc.
III	Furniture toe & rackboard assembly	18-61 inc.
	3'-0" x 5'-0" reservoir	for Great & Choir organs.



SWELL ORGAN

(1) Install new outside type magnets in the following action -

Primary station	73 magnets
Stop action station	20 magnets

(2) Install new pipes as follows -

4 Octave Geigen	73 pipes
-----------------	----------

(3) Install new 3'-0" x 5'-0" reservoir

\* \* \*

CHOIR ORGAN

(1) Install new outside type magnets in the following action -

8 Cor de Nuit	73 magnets
---------------	------------

(2) Install new 73 note relay with the following switches and stop actions -

8	Cor de Nuit	1-73
8	Dulciana	1-73
4	Koppelflöte	1-73
2-2/3	Nazard	1-61
8	Trumpet	1-73
	Chimes	20-44

\* \* \*

PEDAL ORGAN

(1) Install new outside type magnets in the following action -

16	Bourdon	44 magnets
16	Gedeckt	44 magnets
8	Principal	44 magnets

(2) Install new 2'-0" x 3'-0" reservoir

\* \* \*

MISC.

(1) Install new 10/15 Volt 30 Ampere Orgelectra power unit with switch.

(2) Supply the following materials for installation of parts.

125 feet	77 conductor organ cable
50 feet	44 conductor organ cable
Four	73 conductor cable junctions
Four	44 conductor cable junctions



MISC. (cont'd)

(2) Supply the following materials for installation of parts - (cont'd)

15 feet	10" diam. Flexaust hose
20 feet	8" diam. Flexaust hose
15 feet	6" diam. Flexaust hose
2 feet	4" diam. Flexaust hose
2 feet	3" diam. Flexaust hose
20 feet	4" diam. Galvanized wind conductor
30 feet	3" diam. Galvanized wind conductor
One	10" diam. x 30" long "T" with 10" diam. x 6" long nipple in center.
Four	10" diam. x 6" long nipples
Six	8" diam. x 6" long nipples
Four	6" diam. x 6" long nipples
Four	4" diam. 90° elbows
Six	3" diam. 90° elbows
Four	4" diam. metal & felt collars
Sixteen	3" diam. metal & felt collars
Ten	10" diam. draw bands
Twelve	8" diam. draw bands
Eight	6" diam. draw bands
Six	4" diam. draw bands
Six	3" diam. draw bands
Six	Reservoir weights

\* \* \* \* \*

GENERAL

Retone regulate and tune organ.

3/17/56  
HDO/mb