

M. P. MÖLLER Organ Factory

Pipe Organ No. 7443 Date July 23, 1946
 For FIRST BAPTIST CHURCH, ELDORADO, ILLINOIS
 Action Electro-pneumatic *All-Electric* Console Detached
 Casing No. None Finish As per Sample
 Decorations None Motor 3/4 H.P., Style 3-P-2421
 Width of Key-bed Standard Stop Controls Stop Keys
 No. Manuals TWO Wind Pressure 4 1/2"
 To be Completed Soon as Possible Blower Pipe furnished by Purchaser

SPECIFICATIONS

PITCH: A-440
 ALL UNITS

GREAT ORGAN

1	8'	Diapason.....	44 sc.....	20 Zinc....	C.M.....	73 Pipes
2	8'	Gedeckt.....	L.M.B. Bass....	Reg. St. Flute	Treble.....	85 Pipes
3	8'	Viole Dolce.....	56 sc.....	20 Zinc....	S.M.....	85 Pipes
4	4'	Octave.....	from #1.....			61 Notes
5	4'	Flute.....	from #2.....			61 Notes
6	4'	Fugara.....	from #3.....			61 Notes
7	2-2/3'	Viole Twelfth.....	from #3.....			61 Notes
8	2'	Viole Fifteenth.....	from #3.....			61 Notes
9	8'	Trumpet.....	from #19.....			61 Notes
10		Chimes.....	Maas 1 1/4".....	A to F....	#22 to #42....	(See Note A) 21 Bells

SWELL ORGAN

11	16'	Bourdon...T.C.....	from #2.....			49 Notes
12	8'	Gedeckt.....	from #2.....			61 Notes
13	8'	Viole Dolce.....	from #3.....			61 Notes
14	8'	Voix Celeste...T.C....	58.....	8 Zinc....	S.M.....	49 Pipes 49
15	4'	Flute.....	from #2.....			61 Notes
16	4'	Fugara.....	from #3.....			61 Notes
17	2-2/3'	Flute Twelfth.....	from #2.....			61 Notes
18	2'	Flautino.....	from #2.....			61 Notes
19	8'	Trumpet.....	from #19.....			73 Pipes
20	4'	Clarion.....	from #19.....			61 Notes
21		Tremulant				

PEDAL ORGAN

22	16'	Bourdon....#2 Ped. Bdn....	12 pipes.....	20 from #2.....		32 Notes
23	8'	Diapason.....	from #1.....			32 Notes
24	8'	Flute.....	from #2.....			32 Notes
25	4'	Octave.....	from #1.....			32 Notes
26	4'	Flute.....	from #2.....			32 Notes

COUPLERS

27	Swell to Great
28	Great to Pedal
29	Swell to Pedal

Four (#) Grilles by M. P. Möller Inc.

ADJUSTABLE COMBINATIONS

(Operated by pistons placed under Great Manual)

Pistons No. 1-2-3-4

Affecting Full Organ

PEDAL MOVEMENTS

Great to Pedal Reversible
Balanced Expression Pedal
Balanced Crescendo Pedal

ACCESSORIES

Crescendo Indicator Light
Concave, Radiating Pedal Clavier
Organ Bench with Music Shelf
Electric motor, blower and action current generator

NOTE A - M. P. Moller, Inc., to supply and install a set of Maas Chimes and amplification as follows: Maas Chime Co. complete system #510-R, consisting of one Model #250 amplifier; one #18-R Radial Reflex Trumpet; 100 ft. of speaker cable and plug connectors; 21 Cathedral Chimes with pick ups Model 421 PAD 2.

Diameter of sound coverage is to be $\frac{1}{2}$ to 1 mile or more.

M. P. Moller, Inc. to install the chimes in the organ, completely wired into the console, and install the amplifier system and the speaker properly located on the roof or tower for best sound projection.

The church to provide conduits for the control and speaker cables, if required by local law, and to provide a 110 volt electric outlet near point where amplifier is to be located.

JHB/hr
9/5/46