M. P. MÖLLER Organ Factory

3-26				
Pipe Organ No	R-162 Date October 23, 1984			
For	FIRST UNITED METHODIST CHURCH, RUSSELLVILLE, ARKANSAS			
Action	Electro-Pneumatic Console New - detached - rolltop			
Casing No.	Present - no change Finish To customer's sample			
Decorations	None Motor Present 2 HP, Style 2 JYM			
Width of Key-bed	Standard Stop Controls Draw Knobs & Tilting Tablet			
No. Manuala	THREE & PEDAL - 4 oz. touch Wind Pressure 5"			
To be Completed	March 30, 1985 Blower Pipe furnished by Purchaser			
SPECIFICATIONS				
	FOR REBUILDING, CHANGING TONALLY & ADDING TO PRESENT MOLLER ORGAN OPUS 5405 - 1928 31724			
CONSOLE	Install new three manual, electro-pneumatic draw knob console, pedal keyboard and bench.			
MANUAL CHESTS	Recover all manual pipe pouches. Replace stop action checks and eyelets. Recover three 61 note primary stations and install new magnet armatures. Recover stop action primaries and install new magnet armatures. Replace duplex shifters. Rework and/or install new toeboard/rackboard assemblies as required for tonal changes. Unify actions called for in specifications. Install new actions required for additions.			
OFFSET AND UNIT ACTIONS	Recover the following actions and install new magnet armatures: Swell 16 Bourdon #1-97 Swell 16 Contre Trompette #1-8			
SWITCHES	Install new electro-pneumatic switches with diodes as required.			
PEDAL ORGAN	Recover the following actions and install new magnet armatures:			
	16 Subbass 32 notes 8 Principal 44 notes			
	Install new electro-pneumatic switches with diodes as required.			
EXPRESSION	Recover two 9 note, two 7 note, and one 4 note expression actions and install new magnet armatures. Recover all shade pneumatics. Replace all shade jacks and connecting rods. Refelt shades.			

304 S. Commerce St 72801 New Same 1997 RESERVOIRS

Recover the following reservoirs and install new curtain valves:

Two 2-6 x 4-0 manual One 2-0 x 4-0 manual One 1-6 x 2-6 peda1 Three expression One blower

TREMOLOS

Install new electro-pneumatic tremolos.

PIPES

Install new pipes as indicated by organ specifications. Revoice all pipes being reused, installing slide tuners as required.

Repack all wood pipe stoppers.

CABLES

Install new plastic covered cables between console and main organ only. Install new action current wires between console, main organ and

DC organ power unit.

(Antiphonal cables and action current wires by Gregory P. Koziel).

ACTION CURRENT

Install new 10-15 volts, 30 amperes DC organ power unit.

BLOWER

Reuse present blower without change.

Install new motor-blower coupling leathers.

Install new 12" diameter flexible connection with draw bands.

(New motor by Gregory P. Koziel)

GENERAL.

All parts specified above to be rebuilt to be returned to the factory of M. P. Möller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this program become the property of M. P. Möller, Inc. except certain pipes to be retained by the Church for fund raising purposes.

> **SPECIFICATIONS** FOR CONSOLE AND ORGAN

MANUAL COMPASS	CC to C4, 61 notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	5''
PITCH	A-440 @ 70°F

		GREAT ORGAN - Enclosed
1	8	Principalnew pipes; present Doppel Flute action61 pipe
2	8	Rohrflötenew pipes; present Melodia action
3	8	Dolce
4	4	Octavenew pipes; present Dulciana action
5	4	Rohrflöte
6	2	Super Octavefrom #4
7	III-IV	Mixturenew pipes; present 8 Open Diapason action with #1-8 returned to chest
8 9	8	Oboepresent Swell Oboe Horn pipes; present Gamba action61 pipe Tremolo

R-162		FIRST UNITED METHODIST CHURCH, RUSSELLVILLE, ARKANSAS PAGE	3
		SWELL ORGAN - Enclosed	
10 11 12 13	16 8 8 8	Bourdonpresent pipes and action	notes
14 15 16 17 18 19 20	4 4 2-2/3 2 2 III-IV 16	Principalnew pipes; present 8 Salicional action	pipes notes notes notes notes pipes
21 22 23	8	Trompette	notes
		ANTIPHONAL ORGAN - Enclosed	
24 25 26 27 28 29 30	8 8 4 4 II-IV	Principalnew pipes; new action	pipes pipes notes pipes
		* PEDAL ORGAN	
31 32 33 34	32 16 16 8	Untersatzfrom #10 and #32; see formula32 Subbasspresent Bourdon pipes and action32 Bourdonfrom #1032 Principalnew pipes; #1-32 present Bass Flute action	pipes notes
35 36 37 38 39 40	8 5-1/3 4 4 32 16	#33 up present Bourdon action	notes notes notes notes
41 42	8 4	Trompette	notes

^{*} Pedal Organ playable thru new switches and diodes

COUPLERS

43	Great to Pedal	54	Swell to Antiphonal 8
44	Great to Pedal 4	55	Great 16
45	Swell to Pedal	56	Great Unison Off
46	Swell to Pedal 4	57	Great 4
47	Antiphonal to Pedal	58	Swell 16
48	Antiphonal to Pedal 4	59	Swell Unison Off
49	Swell to Great 16	60	Swe11 4
50	Swell to Great	61	Antiphonal Unison Off
51	Swell to Great 4	62	Antiphonal 4
52	Antiphonal to Great		•
53	Antiphonal to Great 4 antiphonal to Swell		
53a.	antiphonal to Swell		
	U	AD TISTARIE COM	RINATIONS

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5	Affecting Great
Pistons No. 1-2-3-4-5	Affecting Swell
Pistons No. 1-2-3-4	Affecting Antiphonal
Toe Studs No. 1-2-3-4-5	Affecting Pedal
Pistons No. 1-2-3-4-5-6-7-8-9-10	Affecting Full Organ
	(#1-5 duplicated by toe studs)

General Cancel

PEDAL MOVEMENTS

Great to Pedal Reversible
Tutti reversible (duplicated by manual piston) with indicator light
All Swells to Swell Reversible
Balanced Expression Pedal - Great Organ
Balanced Expression Pedal - Swell Organ
Balanced Expression Pedal - Antiphonal Organ
Balanced Crescendo Pedal with indicator light

ACCESSORIES

Concave, radiating pedal clavier
Organ bench with music shelf and back rest
Transparent music rack with light
Pedal light
Roll top
Key operated motor switch

AEN/mr 12/12/84