M. P. MÖLLER Organ Factory

Pipe Organ No	M-3187	Date September 6, 1983
	ADVENT LUTHERAN CHURCH, YORK,	
		Console Present - Detached
	See ''Facade''	
Decorations	None	Motor Present 3 HP, Style 3-P-3027
Width of Egy-ber	Standard	Stop Controls Draw Knobs & Tilting Tablets
No. Manuais	THREE & PEDAL	Wind Pressure See Scale Sheets
To be Completed	March 15, 1984	Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REPAIRS AND TONAL CHANGES PRESENT MOLLER ORGAN OPUS 8743 - 1954 36155 3/22

CONSOLE

Reuse present console, rework same as follows:

Replace drawknobs and tilting tablets and install new contacts.

Replace combination piston buttons and springs. Recover primaries and install new magnet armatures.

Recover coupler pneumatics.
Recover combination pneumatics.

Recover reversibles.

Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers. Refelt console as required.

Refelt pedal keys and replace insulating tips.

Add jamb switches, rework terraces and toe stude, and change markers.

Recover console reservoir.

MANUAL CHESTS

Recover 3 - 61 note primary stations.

Rework and/or install new toeboard/rackboard assemblies as required

for tonal changes.

Install new action as required for additions.

SWITCHES

Recover 2 electro-pneumatic switches.

PEDAL ORGAN

Install new electro-pneumatic switches and diodes as required.

EXPRESSION

Recover two 12 note expression actions.

Recover all shade pneumatics.

Rework Great and Choir Organ shades and frames for Choir Organ only.

Rework and/or supply new swell box and sill for Choir Organ.

RESERVOIRS

Recover the following reservoirs:

Two 2'-6" x 4'-0" manual One 3'-0" x 4'-0" manual

Two 1'-6" x 2'-6" pedal

Two expression

One 3'-0" x 3'-0" blower

Supply one new 1'-6" x 2'-0" offset reservoir.

DACE 7	1900		453.0	TO	400
	7.38	PA.			. 7
	Span.	Profession land	10		

M-3187 ADVENT LUTHERAN CHURCH, YO	ORK.	PENNSYLVANIA
-----------------------------------	------	--------------

PIPES Install new pipes as indicated by organ spacifications.

Revoice Swell 8 Trompette and Choir 8 Krummhorn.

FACADE Rework existing grilles and install new polished zinc facades.

Supply new screen behind facades.

CABLES Install new plastic covered cables between console and organ.

Install new action current wires between console, organ and DC organ

power unit.

ACTION CURRENT Supply new 10-15 volts, 30 amperes organ power unit.

CHIMES Supply new Mayland action, transformer, relay and volume control,

A to F, #22-42, reuse present Maas tubes.

BLOWER Reuse present blower and motor.

Remove blower and motor from present chamber and install in remote

location to be provided by church. Church to furnish necessary wind conductor and wiring for motor.

Install new motor-blower coupling leathers.

Install new 12" diameter flexible connection.

GENERAL All parts from present organ not required to complete this contract are to be removed by and become the property of M. P. Möller, Inc.

SPECIFICATIONS FOR CONSOLE AND ORGAN

GREAT ORGAN - Unenclosed 9

1	8	Principal
2	8	Spitzflötefl pipes
3	4	Octave
4	2	Super Octave61 pipes
5	III-IV	Mixturenew pipes, present 2-2/3 Octave Quint action. 226 pipes
6	8	Trompete (1/2 L)new pipes, present 8 Diapason action61 pipes
7		Chimesnew Mayland action, transformer, relay and
		volume control, present Maas tubes, A to F,
		#22-42
8		Tremulant

SWELL ORGAN - Enclosed 10

		Security control and the security control and
9 10 11 12 13 14 15 16 17 18	8 8 4 2 111 16	Rohrflötepresent pipes & action
		CHOIR ORGAN - Enclosed 10
19 20 21 22 23 24 25 26	8 8 4 2 1-1/3 III-IV 8	Gedacktpresent pipes & action
		* PEDAL ORGAN 2
274. 27 28 29 30	32 16 16 8	Octave
31 32 33 34 35	4 III 32 16	Rohrflöte from #9. 32 notes Choralbass from #30. 32 notes Mixture from #30. 32 notes Trompette Cornet (toe stud) from #15 § 29

^{*} Pedal Organ playable thru new switches and diodes.

COUPLERS

Great to Pedal	48 Swell to Choir 16	
	49 Swell to Choir	
	50 Swell to Choir 4	
	51 Great 4	
	52 Swell 16	
	53 Swell Unison Off (jamb switch)	
	54 Swell 4	
	55 Choir 16	
	56 Choir Unison Off (jamb switch)	
	57 Choir 4	
Choir to Great 4		
	Great to Pedal Great to Pedal 4 Swell to Pedal Swell to Pedal Choir to Pedal Choir to Pedal Choir to Great 16 Swell to Great Swell to Great 4 Choir to Great 16 Choir to Great 4 Choir to Great 4 Choir to Great 4 Choir to Great 4	Great to Pedal 4 Swell to Pedal 50 Swell to Choir 4 Swell to Pedal 4 Choir to Pedal 51 Great 4 Choir to Pedal 4 Swell to Great 16 Swell to Great 4 Swell to Great 55 Choir 16 Choir to Great 4 Choir to Great 16 Swell to Great 4 Shell to Great 4 Shell to Great 55 Choir 16 Choir to Great 16 Shell to Choir 16 Choir to Great 16

ADJUSTABLE COMBINATIONS

Affecting Great

Pistons No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
Toe Studs No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
General Cancel

Affecting Swell
Affecting Choir
Affecting Pedal (duplicated by manual piston)
Affecting Full Organ (duplicated by toe studs)

PEDAL MOVEMENTS

Present, no change

GENERAL

Pipe sill, facade & screen by M. P. Moller, Inc.

1/10/84