

M. P. MÖLLER Organ Factory

Pipe Organ No. R-641 Date April 10, 1959
For HOPEWELL METHODIST CHURCH, DOWNINGTOWN, PA. 5620
Action Electro-Pneumatic Console Detached - RSO
Casing No. Supply Case Panel Only Finish To Customer's Selection
Decorations No Change Motor Present Motor & Blower. New DC Organ Power Unit
Width of Key-bed Standard Stop Controls Tilting Tablets
No. Manuals Two and Pedal Wind Pressure No change Great - Swell Organ 4" Pedal Organ 5"
To be Completed October 10, 1959 Blower Pipe furnished by Present

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 3958 - 1924 ~~3477~~ 44906

CONSOLE Install new two manual electro pneumatic detached tilting tablet type console, pedal keyboard and organ bench.

MANUAL CHEST Releather 346 manual pipe pouches.
Install 590 new stop action checks and eyelets.
Install 244 new duplex shifters.
Releather two 61 note primary stations and install new valves and new outside type magnets.
Releather 10 stop action primaries and install new valves and new outside type magnets.

OFFSET ACTION Releather Great 8 Open Diapason action #1 to #8 and install new valves and new outside type magnets.

CONTACT BOX Install new 8 note Contact Box for Great 8 Open Diapason #1 to #8 inc.

PEDAL ORGAN Releather 16 Bourdon action #1 to #32 inc. and install new valves and new outside type magnets.
Install new chest and pipes for 16 Bourdon #33 to #44 inc.

EXPRESSION Install new accordian type expression action.

RESERVOIRS Recover the following reservoirs and install new curtain valves.
One (1) 2'-6" x 4'-0" Manual Reservoir
One (1) 1'-3" x 1'-9" Pedal Reservoir

PIPES Install modern tuning slides on present metal pipes.

CASE PANEL Install new case panel to enclose present console opening.

CABLES Install new asbestos covered cables between console and organ.

ACTION CURRENT Install new 10-15 volt, 15 ampere DC organ power unit.

BLOWER Present blower to be used without change.

GENERAL The parts specified above for rebuilding to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS CC to C4, 61 notes
PEDAL COMPASS CCC to C, 32 notes
WIND PRESSURE 3- $\frac{3}{4}$ "
PITCH A-440 @ 70°F

GREAT ORGAN

1	8	Open Diapason.....	61 Pipes
2	8	Stopped Diapason.....	61 Pipes
3	8	Viole d'Orchestre.....	61 Pipes
4	8	Dulciana.....	61 Pipes
5	4	Flute Traverso.....	61 Pipes

SWELL ORGAN

6	8	Gedeckt.....from #2.....	61 Notes
7	8	Viole d'Orchestre.....from #3.....	61 Notes
8	8	Dulciana.....from #4.....	61 Notes
9	8	Voix Celeste TC.....	49 Pipes
10	4	Flute.....from #5.....	61 Notes
11		Tremolo	

PEDAL ORGAN *

12	16	Bourdon....present pipes, present action #1 to #32 inc. new pipes, new action #33 to #44 inc.....	44 Pipes
13	8	Flute.....from #12.....	32 Notes

(* Provide slides in console to play Pedal Organ

COUPLERS

14	Great to Pedal	20	Swell to Great 4
15	Great to Pedal 4	21	Great 16
16	Swell to Pedal	22	Great 4
17	Swell to Pedal 4	23	Swell 16
18	Swell to Great 16	24	Swell Unison Off
19	Swell to Great	25	Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great and Pedal Stops
Pistons No. 1-2-3	Affecting Swell and Pedal Stops
Pistons No. 1-2-3	Affecting Full Organ

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Swell to Pedal Reversible
- 3 - Balanced Expression Pedal (8 contacts, reverse system)
- 4 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave and radiating pedal keyboard
Organ bench with music shelf

Present motor and blower. New 15 ampere DC organ power unit.