

M. P. MÖLLER Organ Factory

2/15

File

Pipe Organ No. 8665 Date December 8, 1953
 For UNION METHODIST CHURCH, ST. LOUIS, MISSOURI
 Action Electro-pneumatic Console Detached - All Electric
 Casing No. None Finish As per sample
 Decorations None Motor 3 H.P. - Style 3-P-3027
 Width of Key-bed Standard Stop Controls Tilting Tablets
 No. Manuals Two Wind Pressure Gt. 3 1/2", Sw. 4", Ped. 4"
 To be Completed 8 to 10 months from date Blower Pipe furnished by Purchaser

PITCH: A-440

SPECIFICATIONS

GREAT ORGAN (Unenclosed)

1.	8'	Bourdon.....	54.....	21 1/2.....	12 Zinc.....	S.M....	61 Pipes
2.	8'	Erzähler.....	52 1/4.....	17 1/2.....	12 Zinc.....	S.M....	61 Pipes
3.	4'	Octave.....	58-3/4.....	18 3/4.....		S.M....	61 Pipes
4.	2-2/3'	Nasat.....	66.....	18 3/4.....		S.M....	61 Pipes
5.	2'	Octavin.....	70.....	18 3/4.....		S.M....	61 Pipes
6.		Chimes.....	Maas, electric action, trans former, relay, 21 tubes				
7.		Tremolo	control etc. to be supplied & installed by W. A. Brummer				

SWELL ORGAN (Enclosed)

8.	8'	Spitzflöte.....	48-2/3.....	19 1/2.....	12 Zinc.....	S.M....	80 Pipes
9.	8'	Viola.....	52.....	18 3/4.....	12 Zinc.....	S.M....	73 Pipes
10.	8'	Viola Celeste..T.C.....	54.....	18 3/4.....		S.M....	49 Pipes
11.	4'	Nachthorn.....	60.....	20 1/2.....	Open.....	S.M....	63 Pipes
12.	4'	Fugara.....	From #9.....61 Notes				
13.	2-2/3'	Spitzquinte.....	From #8.....61 Notes				
14.	2'	Flautino.....	From #11.....61 Notes				
15.	III Rks.	Plein Jeu.....	3-R-2.....	17 1/2.....		S.M....	183 Pipes
16.	8'	Trompette.....	2 1/2".....				73 Pipes
17.	4'	Clarion.....	From #16.....61 Notes				
18.		Tremolo					

PEDAL ORGAN

19.	16'	Subbass..(Unenclosed)....	Reg. Ped. Bdn.....	Low Lip.....	44 Pipes		
20.	16'	Liedlichbordon.....	From #19.....	32 Notes			
21.	8'	Major Bass.....	From #19.....	32 Notes			
22.	8'	Principal..(Unenclosed)....	44.....	18 3/4.....	17 Zinc.....	S.M....	56 Pipes
23.	4'	Choral Bass.....	From #22.....32 Notes				
24.	2'	Octav.....	From #22.....32 Notes				
25.	8'	Trompette.....	From #16.....32 Notes				

COUPLERS

26.	Great to Pedal		32.	Great	16'
27.	Swell to Pedal		33.	Great	4'
28.	Swell to Pedal	4'	34.	Great Unison Off	
29.	Swell	16'	35.	Swell to Great	16'
30.	Swell	4'	36.	Swell to Great	
31.	Swell Unison Off		37.	Swell to Great	4'

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4	Affecting Great and Pedal Stops
Pistons No. 1-2-3-4	Affecting Swell and Pedal Stops
Pistons No. 1-2-3-4	Generals, affecting entire organ
General Cancel Piston	

PEDAL MOVEMENTS

Expression Pedal to Swell Organ
 Crescendo Pedal
 Great to Pedal Reversible, toe stud and manual piston
 Swell to Pedal Reversible, toe stud and manual piston
 Sforzando Reversible, toe stud and manual piston

ACCESSORIES

Crescendo Indicator lights (4)
 Sforzando Indicator light
 Generator Test light
 Fluorescent Music Light, built in
 Signal Light - console only
 Signal Button - console only
 Pedal Clavier
 Organ Bench with music shelf
 Motor starter button - console only
 Kinetic Steel Blower with motor
 Action Current power unit

NOTE: The pipes of the Great Organ are to be unenclosed and on display in the chancel. The chest shall be suspended on the wall, same side as the organ chamber, just below the tone opening line. The purchaser will provide small steel channel projecting from the wall to support this chest. The purchaser will provide the necessary cabinet work to surround the chest.

The organ builder will submit the proposed design for pipe grouping to the church architects for approval before construction of this work begins.