

M. P. MÖLLER Organ Factory

Pipe Organ No. R-657 Date March 7, 1960
For FIRST ENGLISH LUTHERAN CHURCH, DUQUESNE, PENNSYLVANIA
Action Electro-Pneumatic Console Detached - Plain White Oak
Casing No. No Change Finish To Customer's Selection
Decorations No Change Motor Present Motor & Blower. New DC Organ Power Unit.
Width of Key-bed Standard Stop Controls Tilting Tablets
No. Manuals Two and Pedal Wind Pressure 3 1/2"
To be Completed October 15, 1960 Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 2856 - 1920

CONSOLE Install new two manual all electric detached tilting tablet console, pedal keyboard and organ bench.

MANUAL CHEST Releather 488 manual pipe pouches.
Install 818 new stop action checks and eyelets.
Install 354 new duplex shifters.
Releather two 61 note primary stations and install new valves and new outside type magnets.
Releather 14 note stop action primary and install new valves and new outside type magnets.

OFFSET CHEST Releather Great 8 Open Diapason action #1 to #12 incl. and install new valves and new outside type magnets.

~~CONTACT BOX Install new 42 note contact box for Great organ.~~

SWITCHES Install the following new switches with stop actions:
Great 8 Open Diapason - #1 to #12 incl. - 12 notes
Great Chimes - #22 to #42 incl. - 21 notes

CHIMES Install new 21 note electro-pneumatic action.
Install new top F #42 chime tube.
Repitch chimes to A=440.

PEDAL ORGAN Releather 16 Bourdon action #1 to #30 incl. and install new valves and new outside type magnets.
Install new chest and pipes for 16 Bourdon #31 and #32.

EXPRESSION Install new 10 note individual type expression action.

RESERVOIRS Install new Chime reservoir.
Releather one 2'-6" x 4'-0" Manual reservoir and install new curtain valve.
Releather one 1'-2" x 1'-4" two pressure Pedal reservoir.

TREMOLO Install one new electro-pneumatic tremolo.

PIPF8 Install modern tuning slides on all metal pipes.
Revoice Great 8 Oboe Horn - 61 pipes.

CABLES Install new asbestos covered cables between console and organ.

BLOWER Present motor and blower to be used without change.

ACTION CURRENT Install new 10-15 Volt, 15 Ampere DC organ power unit with air mercury switch.

GENERAL Entire organ with exception of organ case and display pipes, blower and blower motor to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md. for rebuilding as specified above.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS CC to Ch, 61 notes
PEDAL COMPASS CCC to G, 32 notes
WIND PRESSURE 3 1/2"
PITCH A-440 @ 70°F

GREAT ORGAN

1	8	Open Diapason.....present pipes, present action.....	73 Pipes
2	8	Gamba.....present pipes, present action.....	61 Pipes
3	8	Rohrflöte.....present pipes, present action.....	61 Pipes
4	8	Dulciana.....present pipes, present action.....	61 Pipes
5	4	Octave.....from #1.....	61 Notes
6	8	Oboe Horn.....present pipes, present action.....	61 Pipes
7		Chimes.....present Kohler-Lieblich tubes #22 to #41, new top F #42 tube, new action.....	21 Tubes

SWELL ORGAN

8	16	Bourdon TC.....from #3.....	49 Notes
9	8	Violin Diapason.....present pipes, present action.....	61 Pipes
10	8	Clarabella.....present pipes, present action #13 to #73, 12 from #3.....	61 Pipes
11	8	Gamba.....from #2.....	61 Notes
12	8	Dulciana.....from #4.....	61 Notes

SWELL ORGAN

13	8	Voix Celeste TC.....present pipes, present action.....	49 Pipes
14	4	Flute.....from #10.....	61 Notes
15	8	Oboe Horn.....from #6.....	61 Notes
16		Tremulant	

PEDAL ORGAN (*)

17	16	Bourdon.....present pipes #1 to #30, new pipes #31 & #32, present action #1 to #30, new action #31 & #32.....	32 Pipes
18	16	Lieblich Gedeckt.....from #17.....	32 Notes

(*) Provide slides in console to play Pedal organ.

COUPLERS

19	Great to Pedal
20	Swell to Pedal
21	Swell to Pedal 4
22	Swell to Great 16
23	Swell to Great
24	Swell to Great 4
25	Great 4
26	Swell 16
27	Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great and Pedal Stops
Pistons No. 1-2-3	Affecting Swell and Pedal Stops

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Balanced Expression Pedal (10 contacts, regular system)
- 3 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave and radiating pedal keyboard
Organ bench with music shelf

Present motor and blower. New 10-15 Volt, 15 Ampere DC organ power unit with air mercury switch.