# M. P. MÖLLER Organ Factory

Pipe Organ No	R-751	_DateSeptember 10, 1965
For	MESSIAH LUTHERAN CHURCH, SOUTH	
Action	Electro-Pneumatic	Console Present - No Change
Casing No.	None	Finish No Change
Decorations	None	Motor Present motor, blower & organ power
Width of Key-bed.  No. Manuals  To be Completed	Standard	Stop Controls Pres. draw knobs & tilting tab- lets. Wind Pressure Gr. & Ch. 3-3/4"; Sw. & Ped. 4"
	Three and Pedal	Wind Pressure Gr. & Ch. 3-3/4"; Sw. & Ped. 4"
	April 1, 1966	Blower Pipe furnished by Purchaser

SPECIFICATIONS			
FOR			
· -/-	RE-ENGINEERING WITH TONAL CHANGES PRESENT MOLLER ORGAN OPUS 7961-1948		
CONSOLE	Present three manual electro-pneumatic draw knob type console, pedal keyboard and organ bench to be used without change, except as necessary to confirm revised specifications listed.		
CREAT ORGAN	Install new action for IV Mixture - 244 pipes. Balance of Great Organ to be re-installed unenclosed as re-engineered.		
SWELL ORGAN	Install new action for 4 Schalmei - 61 pipes.  Balance of Swell Organ to be re-installed as re-engineered.		
CHOIR ORGAN	Install new 2 Principal on present 8 Dulciana action. Install present Dulciana #13 to #73 pipes on present 8 Unda Maris action. Balance of Choir Organ to be re-installed as re-engineered.		
PEDAL ORGAN	Install new action for II Mixture - 64 pipes.  Balance of Pedal Organ to be re-installed unenclosed as re-engineered.		
CHIMES	Present Deagan Class M tubes and action to be installed without change.		
EXPRESSION	Install new Swell Box as required (approx. 130 sq. ft.) Install new Swell Shades, frames and action as required(approx. 72 sq. ft.)		
PIPES	Install the following new pipes: 7		
	Great IV Mixture - 2lpl pipes Swell 4 Schalmei - 61 pipes Choir 2 Principal - 61 pipes Pedal II Mixture - 64 pipes		
CABLES	Install new plastic covered cables between console and organ. Install new action current wires between console, organ and organ power unit.		
BLOWER	Present blower to be used without change.		

ACTION CURRENT

Present generator to be used without change.

GENERAL

Entire organ with exception of motor, blower and generator are to be returned to factory of M.P. Moller, Inc. at Hagerstown, Md. for re-engineering with tonal changes for installation in new organ chambers to be provided by customer.

Present Choir 8 Unda Maris TC pipes and present Choir 8 Dulciana pipes #1 to #12 incl. are to be crated and returned to customer for storage on church property.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS
PEDAL COMPASS
WIND PRESSURE
PITCH

CC to Ch, 61 Notes CCC to G, 32 Notes Gr. & Ch. 3-3/4"; Sw. & Ped. 4" A-440 @ 70° F

#### GREAT ORGAN (unenclosed)

1	8	Diapasonpresent pipes; present action
2	8	Bourdon
3	8	Gemshorn
4	4	Octavepresent pipes; present action
5	4	Harmonic Flutefl Pipes; present action
6	2-2/3	Octave Quint
7	2	Super Octavepresent pipes; present action
8	IV	Mixture
9		Chimespresent Deagan M tubes; present action G to G #20 to #44 incl

# SYELL ORGAN (enclosed)

10	8	Rohrflöte
12	8	Viole Celeste TCpresent pipes; present action
13	4	Principal73 Pipes
14	4	Flute Triangulairepresent pipes; present action
15	2	Flautino
16	III	Plein Jeu
17	8	Trompette
18	4	Schalmei
19		Tremolo

# CHOIR ORGAN (enclosed) 7

	discontinuolisa discontinuolis				
20 21 22	8 8 8	Cor de Nuit			
23 24 25 26 27	1-1/3 8	Maris action			
		PEDAL ORGAN (unenclosed) 4			
28	16	Diapasonpresent pipes, present action #1-#12; 20 from #1			
29	16	Bourdon			
30	16	Rohrbourdonpresent pipes; present action #1-#12;			
,		20 from #10			
31	8	Octavepresent pipes; present action			
32	8	Bourdon			
33	8	Dourdons of the second of the			
21.	4	Rohrflöte32 Notes			
34		Super Octave32 Notes			
35	4	Bourdon32 Notes			
36	II	Mixture			
37	16	Double Trompettepresent pipes; present action #1-#12;			
-0		20 from #1732 Notes			
38	8	Trompette32 Notes			
COUPLERS (*)					
39		to Pedal 51 dreat 16			
40		to Pedal 4 52 Great Unison Off to Pedal 53 Great 4 to Pedal 4 54 Swell 16			
41		to Pedal 53 Great 4			
42	Swell .	to Pedal 4 54 Swell 16			
43	Choir	to Pedal Swell Unison Off (by jamb switch)			
44	Choir	to Pedal 55 Swell Unison Off (by jamb switch) 56 Swell 4			
45	Swell -	to Great 16 57 Swell to Choir 16			
46	Swell 4	to Great 58 Swell to Choir			
47	Swell :	to Great 4 59 Swell to Choir 4			
48		to Great 16 60 Choir 16			
49		to Great 61 Choir Unison Off			
50		to Great & 62 Choir &			
		The state of			

<sup>(\*)</sup> No change in Couplers except Swell Unison coupler is to be operated by jamb switch instead of draw knob.

## ADJUSTABLE COMBINATIONS (No Change)

Pistons	No. 1-2-3-4-5-6	Affecting	Great	Stops
Pistons	No. 1-2-3-4-5-6	Affecting	Swell	Stops
Pistons	No. 1-2-3-4-5-6	Affecting	Choir	Stops
Pistons	No. 1-2-3-4-5-6	Affecting	Pedal	Stops
Pistons	No. 1-2-3-4-5-6	Affecting	Full (	organ
General	Cancel Piston			

## PEDAL MOVEMENTS (4)

- 1- Great to Pedal Reversible (duplicated by manual piston)
- 2- Swell to Pedal Reversible (duplicated by manual piston)3- Choir to Pedal Reversible (duplicated by manual piston)
- 4- Balanced Expression Pedal (inoperative)
- 5- Balanced Expression Pedal Swell Organ
- 6- Balanced Expression Pedal Choir Organ
- 7- Balanced Crescendo Pedal with indicator light (green jewel)
- 8- Sforzando Reversible (duplicated by manual piston) with indicator light (red jewel)
- 9- All Swells to Swell Reversible (duplicated by manual piston) with indicator light (white jewel)
  - (\*) No change in Pedal Movements except existing dreat expression pedal is to become inoperative.

# ACCESSORIES (No Change)

Present concave and radiating pedal keyboard.

Present organ bench with music shelf.

Present motor, blower and generator.