

# M. P. MÖLLER Organ Factory

Pipe Organ No. 7806 Date December 12, 1947  
 For PRESBYTERIAN CHURCH, BOKSBURG, TRANSVAAL, SOUTH AFRICA  
 Action Electro-pneumatic Console Detached ALL ELECTRIC  
 Casing No. Case & Front Pipes Finish Mahogany to match Kejaat  
 Decorations None Motor blower & generator by purchaser  
 Width of Key-bed Standard Stop Controls Stop Keys  
 No. Manuals Two Wind Pressure 6"  
 To be Completed Soon as possible Blower Pipe furnished by Moller  
 Altitude 6,000 feet.

ALL UNITS  
PITCH

## SPECIFICATIONS

A-440

### Great Organ

1	8'	Diapason.....43.....17 Zinc...C.M.....73 pipes
2	8'	Gedeckt.....Spec. Bass, Reg. Stopped Flt.....85 pipes
3	8'	Viole Dolce.....56.....12 Zinc...S.M.....85 pipes
4	4'	Octave.....from #1.....61 notes
5	4'	Flute.....from #2.....61 notes
6	4'	Fugara.....from #3.....61 notes
7	2-2/3'	Viole Twelfth.....from #3.....61 notes
8	2'	Viole Fifteenth.....from #3.....61 notes

### Swell Organ

9	16'	Bourdon..t.c.....from #2.....49 notes
10	8'	Gedeckt.....from #2.....61 notes
11	8'	Viole Dolce.....from #3.....61 notes
12	4'	Flute.....from #2.....61 notes
13	4'	Fugara.....from #3.....61 notes
14	2-2/3'	Flute Twelfth.....from #2.....61 notes
15	2'	Flautino.....from #2.....61 notes
16	8'	Horn.....(console only).....61 contacts
17		Tremulant

### Pedal Organ

18	16'	Bourdon.....Reg. Ped. Bdn.....12 pipes, 20 from #2.....32 notes
19	8'	Diapason.....from #1.....32 notes
20	8'	Flute.....from #2.....32 notes
21	4'	Octave.....from #1.....32 notes
22	4'	Flute.....from #2.....32 notes

### Couplers

23	Swell to Great
24	Great to Pedal
25	Swell to Pedal

### Adjustable Combinations

(Operated by pistons placed under Swell Manual)

Pistons No. 1-2-3-4

Affecting Full Organ

Pedal Movements

Great to Pedal, Reversible  
Balanced Expression Pedal  
Balanced Crescendo Pedal

Accessories

Crescendo Indicator light  
Concave, Radiating Pedal Clavier  
Organ bench with music shelf  
Electric motor, blower and action current generator of ample capacity.

General

Blower Pipes: By. M. P. Moller, Inc.

Starter Switch: Silent Push Button starter switch supplied and installed in console by M. P. Moller, Inc.

Blower and Generator: Supply by purchaser.

Case: Display case to be similar to the design enclosed with two small towers of pipes added to the sides to make up width. The centre pipe should be about nine feet high and the rest of the case to be in keeping width with the scribe of the arch. This should be furnished in Mahogany and stained to match Kejaat. In order that there should be no misunderstanding about this we are sending you a chip which comes off the Lichtenburg case. This is a good general match. Front pipes should be silvered. Please keep the case out from the face of the arch at least the thickness of the end case posts.

Send the usual spares with the job including blacked fixings for fastening the case.

Console: To be detached and same colour as case. Standard Stop Key design. All Electric (no wind), cable to be 45 feet from position marked on sketch.

Shipping Address: Cooper, Gill & Tomkins,  
Presbyterian Church  
Boksburg, Transvaal, South Africa

via Durban