

M. P. MÖLLER Organ Factory

Organ No. R-620 Date April 1, 1958
ST. MARK'S EVANGELICAL LUTHERAN CHURCH, OAKLAND, MD.
 on Electro-Pneumatic Console Detached - QWO
 ng No. Supply new case panel only Finish To Customer's Selection
 orations Present Motor New Motor, Blower and DC Organ Power
 Unit
 th of Key-bed Standard Stop Controls Tilting Tablets
 Manuals Two and Pedal Wind Pressure _____
 e Completed October 1, 1958 Blower Pipe furnished by No Change

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 2162 - 1916

OLE

Install new two manual electro-pneumatic detached tilting tablet console, pedal keyboard and organ bench.

AL CHEST

Releather 342 manual pipe pouches.
 Install 998 new stop action checks and eyelets.
 Install 244 new duplex shifters.
 Install 4 duplex stop action rails.
 Install 2 single stop action rails.
 Install new manual chest groove boards.
 Releather and electrify two 61 note primary stations.
 Releather and electrify 10 note stop action primary.

ET ACTION

Releather and electrify 8 Diapason action #1 to #17 inc. (front pipe action)

ACT BOX

Install new 17 note contact box for offset action.

ES

Releather and electrify 21 note action.
 Recover 21 pneumatics.
 Install new 21 note switch.

L ORGAN

Releather and electrify 16 Bourdon action #1 to #30 inc.
 Install new chest and pipes for 16 Bourdon #31 and #32.

SSION

Install new accordian type expression action.

RVOIRS

Install new 2'-6" x 4'-0" Manual reservoir.
 Install new 1'-6" x 2'-6" Pedal reservoir.

OLO

Install new electro-pneumatic tremolo.

S

Install 8 Vox Celeste TC - 49 pipes (reconditioned pipes) on present
 8 Vox Humana action.
 Install modern tuning slides on all metal pipes.

ES

Install new asbestos covered cables between console and organ.

CASE PANEL Install new case panel to enclose present console opening.

ACTION CURRENT Install new 10-15 volt 15 ampere DC organ power unit.

BLOWER Install new 3/4 H.P., Style 2-P-2117 Kinetic Blower.

GENERAL The entire organ to be returned to the factory of M. P. Moller, Inc. at Hagerstown, Md. for rebuilding as specified above.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS CC to C₄, 61 notes
 PEDAL COMPASS CCC to C, 32 notes
 WIND PRESSURE ~~2 3/8"~~ 3 3/8"
 PITCH A-440 @ 70 F

GREAT ORGAN

1	8	Diapason.....	61 Pipes
2	8	Stopped Diapason.....	61 Pipes
3	8	Dulciana.....	61 Pipes
4	4	Flute Harmonique.....	61 Pipes
5	8	Oboe D'Orchestre.....	61 Pipes
6		Chimes.....present Deagan Class D A to F #22 to #42....	21 Tubes
7		Blank	
8		Blank	

SWELL ORGAN

9	8	Cedeckt.....from #2.....	61 Notes
10	8	Vox Celeste TC....present Vox Humana action, reconditioned pipes.....	49 Pipes
11	8	Dolce.....from #3.....	61 Notes
12	4	Flute.....from #4.....	61 Notes
13	8	Oboe.....from #5.....	61 Notes
14		Blank	
15		Blank	
16		Tremolo	

PEDAL ORGAN *

17	16	Bourdon.....present pipes, present action #1 to #30 new pipes, new action #31 and #32.....	32 Pipes
18		Blank	
19		Blank	
20		Blank	

(*) Provide slides in console to play Pedal Organ

COUPLERS

21	Great to Pedal
22	Great to Pedal 4
23	Swell to Pedal
24	Swell to Pedal 4
25	Swell to Great 16
26	Swell to Great
27	Swell to Great 4
28	Great 16
29	Great Unison
30	Great 4
31	Swell 16
32	Swell Unison
33	Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3

Affecting Great and Pedal stops

Pistons No. 1-2-3

Affecting Swell and Pedal stops

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Balanced Expression Pedal (8 contacts - reverse system)
- 3 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave and radiating pedal keyboard

Organ bench with music shelf

New motor, blower and DC organ power unit of ample capacity.