M. P. MÖLLER Organ Factory

Pipe Organ No. R-550 Date October 19, 1955

For FIRST METHODIST CHURCH, JERSEY SHORE, PA.

Action Electro-Pneumatic Console Detached - QWO

Casing No. Supply Case Panel Only Finish To Match Present Furnishings

Decorations Present Motor Present Motor & Blower

Width of Key-bed Standard Stop Controls Tilting-Tablet

No. Manuals Two & Pedal Wind Pressure See Below

To be Completed June 3, 1956 Blower Pipe furnished by Purchaser

SPECIFICATIONS
FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 1376 - 1912

CONSOLE Install new two manual electro-pneumatic detached tilting-tablet console, pedal keyboard and organ bench.

MANUAL CHEST Recover 581 manual pipe membranes.
Releather and electrify two 61 note primary stations.
Releather and electrify 10 ventil stop actions.

OFFSET CHEST Releather and electrify 17 note front pipe action.

CONTACT BOX Install new 44 note contact box for Great Organ.

SWITCHES Install new 17 note switch and stop action for Great 8 Diapason #1-#17 inc.
Install new 25 note switch and stop action for Great Chimes #20-#44 inc.

PEDAL CHEST Releather and electrify 16 Bourdon action #1-#30 inc.
Install new 14 note chest and pipes for extension of 16 Bourdon #31-#44 inc

EXPRESSION Install new 8 stage individual type expression action (mount outside of swell box).

RESERVOIRS Recover the following reservoirs -

Two 2'-6" x 4'-0" reservoirs for pipe wind
One 3'-0" x 4'-0" reservoir for action wind

Install new 1'-6" x 2'-6" Pedal reservoir.

TREMOLO Install two new beater type tremolos.

PIPES Install modern tuning slides on all metal pipes.

CABLE Install new asbestos covered cable between console and organ.

CASE PANEL — Install new case panel approximately 5'-0" x 6'-0".

ACTION CURRENT — Install new Orgelectra power unit of ample capacity.
Install pneumatic mercury switch for Orgelectra

GENERAL — All parts to be rebuilt to be returned to the factory at Hagerstown, Md.

M. P. MOLLER, INC. to supply all labor, drayage, and miscellaneous material for the above specified work.

SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS — CC to C4, 61 notes
PEDAL COMPASS — CCC to G, 32 notes
WIND PRESSURE — 3-1/2" Great; Swell 3¼"
PITCH — ~~A-440~~ A-435 @ 70° F

GREAT ORGAN

1	8	Diapason	61 Pipes
2	8	Melodia	61 Pipes
3	8	Dulciana	61 Pipes
4	4	Principal	61 Pipes
5		Chimes	
6		Tremolo	

SWELL ORGAN

7	8	Violin Diapason	61 Pipes
8	8	Stopped Diapason	61 Pipes
9	8	Vox Celeste TC	49 Pipes
10	8	Aeoline	61 Pipes
11	4	Flute Traverso	61 Pipes
12	8	Orchestral Oboe	61 Pipes
13		Tremolo	

PEDAL ORGAN *

14	16	Bourdon	44 Pipes
15	8	Flute from #14	32 Notes

(*) Pedal stops to play thru slides in console

COUPLERS

16	Great to Pedal	22	Great 16
17	Swell to Pedal	23	Great 4
18	Swell to Pedal 4	24	Swell 16
19	Swell to Great 16	25	Swell 4
20	Swell to Great		
21	Swell to Great 4		

* - Blower - Supply 4 couplers with screws & washers.
Supply one (1) 8" diam flexible rubber connector
" two (2) " " pleated drawbands

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great and Pedal Stops
Pistons No. 1-2-3	Affecting Swell and Pedal Stops
Pistons No. 1-2-3	Affecting Full Organ

PEDAL MOVEMENTS

1 - Great to Pedal Reversible
2 - Balanced Expression Pedal (8 contacts - regular system)
3 - Balanced Crescendo Pedal
4- Balanced Expression Pedal - Carillonic Bells.

ACCESSORIES

Action current indicator light - White
Crescendo indicator light - Green

Concave & radiating pedal keyboard
Organ bench with music shelf

Present motor & blower. New Orgelectra power unit.

11/30/55
HDO/mb