SPECIFICATION

OF

REUTER ELECTRO-PNEUMATIC PIPE-ORGAN

FOR THE

FIRST CHRISTIAN CHURCH

CHATTANOOGA, TENN.

THREE MANUAL & PEDAL

Details of Construction:

Manuals:

Compass CC to c4, 61 notes

Pedals:

Compass CCC to G, 32 notes

Action:

Electro-Pneumatic

Console:

Detached

Registration:

Controlled by Stop-Keys

Casework:

None except for the Console

Display Pipes:

None

Organ Chambers:

Suitable chambers to be fur-

nished by the church

Pitch:

A-440

⁵¹ 20792

⁵³ 20891

GREAT ORGAN

(Expressive)

1	l.	8 ft.	Diapason	metal	61 pipes
7	2.	8 ft.	Claribel Flute	wood	6I pipes
7	3.	8 ft.	Viola	metal	61 pipes
1	4.	8 ft.	Gemshorn	metal	61 pipes
-1	5.	4 ft.	Octa ve	metal	61 pipes
4	6.	4 ft.	Flauto Traverso	metal 30 notes from #2	12 pipes
	7.	3 x ks	Mixture Conso	lo Preparation Only	183 fifes for let
¥	8.		Chimes *	Maas A-F	21 tubes ' 115
1			Tremolo	Vibra chini	
			Couplers:	for Forshay	lette of a
			Great to Grea	Maas A-F Vulva chines for Forshay t 16 ft. Off	march 20
			Great Unison	Off	~7,/95
			Great to Grea		
			Swell to Grea	t 16 ft.	
			Swell to Grea	t 8 ft.	
			Swell to Grea	t 4 ft.	
			Choir to Grea	t 16 ft.	
			Choir to Grea	t 8 ft.	4.2
			Choir to Grea	t 4 ft.	

^{*} The Chimes are to have a panel switch in the Console to provide five variations in volume from soft to loud. They are also to be bored so that electrical pick-ups may be attached to them for the purpose of amplification if this should ever be desired by the church.

SWELL ORGAN

(Expressive)

1	¬ 9.	16	ft.	Flute Conique	Metal	Tenor	C (#14)	61	notes	
	~10.	8	ft.	Geigen Diapason	metal			73	pipes	+
7	` 11.	8	ft.	Rohrfloete	metal			73	pipes	
	12.	8	ft.	Viole de Gambe	metal			73	pipes	
	13.	8	ft.	Viole Celeste	metal	Tenor	· C	61	pipes	
	14.	8	ft.	Spitzfloete	metal	G ₂		73	pipes	
	15.	4	ft.	Geigen Principal	metal	Censole	Proparation	0n	13 P	مع
	16.	4	ft.	Chimney Flute	metal	From			notes	1
	17.	4	ft.	Spire Flute	metal	61 notes	from #14	12	pipes	
	18.		ft.	Violina	metal	From	#12	61	notes	
		2-2/3	ft.	Nasard	metal	From	No.14	61	notes	
	20.		ft.	Flautino	metal	From	No.14	61	notes	
	~ 21.	. 8	ß ft.	Trompette	reed			73	pipes	
	. 22.		8 ft.	Oboe-Horn	Synthetic	From N	os.12-19	73	notes	
	- 23.		B ft.	Vox Humana	reed	Console :	Preparation	0n	ly	
	24.		4 ft.	Clarion	reed	61 notes	from No.21	12	pipes	
				m					i.	

Tremolo

Couplers:

Swell to Swell 16 ft.

Swell Unison Off.

Swell to Swell 4 ft.

CHOIR ORGAN *

(Expressive)

25.	8 ft.	Violin Diapason	Console	Preparation	Only
26.	8 ft.	Concert Flute		Preparation	
27.	8 ft.	Dulciana		Preparation	
28.	8 ft.	Unda Maris		Preparation	
29.	4 ft.	Flute d'Amour		Preparation	
` 30.	8 ft.	Clarinet		Preparation	
	•	Tremolo		Preparation	
		Couplers:			

Choir to Choir 16 ft.

Choir Unison Off.

Choir to Choir 4 ft.

Swell to Choir 16 ft.

Swell to Choir 8 ft.

Swell to Choir 4 ft.

* Note: The Console for this organ is to be of Three Manuals and Pedal, even though none of the Stops for the lower manual (The Choir Organ) are to be installed now. However, all of the couplers and combination pistons for the Choir manual, as well as the rest of the organ are to be included in the original installation-- making the "preparation" complete so that when the Stops that are "prepared for" are installed at a later time, the Console will be complete and ready for them without any additional work or expense. In addition, the original blower and motor will be of a size sufficient to supply the entire organ now and also if and when the "prepared for" Stops are purchased and installed. This applies also to the "prepared for" Stops elsewhere in the specification-- on Great, Swell, Choir and Pedal divisions--insofar as it applies to the Console and the Blower for the organ. The extra cost involved in the initial installation will pay dividends several times the amount involved if and when the organ is ever fully completed as planned in the entire tonal scheme of this specification.

Even though the Choir Manual above will not have any Stops installed now, the Swell Organ can be played from the Choir keys through the several couplers, thus affording the organist some of the advantages of a three-manual over a two-manual organ, and giving the church some immediate returns for the extra investment involved in the cost of the organ.

PEDAL ORGAN

7	31.	16 ft.	Diapason	Console Preparation Only
-\$	32.	16 ft.	Major Bass	wood 32 pipes
-4	33.	16 ft.	Bourdon	wood 20 notes from No.2 12 pipes
1	34.	16 ft.	Rohrbordun	wood 20 notes from No.11 12 pipes
7	35.	8 ft.	Octave	Console Preparation Only
7	36.	8 ft.	Major Flute	wood From No.2 32 notes
1	37.	8 ft.	Rohrfloete	metal From No.11 32 notes
1	38.	8 ft.	Cello & #	metal From No.12 32 notes
•	39.	16 ft.	Bombarde (No.21)	Console Preparation Only
V	40.		Chimes	From No.8 21 notes

Couplers:

Great to Pedal 8 ft.

Swell to Pedal 8 ft.

Swell to Pedal 4 ft.

Choir to Pedal 8 ft.

COMBINATIONS

Adjustable at the Keyboard and visibly moving the Stops

Four Pistons, acting on Great Organ ... Four Pistons, acting on Swell Organ ... Four Pistons, acting on Choir Organ ... Four Croe-Stude, acting on Pedal Organ ... Four Generals, acting on entire Organ General Cancel Piston

(Doe Itu

COMBINATION COUPLERS

Pedal Combinations to Great Pistons, On & Off Pedal Combinations to Swell Pistons, On & Off Pedal Combinations to Choir Pistons, On & Off

ACCESSORIES

Balanced Great Expression Pedal
Balanced Swell Expression Pedal
Balanced Choir Expression Pedal
Balanced Crescendo Pedal and Indicator light
Great to Pedal Reversible toe-stud
Sforzando Pedal Reversible and Indicator light
"All Swells" to Swell Pedal Stop-Key
Organ Blower and Motor of ample capacity
Action Current Power-Unit
Organ Bench, adjustable in height and
with music compartment
Music Rack with fluorescent light
Concave-Radial Pedal Manual, A.G.O. Model

SPECIFICATIONS

Of The

"A dditions to the present Organ"

in

The First Christian Church, Chattanooga, Tenn.

as listed in the attached agreement

1953

	CHOIR ORGAN.	Expressive	200
1. 8'	Gedeckt Req.	wood Smibass	73 pipes
2. 81	Dolcan 52	metal	73 pipes
3. 41	Nachthorn 55	metal	73 pipes
4. 231 5. 21	Nasard 64	metal	61 pipes
5. 2'	Zauberflöte 60	metal	61 pipes
6. 1-3/5'	Tierce 68	metal taperad 7-5M	61 pipes
7. 8'	Fagotto (Reg +16')	reeds	73 pipes
8.	Tremolo 4%	to the Gradien Factor and	
		The state of the s	
	PEDAL ORGAN		
9. 81	Octave (44)	metal	32 pipes

NOTES

In connection with adding the above registers to the organ, the agreement includes the wind-chests, frame work, percussion bellows, wind conductors, reservoir, tremolo, primary action, expression shades and engine, necessary to the operation of the pipework.

The tablets now in the Console for the Choir Organ stops will be replaced with others appropriately engraved to conform to the above stop list. The S' Fagotto is to occupy the space now used by the Choir-to-Choir 16' Coupler, which is to now be inoperative, and the Tremolo tablet will be moved to the right in its proper place in the arrangement of the stops.

It is understood that the purchase price includes the labor for removing whatever pipework in the Great Organ is needed in order to install the pipes for the 8' Pedal Octave; also replacing and tuning as required. It is suggested that the pipes of the Great 8' Gemshorn be tuned as a "Geleste" to beat with the pipes of the Great 8' Vicla.

At the time of installation, the entire organ, both new and old will be checked, tuned as needed, and tonally regulated and balanced to produce the kind of organ this would have been had it been purchased and installed in its entireity at the beginning.

AD: Reflace also with Blank Dot Keys, The free to 8 Vox Humana, Palel 16' Dieferon, and Palel 10' Bombarde stoffays, for his Horshay latter of 12/5/55