M. P. MÖLLER Organ Factory

Pipe Organ No	10335	Date June 20, 1966		
For	ST. PAUL'S METHODIST CHURCH,	TALLAHASSEE, FLORIDA		
Action	Moller's Electro-Pneumatic	Console Detached. Placed in Choir		
Casing No	None	Finish As per sample		
Decorations	None	Motor 3 HP - Style 3-P-3027		
Width of Key-bed_	Standard	Stops and intra-manual couplers by draw Stop Controls knobs. Inter-manual couplers		
No. Manuals	Three	Wind Pressure tablets. 3-1/4"		
To be Completed_	October 13, 1967	Blower Pipe furnished by Purchaser		
PITCH: A-440 SPECIFICATIONS CENERAL: The church, at its expense, to make preparations in the building for the organ from plans by M. P. Moller, Inc. The organ to be the distinctive work of the builder, not an assembled product.				
	GREAT ORG	HAN (unenclosed)		
1. 8' 2. 8' 3. 4' 4. 2' 5. III Rks. 6.	Bourdon5420-1/3 Octave5818-1/3 Doublette7319-1/3 MixtureFormula "A" Chimes (prepared for in constremulant			
8. 8' 9. 8' 10. 8' 11. 4' 12. 2' 13. 1-1/3' 14. 8' 15. 4'	Rohrflöte5421-1/ Viole de Gambe5218-1/ Viole Geleste(prepared for Principal5918-1/ Waldflöte68-2/320-1/ Larigot80-2/320-1/ TrompetteCC 3-3/h" T.C. 2	AN (enclosed) 2		
CHOIR ORGAN (enclosed)				
17. 8' 18. 8' 19. 4' 20. 2' 21. 8'	Erzahler52-1/417-1/ Koppelflöte6420-1/ Blockflöte68-1/221-1/	Bass & TrebleWood		

PEDAL ORGAN

23.	161	SubbassLarge Ped. BdnWood
24.	161	Rohrgedackt1221-1/212 pipes 20 from #832 Notes
25.	81	Octave
26.	89	Subbass32 Notes
27.	81	Rohrflöte32 Notes
28.	42	Super Octave32 Notes
29.	718	Rohrflöte32 Notes
30.	161	Bass TrumpetCCC 6" CC 3-3/4"12 pipes, 20 from #1432 Notes

COUPLERS

31.	Great	to	Pedal	88
32.	Swell	to	Pedal	81
33.	Choir	to	Pedal	81
34.	Swell	to	Great	168
35.	Swell	to	Great	81
36.	Swell	to	Great	718
	Choir	to	Great	16
38.	Choir	to	Great	81
39.	Choir	to	Great	718
40.	Swell.	to	Choir	161
41.	Swell	to	Choir	81
42.	Swell.	to	Choir	718
43.	Swell	16		
ليل	Swell	118		
45.	Choir	16	1	
46.	Choir	118		

ADJUSTABLE COMBINATIONS

Pistons	No.	1-2-3-4-5	
Pistons	No.	1-2-3-4-5	
Pistons	No.	1-2-3	
Pistons	No.	1-2-3-4	
Pistons	No.	1-2-3-4	
Cancel Piston			

For stops of Great Organ For stops of Swell Organ For stops of Choir Organ For stops of Pedal Organ For stops and couplers of Full Organ (Generals)

PEDAL MOVEMENTS

```
Swell Expression Pedal with indicator light
Choir Expression Pedal with indicator light
Crescendo Pedal with indicator light
Sforzando Pedal (Reversible) with indicator light (duplicated by manual piston)
Great to Pedal (Reversible) (duplicated by manual piston)
Swell to Pedal (Reversible) (duplicated by manual piston)
Choir to Pedal (Reversible) (duplicated by manual piston)
```

ACCESSORIES

Organ bench with music rack and back rest Concave and radiating pedal clavier, AGO pattern Music light Pedal light Plexiglas music rack Slow speed electric motor, action power unit and blower in steel housing of ample capacity. Motor starter switch mounted on console.

"The organist requests that the quality that will best fit the taste of our congregation is "baroque". He feels that this quality may be difficult to obtain in tuning and voicing the organ because there are so many flutes among the ranks."

JHH/mr 6/23/66 Salesman: Pilcher 5/17/67

The state of the s

MIXTURE FORMULAS

	GREAT	ORGAN	
III	Rks. Mi	xture Formula	"AH

22	19	15	12	8
26	22	19	15	12
29	26	22	19	15
1-12	13-24	25-36	37-48	49= -61

Unison 47 @ 8° CC 17-1/2 1/4 mouth S.M. Quint 48 @ 8° CC 17-1/2 1/4 mouth S.M.