

M. P. MÖLLER Organ Factory

Pipe Organ No. 7576 Date _____
For DUTCH REFORMED CHURCH, LAINGSBURG, SOUTH AFRICA
Action Electro-pneumatic Console Detached - All Electric
Casing No. Case & Front Pipes Finish As per Sample
Decorations none Motor & Generator By Purchaser
Width of Key-bed Standard Stop Controls Stop Keys
No. Manuals TWO Wind Pressure 5 1/2"
To be Completed As soon as possible Blower Pipe furnished by Möller

SPECIFICATIONS

*all units
Pitch A-440*

UNITS

A	8'	Large Open Diapason...	CC40 TC 54	17. Fine C. M.	73 Pipes
B	8'	Small Open Diapason...	46	17. Fine S. M.	85 Pipes
C	8'	Salicional...	56	17. Fine S. M.	73 Pipes
D	16'	Flute...	1-12 Reg. P. Bd. 13-24 Spic. Bass #25 up Reg. Melodia		97 Pipes
E	8'	Cornopean...	4 1/2"		73 Pipes

GREAT ORGAN

1	16'	Double Diapason...T.C.	from Unit B.	49 Notes
2	8'	Large Open Diapason...	from Unit A.	61 Notes
3	8'	Small Open Diapason...	from Unit B.	61 Notes
4	8'	Salicional...	from Unit C.	61 Notes
5	8'	Melodia...	from Unit D.	61 Notes
6	4'	Principal...	from Unit A.	61 Notes
7	4'	Flute...	from Unit D.	61 Notes
8	4'	Octave...	from Unit B.	61 Notes
9	2'	Fifteenth...	from Unit B.	61 Notes

SWELL ORGAN

10	16'	Contra Viol...T.C.	from Unit C.	49 Notes
11	8'	Open Diapason...	from Unit B.	61 Notes
12	8'	Salicional...	from Unit C.	61 Notes
13	8'	Melodia...	from Unit D.	61 Notes
14	4'	Octave...	from Unit B.	61 Notes
15	4'	Salicet...	from Unit C.	61 Notes
16	4'	Flute...	from Unit D.	61 Notes
17	2'	Piccolo...	from Unit D.	61 Notes
18	16'	Contra Fagotto...T.C.	from Unit E.	49 Notes
19	8'	Cornopean...	from Unit E.	61 Notes
20	4'	Clarion...	from Unit E.	61 Notes
21		<i>Tremulant</i>		

PEDAL ORGAN

21-22	16'	Sub Bass...	from Unit D.	32 Notes
22-23	8'	Diapason...	from Unit A.	32 Notes
23-24	8'	Bass Flute...	from Unit D.	32 Notes
24-25	8'	Cello...	from Unit C.	32 Notes

COUPLERS

25 26 Swell to Great
26 27 Swell to Pedal
27 28 Great to Pedal

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4 Affecting Great and Pedal Stops
Pistons No. 1-2-3-4 Affecting Swell and Pedal Stops
General Cancel Piston

PEDAL MOVEMENTS

Great to Pedal Reversible
Balanced Expression Pedal - Swell Organ
Balanced Crescendo Pedal

ACCESSORIES

~~Tremulant~~
Crescendo Indicator
Action Current Indicator
Organ Bench
Starter Buttons (Silent in operation)

All Electric, Detached Console; 25 feet of cable required; action electro-pneumatic.
Stopkeys for all stops and couplers.
Swell Shutters to be operated electrically.
Stopkeys to operate stops and couplers.
Supply sufficient wind conduits for connecting blower to organ.
Casework in oak, medium dark flat finish, as per sample chip herewith. The design to be on the lines of your No. 8 as shown in booklet forwarded us some weeks ago.
Front Pipes gilded, powder or liquid.
Blower and generator not included. We will order them separately.

Space for organ on Gallery as shown on blueprint herewith. There is ample space.
Organ must be built about 18 ins. from back wall of church as there is a window immediately behind organ which will be bricked up, but even so, the heat of summer will strike through and cause trouble if precautions are not taken. Please submit your layout and case design.

~~Price based on your recent advice of \$3075.00 for 4 Unit no blower or casework; and casework at \$4.30 per s. f. less 15%.~~

~~Payment: By letter of credit through Standard Bank of S. A. Ltd., New York Branch in full plus freight and handling charges to Cape Town, against all shipping documents.~~

CASES TO BE ADDRESSED:- Cooper, Gill & Tomkins
Dutch Reformed Church
LAINGSBURG
via Cape Town, S. A.

SHIP TO CAPE TOWN

BR
2/27/47