

M. P. MÖLLER Organ Factory

216

Handwritten signature

Pipe Organ No. R-650 Date August 19, 1959
For ST. PAUL'S EPISCOPAL CHURCH, BENNETT'SVILLE, SOUTH CAROLINA
Action Electro-Pneumatic Console Detached
Casing No. None Finish To Customer's Selection
Decorations None Motor Present Motor & Blower. New DC Organ Power Unit
Width of Key-bed Standard Stop Controls Tilting Tablets
No. Manuals Two and Pedal Wind Pressure _____
To be Completed September 1, 1960 Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OPUS 2673 - 1919⁴³²⁰²

CONSOLE Install new two manual electro-pneumatic detached tilting tablet console, pedal keyboard and organ bench.

MANUAL CHEST Releather 288 manual pipe pouches.
Install 598 new stop action checks and eyelets.
Install 305 new duplex shifters.
Releather and electrify 10 stop action controls.
Releather and electrify two 61 note primary stations.

OFFSET ACTION Install new action for Great 8 Open Diapason #1 to #17 incl.

CONTACT BOX Install new 17 note contact box for offset action.

PEDAL ORGAN Releather and electrify 16 Bourdon action #1 to #30 incl.
Install new pipes and action for 16 Bourdon #31 and #32.

EXPRESSION Install new shades and action as required.

RESERVOIRS Recover one (1) 2'-6" x 4'-0" Manual reservoir.
Install one (1) new Pedal reservoir.

TREMOLO Install one new electro-pneumatic tremolo.

PIPES Supply the following new pipes:

Great 8 Open Diapason - #1 to #17 incl. - 17 pipes

Install modern tuning slides on all metal pipes.

CABLES Install new asbestos covered cables between console and organ.

BLOWER Present blower and motor to be used without change.

ACTION CURRENT Install new 10-15 volt, 15 ampere DC organ power unit.

GENERAL The entire organ except organ case, blower and blower motor to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md. for rebuilding as specified above.

SPECIFICATIONS
FOR
CONSOLE AND ORGAN

MANUAL COMPASS CC to Ch, 61 notes
PEDAL COMPASS CCC to G, 32 notes
WIND PRESSURE
PITCH A=440 @ 70°F

GREAT ORGAN

1	8	Open Diapason.....new pipes, new action #1 to #17 present pipes, present action #18 to #73....73 Pipes
2	8	Rohrflöte.....present pipes, present action.....73 Pipes
3	8	Dulciana.....present pipes, present action.....61 Pipes
4	4	Octave.....from #1.....61 Notes
5	8	Oboe Gamba.....present pipes, present action.....61 Pipes

SWELL ORGAN

6	8	Gedeckt.....from #2.....61 Notes
7	8	Dolce.....from #3.....61 Notes
8	8	Vox Celeste TC.....present pipes, present action.....49 Pipes
9	4	Flute.....from #2.....61 Notes
10	8	Oboe.....from #5.....61 Notes
11		Tremulant

PEDAL ORGAN (*)

12	16	Bourdon.....present pipes, present action #1 to #30, new pipes, new action #31 & #32.....32 Notes
----	----	--

(*) Provide slides in console to play Pedal Organ

COUPLERS

13	Great to Pedal
14	Great to Pedal 4
15	Swell to Pedal
16	Swell to Pedal 4
17	Swell to Great 16
18	Swell to Great
19	Swell to Great 4
20	Great 16
21	Great Unison Off
22	Great 4
23	Swell 16
24	Swell Unison Off
25	Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3	Affecting Great and Pedal Stops
Pistons No. 1-2-3	Affecting Swell and Pedal Stops

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Balanced Expression Pedal (16 contacts, regular system)
- 3 - Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Concave and radiating pedal keyboard
Organ bench with music shelf

Present motor & blower. New 15 ampere DC organ power unit.

