

SPECIFICATIONS
OF
TWO RANK SERIES 70 ORGAN
FOR

#11341, CHAPEL, ST. JOHN'S CHURCH, (EPISCOPAL), SAVANNAH, GEORGIA

2/2

(1) ORGAN

Cabinet	Standard design
Wood & Finish	Rift Sawn Oak to customer's sample
Action	Electro-Pneumatic
Wind Pressure	See Pipe Analysis
Pitch	A-440 @ 70°F

(2) CONSOLE (Attached)

Cabinet	Standard design
Wood & Finish	Rift Sawn Oak to customer's sample
Manuals	Two and Pedal
Manual Compass	CC to C4, 61 notes
Pedal Compass	CCC to G, 32 notes
Stop Controls	Tilting Tablets
Action	All Electric

(3) BLOWER (mounted within organ cabinet)

Type	Meidinger Style 602, .15 HP, 3360 RPM
Wind	120 c.f.m. @ 2-3/4"
Current Specification	1 Ph - 60 Cy - 115 Volts, 2.2 Amperes

(4) POWER UNIT (mounted within organ cabinet)

Rating	DC Output 10-15 Volts, 30 Amperes
Current Specification	1 Ph - 60 Cy - 115 Volts, 10 Amperes

CONSOLE AND ORGAN

MANUAL I

1	16	Gedeckt -----102 pipes
2	8	Rohrflöte -----from #1 -----61 notes
3	4	Principal -----78 pipes
4	2	Blockflöte -----from #1-----61 notes
5	1	Zimbel -----from #2--(repeat 7 top notes)-----61 notes

MANUAL II

6	8	Rohrflöte -----from #1-----61 notes
7	4	Spillflöte-----from #1-----61 notes
8	2	Octave -----from #2-----61 notes
9	1	Siffelöte-----from #1--(repeat 19 top notes)-----61 notes

ACCESSORIES

Motor and power unit on-off switch (lock type) with indicator light (amber jewel) and related electrical wiring.

Organ bench with music shelf

Rigid wood music rack

Music rack light

PIPE ANALYSIS

STOP	PITCH	PIPES	SCALE	HALVING	MOUTH	METAL	WIND PRESSURE	
Gedeckt	16	102	1-12 RMB Starting on #4 for scale but correct length for CCC					
			CCC 5-5/8" x 6-1/2" O.D.					
			BBB 3-11/16" x 4-7/16" O.D.					Wood
			13-24	Reg. Artiste tapered bass		Wood	1-12	4"
25-42	68	21-1/2 (Rohrflöte)	2/9	S.O.S. Chimney	13 up	2-3/4"		
43-61	76	18-1/2 (Spillflöte)	2/9	6 Zinc S.M.				
62 up	92	17-1/2 (Open Metal)	1/5	L.T.T. S.M.				
Principal	4	78	60	17-1/2	1-24	2/9	(3-23 inc. polished)	
					25 up	1/4	23 Zinc S.M.	