M. P. MÖLLER Organ Factory

| | 3-29 | neder date. | | |
|----------------------------------|--|--|--|--|
| Pipe Organ No | R-166 | Date January 29, 1985 | | |
| For | FIRST BAPTIST CHURCH, SEVIERVII | LLE, TENNESSEE | | |
| Action | Electro-Pneumatic | Console Present - Detached | | |
| Casing No | Enclosures - No change | Finish No Change | | |
| Decorations | None | Motor Present - 3 H.P., Style 140-9 | | |
| Width of Key-bed. | Standard | Stop Controls Draw Knobs & Tilting Tablets | | |
| No. Manuala | | Kewind Pressure Gr.3", Sw.,Ch., & Ped.3-1/2 | | |
| o be Completed_ | July 1, 1985 | Blower Pipe furnished by Present | | |
| | SPECIFICATI | ONS | | |
| | FOR REBUILDING AND ADDING TO MÖLLER ORGAN OPUS 10359 | | | |
| CONSOLE | Clean, repair, and polish cons | ole cabinet, bench and pedal keyboard. play additions according to specifications. | | |
| MANUAL, OFFSET & PEDAL CHESTS | Recover all pipe pouches. Recover all primaries and install new magnet armatures. Install all new stop action checks and eyelets. Install new actions as required. | | | |
| CHIMES | Install new Mayland 21 note ac volume control, present Deag | tion with canopy, relay, transformer, an Class 'M' tubes. | | |
| SWITCHES | Recover all electro-pneumatic Install new switches and diode | | | |
| RELAY | Clean and adjust contacts. Supply new enclosure for relay | and switches. | | |
| EXPRESSION | Recover all primaries and install new armatures. Recover all shade pneumatics. Replace all shade jacks and connecting rods. Refelt all shades. Repair, supply new and refinish swell partitions as required. | | | |
| RESERVOIRS | One 3'-0" x 4'-0" One 2'-6" x 4'-0" Two 2'-0" x 4'-0" One 1'-6" x 2'-0" | rs and install new curtain valves. | | |

Recondition present air-flow regulator Install new reservoirs as required for additions.

Two expression Two concussions TREMOLOS Install new electro-pneumatic tremolos.

PIPES Install new pipes as required. Revoice all pipes being reused.

Repack all wood pipe stoppers being reused.

Install slide tuners as required.

CABLES Install new plastic covered cables and action current wires

between console and organ.

ACTION CURRENT Install new 10-15 volts, 30 amperes DC organ power unit with

air switch.

BLOWER Reuse present 3 H.P., Style 140-9 motor and blower without change.

Install new flexible connection on wind (baffle) box.

Reline wind boxes with felt.

MISCELLANEOUS Great Organ:

Replace top note pipes as required.

Wash and refinish 8 Principal 1 - 3 and 16 Contre Basse 13-15. Refinish portions and replace return on existing panelwork.

Supply new racks for Great chests.

GENERAL All parts specified to be rebuilt to be returned to factory of

M. P. Moller, Inc., Hagerstown, Maryland.

All parts from present organ not required to complete this program

are to be removed and become the property of M. P. Moller, Inc.

SPECIFICATIONS

FOR

ORGAN AND CONSOLE

MANUAL COMPASS

PEDAL COMPASS

ACTION CONSOLE

PITCH

CC to C4, 61 notes CCC to G, 32 notes Electro-Pneumatic

Present, rebuilt as specified

A-440 @ 70^OF

GENERAL Present pipes and action except as noted, rebuilt and revoiced

in factory according to specifications.

Tone finishing in Church by head factory finisher.

| | | GREAT ORGAN - Exposed 10 | |
|----------|---------------|--|-------|
| . 1 | 16 | Gedackt Pommer#1-24 present Swell 16 Rohrgedeckt pipes, | |
| | | new action, #25 up new pipes & action85 p | |
| 2 | 8 | Principalpresent pipes & action61 p | pipes |
| 3 | 8 | Bourdon | ipes |
| 4 5 | 4 | Octave present pipes & action | |
| 6 | 4 2 | Gedackt | ines |
| 7 | | MixtureFormula ''A''present pipes & action208 p | |
| * 8 | 8 | Trompette enChamadenew pipes & action | pipes |
| | (*) not affec | ted by couplers | |
| | | SWELL ORGAN - Enclosed 9 | |
| 9 | 16 | Rohrgedeckt#1-24 new pipes present action, #25 up present pipes and action | pipes |
| 10 | 8 | Rohrflötefrom #9 | notes |
| 11 | 8 | Viole de Gambepresent pipes & action61 p | pipes |
| 12 | 8 | Viole Celeste T.Cpresent pipes & action | |
| 13 14 | 4 2 | Principalpresent pipes & action | pipes |
| 15 | III Rks. | Plein JeuFormula 'B''present pipes & action183 | pipes |
| 16 17 | 8 | Trompettenew pipes, present action | pipes |
| | | CHOIR ORGAN - Enclosed 7 | |
| 18 | 8 | Gedecktpresent pipes & action61 | pipes |
| 19 | 8 | Erzählerpresent pipes & action61 | pipes |
| 20 | 4 | Koppelflötefresent pipes & action61 | pipes |
| 21 | 2-2/3 | Nazardpresent pipes & action | pipes |
| 22 23 | 2 | Blockflötepresent pipes & action | pipes |
| * 24 | 8 | Krummhornnew pipes, present action | notes |
| 25 | | Chimesnew Mayland electric action with canopy, relay, | |
| | | transformer, and volume control, present Deagan 'M' | |
| | | bells, A to F, #22 to 4221 | bells |
| 26 | | Tremulant | |
| 27 | | Harp(console only) | |

(*) Not affected by couplers

FIRST BAPTIST CHURCH, SEVIERVILLE, TENNESSEE

R-166

PAGE 3

PEDAL ORGAN 3

| 28 | 16 | Contrebass#1-12 new pipes & action |
|----------------------|-------------------|------------------------------------|
| 29 30 31 32 | 16 8 8 4 | #13 up present pipes & action |
| 33 | 4 | 72 |
| 34 | 2 | Octavinirom #32 |
| 35 36 | 16 8 | 1 ago con control of mines |
| 37 | 4 | Fagot |
| | | |

COUPLERS

| 38 | Great to Pedal 8 | 49 | Suroll to Chain 16 |
|----|-------------------|----|--------------------|
| 39 | Swell to Pedal 8 | 50 | Swell to Choir 16 |
| 40 | Swell to Pedal 4 | 51 | Swell to Choir 8 |
| 41 | Choir to Pedal 8 | | Swell to Choir 4 |
| 42 | Choir to Pedal 4 | 52 | Great 4 |
| 43 | Swell to Great 16 | 53 | Swell 16 |
| 44 | Swell to Great 8 | 54 | Swell Unison Off |
| 45 | Swell to Great 4 | 55 | Swe11 4 |
| 46 | | 56 | Choir 16 |
| 47 | Choir to Great 16 | 57 | Choir Unison Off |
| 48 | Choir to Great 8 | 58 | Choir 4 |
| 40 | Choir to Great 4 | | |

ADJUSTABLE COMBINATIONS

| Affecting Great Affecting Swell Affecting Choir Affecting Pedal Affecting Full Organ (duplicated by toe stud |
|--|
| |

PEDAL MOVEMENTS

ACCESSORIES

Concave, radiating pedal clavier Organ bench with music shelf Light for music rack Light for pedal clavier Key operated motor switch