

#2066
1985 3/26

THE REUTER ORGAN COMPANY
LAWRENCE, KANSAS

PROPOSES A THREE MANUAL AND PEDAL PIPE ORGAN

FOR

ST. STEPHEN'S EPISCOPAL CHURCH
BEAUMONT, TEXAS

APRIL 27, 1984

Mr. Tom Crow, Reuter Representative
12519 Kittybrook, Houston, Texas 77071

2066

THE *Reuter* ORGAN COMPANY

GENERAL SPECIFICATIONS

CONSOLE	Detached, with organist's bench with blocks for adjustment, safety music rack with fluorescent light at base, and console case; <i>back rest for bench</i>
MANUALS	Compass CC to C4, 61 notes; simulated tracker touch.
PEDAL	Compass CCC to G, 32 notes, American Guild of Organist's standard, with light.
REGISTRATION	Controlled by drawknobs. The intra-manual couplers are controlled by knobs placed with their respective groups, and the intermanual and manual to pedal couplers are controlled by tilting tablets placed above the top manual.
ACTION	Reuter's electro-pneumatic chests with pitman stop action.
PITCH	A-440 Hz at 70° F.
CASEWORK	None. Such casework as may be desired to enclose the mechanical portions of any exposed pipework to be furnished by the Purchaser.
SWELL ENCLOSURE	A plywood Swell enclosure will be provided by The Reuter Organ Company of Reuter's standard triple-wall type. The exterior of the Swell enclosure to be covered with suitable hardwood by the Purchaser.
ORGAN STRUCTURAL SUPPORTS	Such structural supports as may be required for any exposed sections are to be furnished by the Purchaser, and located to specifications provided by The Reuter Organ Company.
WIND AND POWER	An organ blower with motor of ample capacity and a static reservoir. An action power unit of ample capacity with current indicator light in the console.

2066

GREAT ORGAN

- | | | |
|-----|---|--|
| 1. | 8' Principal | 61 pipes. |
| 2. | 8' Bourdon | 61 pipes. |
| 3. | 4' Octave | 61 pipes. |
| 4. | 4' Spillflöte (Preparation) | |
| 5. | 2' Flachflöte | 61 pipes. |
| 6. | IV Mixture (Present pipes) | 244 pipes. |
| 7. | 8' (Sw) Trumpet | |
| 7a. | 8' (Pos) <i>Trompette en chamade (Prep)</i> | |
| | Chimes | Present chimes and
action to be reused. |
| | Couplers to Great: | |

Great to Great 16'

Great Unison Off

Great to Great 4'

Swell to Great 16'

Swell to Great 8'

Swell to Great 4'

Positiv to Great 16'

Positiv to Great 8'

Positiv to Great 4'

2066

SWELL ORGAN

8.	16' Rohrflöte	97 pipes.
9.	8' Rohrflöte	
10.	8' Viola	61 pipes.
11.	8' Viola Celeste (CC)	61 pipes.
12.	4' Spitzprincipal	61 pipes.
13.	4' Rohrflöte	
14.	2 2/3' Nasard	61 pipes.
15.	2' Blockflöte	
16.	1 3/5' Tierce	61 pipes.
17.	IV Mixture	244 pipes.
18.	16' Oboe (1/2 L) (Preparation)	
19.	8' Trumpet	73 pipes.
20.	8' Oboe (Preparation)	
21.	4' Clarion	
21a.	8' <i>(Pao) Trompette ou Chamade (Prep)</i> Tremolo	

Couplers to Swell:

Swell to Swell 16'

Swell Unison Off

Swell to Swell 4'

2066

POSITIV ORGAN

22.	8' Gedeckt	61 pipes.
23.	8' Erzähler (Preparation)	
24.	8' Erzähler Celeste (Preparation)	
25.	4' Koppelflöte	61 pipes.
26.	2' Principal	61 pipes.
27.	1 1/3' Larigot	61 pipes.
28.	III Mixture (Preparation)	
29.	8' Krummhorn	61 pipes.

Tremolo

Couplers to Positiv:

Positiv to Positiv 16'

Positiv Unison Off

Positiv to Positiv 4'

Swell to Positiv 16'

Swell to Positiv 8'

Swell to Positiv 4'

29a 16' Trompette en Chamade ^(re) (Prep)
29b 8' " " " "
29c 4' " " " "

2066

PEDAL ORGAN

30. 32' Resultant
31. 16' Principal 1-12 new; 56 pipes.
13-56 present pipes
32. 16' Subbass present pipes 56 pipes.
33. 16' (Sw) Rohrflöte
34. 8' Principal
35. 8' Subbass
36. 8' (Sw) Rohrflöte
37. 4' Principal
38. 4' Subbass
39. III Mixture (Preparation)
40. 16' Bombarde (Full Length) 12 pipes.
41. 16' (Sw) Oboe (Preparation)
42. 8' Bombarde (Preparation)
43. 8' (Sw) Trumpet
44. 4' Bombarde (Preparation)

Couplers to Pedal:

Great to Pedal 8'

Great to Pedal 4'

Swell to Pedal 8'

Swell to Pedal 4'

Positiv to Pedal 8'

Positiv to Pedal 4'

44a. 8' (Pos) Trompette en Chamade (Prep)
44b. 4' " " " " " "

2066

ADJUSTABLE COMBINATIONS

Operated by pistons under their respective manuals.
Adjustable at keyboard and visibly affecting stop controls.

Six thumb pistons affecting the Great stops and intramanual couplers

Six thumb pistons affecting the Swell stops and intramanual couplers

Six thumb pistons affecting the Positiv stops and intramanual
couplers.

Six toe pistons affecting the Pedal stops only.

Ten thumb pistons affecting all stops and couplers of the entire
organ, duplicated on toe pistons.

General Cancel thumb piston.

Setter thumb piston.

REVERSIBLES

Great to Pedal, thumb and toe pistons.

Swell to Pedal, thumb and toe pistons.

Full Organ, thumb and toe pistons, with indicator light.

Positiv to Pedal, thumb & toe pistons

PEDAL MOVEMENTS

Register Crescendo Pedal, with indicator light.

Balanced Shutter Pedal, Swell Organ.

Necessaries

Cymbelstern

2066