THE REUTER ORGAN COMPANY LAWRENCE, KANSAS

PROPOSES A THREE MANUAL & PEDAL PIPE ORGAN

FOR

CHRIST UNITED METHODIST CHURCH, TULSA, OKLAHOMA

September 27, 1976

Frank R. Green. Home Office Sales Representative.

THE REUTER ORGAN COMPANY

217/

GENERAL SPECIFICATIONS

MANUALS

Compass CC to C4, 61 notes.

PEDAL

Compass CCC to G. 32 Notes.

KEYBOARDS

Manual Naturals: Genuine Maple-faced.

Pedal Naturals: Genuine Maple.

Manual Sharps: Genuine Rosewood-faced.

Pedal Sharps: Genuine Rosewood.

ACTION

Reuter's pitman, electro-pneumatic.

REGISTRATION

Speaking stops, Tremulants, and intramanual couplers controlled by Draw Knobs.

Inter-manual couplers controlled by Tilting tablets, rounded at top and bottom (no hyphens to be used in the engraving of

the stop names .

CONSOLE

Detached, wood and color-finished to Purchaser's sample. Plain, slab panels

console to be provided.

CASEWORK OR GRILLE

None. except that for consode.

ORGAN CHAMBERS

The present organ chambers to be enlarged, in accordance with architect's plans, but also subject to Reuter approval Such enlargement and/or renovation of the

existing organ chambers will be the

expense of the Purchaser.

INSTALLATION OF THE GREAT ORGAN AND THOSE STOPS OF THE PEDAL ORGAN DESIGNATED AS BEING UNENCLOSED and/or DISPLAYED

Essentially as shown in The Reuter Organ Company color drawing submitted in October 1974, but in keeping with specifications dated September 27, 1976.

GREAT ORGAN (Unenclosed and/or Displayed)

1.		81	Principal	61	Pipes.
2.		81	Bourdon	61	Pipes.
3. 4.		41	Octave SA) // Flote Flochflöte Principal	61	Pipes. Pipes.
5.		IV	Fourniture	244	Pipes.
6.	#	81	Trompette-en-Chamade	61	Pipes.
7•			Chimes (Console Preparation only, including 25 notes, G to G, switch	.).	

Couplers to Great:

Great to Great 16'
Great Unison Off
Great to Great 4'

Swell to Great 16'
Swell to Great 8'

Swell to Great 4'

Choir to Great 16'

Choir to Great 8'

Choir to Great 4'

Not to be affected by any couplers.

THE Reuter ORGAN COMPANY

SWELL ORGAN (Expressive)

-			
8.	16*	Rohrflöte	73 Pipes.
9.	8'	Rohrflote	
10.	81	Viola da Gamba	61 Pipes.
11.	8'	Viola Celeste (GG)	54 Pipes. Gr Pipes.
12.	= 4	Spitzflöte	73 Pipes.
13.	2 2/3'	Nesard	61 Pipes.
14.	21	Spitzflöte	
15.	1 3/5'	Tierce	61 Pipes.
16.	16	Contra Bassoon	73 Pipes.
17.	81	Trompette	73 Pipes.
18.	81	Oboe-Bassoon	
19.	* 8	Vox Humana (onsole Prep.only)	G. Here.
20.	41	Clairon	
21.		Tremulant	

Couplers to Swell:

Swell to Swell 16'
Swell Unison Off
Swell to Swell 4'

- * Not to be affected by Tremulant unless it is drawn.
- = Large-scale, tapered, flutey-principal.

		en la companya di managana	
CHOIR ORG	AN (Exp	ressive)	
22.	81	Holzgedackt	61 Pipes
23.	8'	Dolcan (not slotted)	61 Pipes
24.	81	Dolcan Celeste (GG) (not slotted)	54 Pipes
25.	4.	Koppelflöte	61 Pipes
26.	21	Principal	61 Pipes
27.	1 1/3'	Quint	61 Pipes
28.	1'	Zauberflöte	61 Pipes
29.	8.	Krummhorn	61 Pipes
30.		Harp-Chrysoglott, (Console Preparation only, including 61 notes switch).	
31.		Tremulant	
32.	# 16'	Trompette-en-Chamade (tc)	
33•	# 81	Trompette-en-Shamade	
34.	# 41	Trompette-en-Chamada (c3)	
		Couplers to Choir:	
		Choir to Choir 16'	
		Choir Unison Off	
		Choir to Choir 4'	
		Swell to Choir 16'	
		Swell to Choir 8'	
		Swell to Choir 4'	

Not to be affected by any couplers.

THE Reuter ORGAN COMPANY

GALLERIE ORGUE: (Complete console preparation only) 18 35. Bourdon Doux 36. 8 Flute de Bois 37. 8 Flute de Bois Celeste 38. 4. Prestant Flute a Bec 21 39. 40. III Plein Jeux 8 41. Chalumeau 42. 16' Pedale Bourdon 43. Tremulant GALLERIE ORGUE CONTROLS: Gallerie on Great Great Off Gallerie on Swell Swell Off Gallerie on Choir Choir Off Blank Blznk

When installed, the Gallerie division will be affected by the couplers native to the manual from which it is played.

^{**} When installed, to be in an expression enclosure.

PEDAL ORGAN	(+ Unenclosed and/or under expression)	displayed; all	others to be
44.	32 • Acoustic Bourdon		Resultant.
45. +	16' Principal		44 Pipes.
46. +	16' Bourdon		44 Pipes.
47.	16' (Sw) Rohrflöte		
48. +	8' Principal		
49. +	8' Bourdon		
50.	8' (Sw) Rohrflöte		
51. +	4º Choralbass		32 Pipes.
52.	4 (Sw) Rohrflöte		
53. +	III Mixture		96 Pipes.
54. +	16' Bombarde		56 Pipes.
55.	16' (Sw) Contra Bas	soon	
56. +	8 Bombarde		
57. +	4º Bombarde		
58.	4 (Sw) Oboe-Basso	oon	
	Chimes Podele Bonda Cp- Couplers to Pede	il:	
	Great to Pe	edal 8°	
	Great to Pe	edal 4	
	Swell to Pe	edal 8'	
	Swell to Pe	edal 4	
	Choir to Pe		
	Choir to Pe	edal 4	

THE Feuter ORGAN COMPANY

ADJUSTABLE COMBINATIONS: (Solid State, Capture System). Operated by pistons under their respective manuals. Adjustable at keyboard and visibly affecting stop controls.

Six thumb pistons acting on the Great stops.

Six thumb pistons acting on the Swell stops.

Six thumb pistons acting on the Choir stops.

toe pistons acting on the Pedal stops. Six

Ten General pistons acting on all stops and couplers of the entire organ, duplicated on toe pistons.

General Cancel thumb piston, mounted extreme right under Choir manual. Setter Piston.

REVERSIBLES:

Great to Pedal, duplicated on thumb piston.

Swell to Pedal, duplicated on thumb piston.

Choir to Pedal, duplicated on thumb piston.

Tutti. duplicated on thumb piston.

Cymbelstern, duplicated on thumb piston.

PEDAL MOVEMENTS:

Balanced Swell Shutters Expression Pedal.

Balanced Choir Shutters Expression Pedal.

Gallerie Organ Shutters Expression Pedal to be connected for use when the Gallerie Organ is installed, and to affect only the pair of Fluits de Boid.

Register Crescendo Pedal.

CHOIR NAVE SHUTTERS ON-OFF Swell NAVE SHUTTERS ON-OFF

Current Indicator Light, green.

Crescendo Indicator Light, amber.

Tutti Indicator Light, red.

Solid wood music rack, with built-in at base, fluoreseent light.

Crank style Organ Bench, with curved front.

Concave, Radiating Pedal Keyboard, A. G. O. standard.

THE Reuter ORGAN COMPANY

ACCESSORIES, continued:

Concealed type Pedal Keyboard Light.

Blower & Motor of ample capacity, 3 HP, (Laukhuff or Meidinger), for Main Organ only. (Gallerie Organ, eventually, will have its own blower).

Action Current Power Unit.

Lined Static Pressure Control Reservoir on Blower.

Digital Clock mounted inconsole.

Concussion "winkers" for stabilized air pressures at all times.
Three Pedal Reservoirs for the Main Organ.

Unwired Singnal Button, mounted in console and labeled NARTHEX.

The foregoing specifications employed a total of 35 ranks and 1.892 Pipes. (When the Gallery Division is added the organ 1,953 will then have a total of 45 ranks and 2.466 Pipes).