# M. P. MÖLLER Organ Factory

. V	other colors and the state of the colors and the co	and the second of the second o
Pipe Organ No	R-708	Date June 3, 1963
For	St. Paul's Methodist Church	Hagerstown, Md.
Action	Electro-Pneumatic	Console Present - rebuilt and refinished
Casing No	None	Finish To customer's selection
Decorations	None	MotorNew Style 3-P-3328 Blower & new DC
Width of Key-bed	Standard	Stop Controls Draw knobs & tilting tablets
No. Manuals	Three and Pedal	Wind Pressure 6+.35", 5w.cl. 5", 84.35"5"
To be Completed	October 1, 1963	Blower Pipe furnished by M. P. M., Inc.
	SPECIFICATI	ONS
	FOR	
	REBUILDING PRESENT MOLLER OF	GAN OPUS 3030-1921 (Rebuilt 1941)
CONSOLE	Rebuild existing console as	follows:
	Rework present combination a Install three new reversible Install two new expression rational new crescendo roller Install new sforzando mechan Install new 29 note primary Install two new console term Install new expression pedal Recover five combination procession pedal Recover five combination procession console.  Refelt console completely. Refelt pedal keyboard completon wiper wires.  Refinish console, organ bence the console complete console.	equired. on present combination pistons.  action to conform to revised specifications. actions. coller switches with silver contacts. co
GREAT ORGAN	Install new unenclosed Great	Organ division, complete, as specified.
MANUAL CHESTS	plugs and armatures. Releather one 73 note primar and armatures.	
OFFSET ACTIONS	Releather Swell 16 Gedeckt a new magnet plugs and armatum Releather Swell 8 Violin Dia	unit action #1 to #97 and install res. apason action #1 & #2.

48168

wire contact blocks.

Releather one 73 note Swell Contact Box and install new silver

CONTACT BOX

SWITCHES

Install the following new electro-pneumatic switches with stop actions:

Swell 16 Gedeckt 73 notes Swell 8 Gedeckt 73 notes Swell 4 Flute d Amour 73 notes

CHIMES

Releather and refelt present 20 note Chime action. Recover 20 chime pneumatics.
Install new tube and action for Top F#42.

HARP

Releather and refelt present 49 note Harp action. Recover 49 harp pneumatics.

PEDAL ORGAN

Releather 16 Diapason action #1 to #32 incl. and install new magnet plugs and armatures.

Releather 16 Bourdon action #1 to #44 incl. and install new magnet plugs and armatures.

Releather 16 Trumpet action #1 to #12 incl. and install new magnet plugs and armatures.

Releather 20 note primary for 16 Trumpet.

Install new action for 8 Octave #1 to #56 incl.

Install new 32 note Pedal Relay with eight 32 note switches.

EXPRESSION

Releather 8 note expression action for Swell Organ.
Releather 10 note expression action for Choir Organ.
Recover 18 shade and bumper pneumatics.
Install 18 new shade jacks with connecting rod assemblies.

RESERVOIRS

Recover the following existing reservoirs and install new curtain valves as required:

One (1) 3°-O" x 5°-O" Manual reservoir
One (1) 3°-O" x 4°-O" Manual reservoir
One (1) 1°-9" x 3°-O" Pedal reservoir
One (1) 16" x 21" Cone Valve reservoir
One (1) Blower reservoir
One Chimes reservoir
One Harp reservoir
Two Expression reservoirs

TREMOLOS

Install three new electro-pneumatic tremolos.

PIPFS

Install the following new pipes on new actions: 13

Great	16	Quintaton	61 Pipes
Great	8	Diapason	61 Pipes
Great	8	Rohrflote	61 Pipes
Great	4	Octave	61 Pipes
Great	2	Doublette	61 Pipes
Great	IV	Fourniture	244 Pipes

```
PIPES (Contid)
```

Install the following new pipes on present actions:

Swell	III	Plein Jeu	183 Pipes				
Swell	8	Trompette	73 Pipes				
Swell	1	Clarion	61 Pipes			#61	
Choir	4	Gemshorn	Pipes	(#50	to		incl)
Choir	2-2/3	Nazard	61 Pipes				
Choir	2	Blockflöte	61 Pipes				
Choir	1-3/5	Tierce	61 Pipes				
Choir	8	Harmonic Trumpet	61 Pipes				
Pedal	16	Trumpet	12 Pipes				

CABLES

Install new plastic covered cables between console and organ.

Install new action current wires between console, organ and blower.

BLOWER

Install new 5 HP, Style 3-P-3328 Kinetic Blower.

ACTION CURRENT

Install new 30 ampere DC organ power unit.

GENERAL

The entire organ to be returned to factory of M. P. Moller, Inc. at Hagerstown, Md. for reworking and rebuilding as specified above.

# SPECIFICATIONS FOR CONSOLE AND ORGAN

MANUAL COMPASS
PEDAL COMPASS
WIND PRESSURE
PITCH

CC to Ch, 61 Notes CCC to G, 32 Notes C+.3\(\frac{1}{2}\), 5 \(\tilde{1}\), 5 \(\frac{1}{2}\), 5 \(\frac{1}2\), 6 \(\frac{1}2\), 6 \(\frac{1}2\), 6 \(\frac{1}2\),

### GREAT ORGAN (unenclosed) 9

1234567	16 8 4 2 17	Quintaton
-		to #lil incl; new top F #li2 tube and action. A to F #22 to #li2 incl

8

Tremolo

山 山 山 山 山

45

4

2

Pistons No. 1-2-3-4-5-6

16

# #

## PEDAL ORGAN (\*) 3

35	TO	Diapason present Great to Double Open Diapason ' L Lywll & Open
		pipes; present Pedal 16 Open Diapason present Swell 8 Open pipes; present Pedal 16 Open Diapason Pipes 25 Trup
		action
36	16	Bourdonpresent pipes; present action
37	16	Gedecktes as a consecution #9 and a consecution and 32 Notes
38	8	Octavepresent Swell 8 Open Diapason pipes #1-12 present Areat 16 Double new action
		new action
39	8	Bourdon32 Notes
40	8	Gedeckt32 Notes

Trumpet.....new pipes, present 16 Tuba action #1-12; 20 from #32......32 Notes

(\*) Pedal Organ playable thru new Pedal Relay and Switches to be supplied by MPM, Inc.

### COUPLERS (no change except as indicated by \*)

#### 59 60 Great to Pedal Great L Great to Pedal L Choir to Swall 16 61 Swell to Pedal Choir to Swell 62 Swell to Pedal L Choir to Swell h 63 Choir to Pedal Swell 16 64 Choir to Pedal L Swell Umison Off 65 Swell to Great 16 Swell L 66 Swell to Great Swell to Choir 16 Swell to Great L 67 Swell to Choir Choir to Great 16 68 Swell to Choir 4 Choir to Great 69 Choir 16 Choir to Great h 70 Choir Unison Off Great 16 71 Choir h Great Unison Off

### ADJUSTABLE COMBINATIONS (no change except as indicated by \*) Affecting Great Organ (with cancel bar)

Pistons No. 1-2-3-4-5-6 Affecting Swell Organ (with cancel bar) Pistons No. 1-2-3-4-5-6 Affecting Choir Organ (with cancel bar) Pistons No. 1-2-3-4-5 \*Affecting Pedal Organ (with cancel bar) Pistons No.11-2-3-4-5-6-7-8 \*Affecting Full Organ (pistons #1 to #5 duplicated by toe studs) General Cancel Piston

#### PEDAL MOVEMENTS

- 1- Great to Pedal Reversible.
- 2- Swell to Pedal Reversible.
- 3- Choir to Pedal Reversible.
- 4- Balanced Expression Pedal Swell Organ (8 contacts, regular system) with indicator disc.
- 5- Balanced Expression Pedal Choir Organ (10 contacts, regular system) with indicator disc.
- 6- Balanced Expression Pedal Schulmerich Chimes.
- 7- Balanced Crescendo Pedal with indicator disc.
- 8- Sforzando Reversible (duplicated by manual piston) with indicator light (red jewel)

#### ACCESSORIES

Present music rack light.

Present concave and radiating pedal keyboard.

Present organ bench with music shelf.

New 5 HP Kinetic Blower and new DC organ power unit of ample capacity.

Pedal light