THE REUTER ORGAN COMPANY LAWRENCE, KANSAS

PROPOSES A FOUR MANUAL AND PEDAL MEMORIAL PIPE ORGAN

FOR

FIRST BAPTIST CHURCH
HATTIESBURG, MISSISSIPPI

SEPTEMBER 25, 1986

(REVISED DECEMBER 15, 1986)

James Scoggins, Reuter Representative Box 2323, Jackson, Mississippi 39205

## GENERAL SPECIFICATIONS

CONSOLE

Detached, with organist's bench with crank for adjustment; adjustable, safety glass music rack with fluorescent light at base, console case with roll top and lock, and recessed wheels on console with 40 feet of cable.

MANUALS - 4

Compass CC to C4, 61 notes. Simulated tracker touch.

PEDAL

Compass CCC to G, 32 notes, American Guild of Organists standard, with light.

REGISTRATION

Controlled by draw knobs. The intramanual couplers are controlled by knobs placed with their respective groups, and the intermanual and manual to pedal couplers are controlled by tilting tablet placed above the top manual.

ACTION

New Great and Positiv chests are electropneumatic. Concussion bellows will be added to the existing chestwork to aid wind steadiness.

PITCH

A-440 Hz at  $70^{\circ}$  F.

CASEWORK

Case to cover the mechanical portions of the exposed chestwork to be painted (manufacturer and paint number supplied by purchaser) to harmonize with the other woodwork in the building.

ORGAN CHAMBER

Suitable, finished chamber to be furnished by the purchaser. Such structural supports as may be required for any exposed sections are to be furnished by the purchaser, and located to specifications provided by The Reuter Organ Company. Reuse the existing Swell Shades for the Ancillary and Swell divisions.

WIND AND POWER

The existing organ blower will be retained. In the unlikely event that the existing blower proves inadequate for proper results, an appropriate blower will be installed at extra cost. action power unit of ample capacity with current indicator light in the console will be provided by The Reuter Organ Company. An auxiliary booster blower for the Festival Trumpet will be included.

The builder will dispose of any unused portions of the organ.

THE REUTER ORGAN COMPANY

GREAT	ORGAN	(Expo	osed) - All new pipes and che	ests
1.		8 '	Principal	61 pipes.
2.	*	8 '	Bourdon	61 pipes.
3.		4 '	Octave	61 pipes.
4.		2 '	Flachflöte	61 pipes.
5.		VI	Fourniture	244 pipes.
6.	•	16 <b>'</b>	(Anc) Clarinet (TC)	
7.	*	8'	Festival Trumpet	61 pipes.
8.	**	8'	Trompette en Chamade (Prepa	ration)
			Chimes (New relay to play chimes and action)	existing
			Couplers to Great:	
			Great to Great 16'	
			Great Unison Off	
			Great to Great 4'	
			Swell to Great 16'	
			Swell to Great 8'	
			Swell to Great 4'	
			Positiv to Great 16'	
			Positiv to Great 8'	
			Positiv to Great 4'	
			Ancillary to Great 16'	
			Ancillary to Great 8'	
			Ancillary to Great 4'	

<sup>\*</sup> Placed in Ancillary Chamber. \*\* Not affected by couplers.

SWELL ORGAN - New	pipes on existing chests unle	ess noted.
30. 8'	Rohrflöte (Existing pipes)	61 pipes.
3,1. 8'	Viola	61 pipes.
32. 8'	Viola Celeste (TC)	49 pipes.
33. 4'	Principal	61 pipes.
34. 4'	Hohlflöte	61 pipes.
35. 2 2/3'	Nasard	61 pipes.
36. 2'	Blockflöte	61 pipes.
37. 1 3/5'	Tierce (new chest)	61 pipes.
38. IV	Cymbel (new chest)	244 pipes.
39. 16'	Fagotto	73 pipes.
40. 8'	Trompette	73 pipes.
41. 8'	Fagotto	
42. 8'	Oboe (Existing pipes; revoiced)	61 pipes.
43. 8'	Vox Humana (Preparation)	
44. 4'	Trompette	
	Tremolo	
	Swell Nave Shutters Closed	
	Couplers to Swell:	
	Swell to Swell 16'	
	Swell Unison Off	
	Swell to Swell 4'	
	Ancillary to Swell 16'	
	Ancillary to Swell 8'	
	Ancillary to Swell 4'	

POSITIV	ORGAN (	Exposed) - All new pipes and chests
9.	8'	Gedeckt 61 pipes.
10.	4 '	Spitzflöte 61 pipes.
11.	2'	Principal 61 pipes.
12.	1 1/3'	Quinte 61 pipes.
13.	IV	Scharf 244 pipes.
14.	* 16 <b>'</b>	(Gt) Trompette en Chamade (TC)
15.	* 8'	(Gt) Trompette en Chamade
16.	* 4'	(Gt) Trompette en Chamade
		Couplers to Positiv:
		Positiv to Positiv 16'
		Positiv Unison Off
		Positiv to Positiv 4'
		Swell to Positiv 16'
		Swell to Positiv 8'
		Swell to Positiv 4'
		Ancillary to Positiv 16'
		Ancillary to Positiv 8'
		Ancillary to Positiv 4'

<sup>\*</sup> Not affected by couplers.

ANCILLARY	- Exis	ting pipes and chests except w	where noted
17.	16'	Rohrflöte	73 pipes.
18.	16'	Gemshorn (1-12 new pipes)	73 pipes.
19.	8'	Rohrflöte	
20.	8'	Gemshorn	
21.	8,'	Viole de Gambe	61 pipes.
22.	8'	Viole Celeste (TC)	49 pipes.
23.	8'	Dulciana	61 pipes.
24.	8'	Unda Maris (TC)	49 pipes.
25.	4'	Concert Flute	61 pipes.
26.	2 2/3'	Nasard	61 pipes.
27.	2 '	Flautino	61 pipes.
28.	8'	Clarinet (Existing pipes; revoiced)	61 pipes.
29.	8 '	(Gt) Festival Trumpet	
		Tremolo	
		Ancillary Nave Shutters Close	ed.
		Couplers to Ancillary:	
		Ancillary to Ancillary 16'	
		Ancillary Unison Off	
		Ancillary to Ancillary 4'	

PEDAL	ORGAN	(New	pipes and chests as indicated)
45.		32'	Resultant
46.		16'	Principal (new pipes; 44 pipes. present chest)
47.		16'	Bourdon (1-56 present pipes 56 pipes. & chests)
48.		16'	(Anc) Gemshorn
49.		16'	(Anc) Rohrflöte
50.		8'	Principal
51.		8'	Bourdon
52.		8 '	(Anc) Gemshorn
53.		4'	Choral Bass (New pipes; 32 pipes. present chest)
54.		4 '	Bourdon
55.		4 '	(Anc) Gemshorn
56.		2'	Flute (Present pipes 32 pipes. & chest)
57.		IV	Mixture (Present Swell 128 pipes.  Mixture pipes & chest revoiced & rescaled)
58.		16'	Posaune (New pipes; reuse 56 pipes. present resonator; present chest)
59.		16 <b>'</b>	(Sw) Fagotto
60.		8'	Posaune
61.		8'	(Sw) Fagotto
62.		4'	Posaune
63.		4 '	(Anc) Clarinet
64.		8'	(Gt) Trompette en Chamade
			Chimes
			Couplers to Pedal: Great to Pedal 8' Positiv to Pedal 8' Great to Pedal 4' Positiv to Pedal 4' Swell to Pedal 8' Ancillary to Pedal 8' Swell to Pedal 4' Ancillary to Pedal 4' THE Letter ORGAN CO
			THE Keller ORGAN O

THE Reuter ORGAN COMPANY

## ADJUSTABLE COMBINATIONS (Quad Memory)

An all-new solid-state combination action, operated by pistons under their respective manuals. Adjustable at keyboard and visibly affecting stop controls.

Eight thumb pistons affecting the Great stops and couplers.

Eight thumb pistons affecting the Swell stops and couplers.

Eight thumb pistons affecting the Positiv stops and couplers.

Eight thumb pistons affecting the Ancillary stops and intramanual couplers. Eight toe pistons affecting the Pedal stops and couplers.

Twelve thumb pistons affecting all stops and couplers of the entire organ, duplicated on toe pistons.

General Cancel, thumb piston.

Setter, thumb piston.

## REVERSIBLES

Great to Pedal, thumb and toe pistons.

Swell to Pedal, thumb and toe pistons.

Positiv to Pedal, thumb and toe pistons.

Ancillary to Pedal, thumb and toe pistons.

Swell to Great, thumb and toe pistons.

Positiv to Great, thumb and toe pistons.

Full Organ, thumb and toe pistons, with indicator light.

## PEDAL MOVEMENTS

Register Crescendo Pedal, with indicator light.

Balanced Shutter Pedal, Swell Organ.

Balanced Shutter Pedal, Ancillary.

Swell Nave Shutters Closed. (Stop knob in respective division.)

Ancillary Nave Shutters Closed. " " " " "