

SPECIFICATION No. 214

DATE May 3rd 1957.

DESIGNED FOR CENTRAL SQUARE BAPTIST CHURCH

PORTLAND, MAINE.

COMPASS OF MANUALS

CC TO C 61 KEYS

COMPASS OF PEDAL

CCC TO G 32 KEYS

FEET

PIPES

- GREAT ORGAN -
(Enclosed)

1-	Principal	8	68
2-	Bourdon	8	68
3-	Dulciana	8	68
4-	Octave	4	68
	Blank		
	Blank		
	Tremulant		
	Chimes prepared for Console only.		

- SWELL ORGAN -

	Blank		
5-	Rohrflöte OR Corderoite	8	68
6-	Salicional	8	68
7-	Voix Celeste (GG)	8	61
8-	Gemshorn	4	68
9-	Nazard	2 2/3	61
10-	Piccolo	2	61
11-	Closed Horn	8	68
	Tremulant		

as per telephone conversation
R.L. Strout - J.A. Chagnon 5/2/57

- PEDAL ORGAN -

12-	Subbass	16	32
13-	Gedeckt, ext. fr. #5	16	12
14-	Bass Flute 20 fr. #12	8	12
	Blank		

- COUPLERS -

- Great to Pedal
- Swell to Pedal
- Great Super to Pedal
- Swell Super to Pedal
- Swell Sub to Great
- Swell to Great
- Swell Super to Great
- Swell Sub
- Swell Super
- Great Super

2445

- ADJUSTABLE COMBINATION PISTONS -

1,2,3 to Great
1,2,3 to Swell
1,2,3 to Entire Organ

1 Reversible Great to Pedal

- BALANCED PEDALS -

Expression Pedal to Great
Expression Pedal to Swell
Crescendo on all stops and couplers

- INDICATORS -

Wind
Crescendo

Electro Pneumatic Action.

The organ to be of one unit located in one organ chamber, Great Organ to be enclosed, and with louvers facing chancel and nave.

No Case work nor display pipes to be provided by the Builders.

The action to be electro-pneumatic, Stop-action and couplers to be operated by tilting tablets above the keyboards.

The console to be detached and located about 25 feet from the organ; unless otherwise specified the exterior woodwork will be of oak and the interior fittings such as key frames, stop-jambs etc., will be of polished walnut. Music rack to be of tempered plate-glass, and the organ bench same as the console casing.

The Electric Blower with Motor, and Rectifier of ample capacity to be supplied by the Builders.

Wiring and switches to and from Motor to Console and organ to be at the expenses of the Purchasers.