M. P. MÖLLER Organ Factory

Pipe Organ No	R-138	Date July 27, 1982
	LUTHERAN CHURCH OF THE HOLY TO	RINITY, EPHRATA, PENNSYLVANIA
Action	Electro-Pneumatic	Console Present - Detached
Casing No	Present Grilles - no change	Mojor Present 5 HP, Style 3-P-3328
Decorations	None Pareling for (rempete	Mojor Present 5 HP. Style 3-P-3328
Width of Key-bed	Standard	Stop Controls Draw Knobs & Tilting Tablets
No. Manuale	THREE	Wind Pressure 4-1/2", Sw. Bdn & Ped Pos 5'
To be Completed_	March 10, 1983	Wind Pressure 4-1/2", Sw. Bdn & Ped Pos 5' Thompotte Nasm: E. Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING AND CHANGING TONALLY PRESENT MÜLLER ORGAN OPUS 8336 - 1952

CONSOLE

Reuse present console rebuilding same as follows:

Replace all draw knobs & install new contacts.

Recover all coupler pneumatics.

Recover all combination pneumatics.

Recover all primaries and install new magnet armatures.

Recover all reversibles.

Replace crescendo and expression pedal pads and edging.

Replace burrs and felt washers on manual keys.

Refelt action as required.

Refelt pedal keyboard and install new insulating bushings.

Recover reservoir.
Recover roll top.

Install new knee panel and toe stud terraces, eliminating Great

expression pedal.

Clean and polish cabinet, bench and pedal keyboard.

Install new markers as required.

Install new pedal light.

MANUAL CHESTS

Recover all manual pipe pouches.

Replace stop action checks and eyelets.

Replace duplex shifters.

Recover two 73 note, one 48 note, and one 25 note primary stations

and install new magnet armatures.

Recover stop action primaries and install new magnet armatures.

Recover pedal primaries and install new magnet armatures.

Rework and/or install new toeboard/rackboard assemblies as required

for tonal changes.

FFSET & UNIT Recover the following actions and install new magnet armatures: ACTIONS 8 Great Principal Principal 11 notes 12 notes Swell 16 Bourdon Swell 8 Gemshorn 12 notes 61 notes Swell IV-V Swell 2 Blockflöte 61 notes Plein Jeu Choir 8 Flauto Dolce 8 notes 85 notes. Choir Principal Reuse present Chime tubes, install new electric action, transformer, HIMES volume control, and relays. CONTACT BOXES Replace single conductor contact box for Great 8 Principal #1-11. Recover two 73 note contact boxes and install new silver wire contact blocks. WITCHES Recover electro-pneumatic switches and stop actions and install new magnet armatures. PEDAL ORGAN Install new actions as required by specifications. Recover the following actions and install new magnet armatures: 16 Contrebasse 56 notes 16 Subbass 32 notes Reuse 2 present 32 note relays. Rework and recover present switches and stop actions and add new switches as required. EXPRESSION Eliminate Great expression. Recover one 10 note, one 8 note, one 6 note and two 4 note expression actions and install new magnet armatures. Recover all shade pneumatics. Replace all shade jacks and connecting rods. Refelt shades. RESERVOIRS Recover the following reservoirs and install new curtain valves as required: One 3-0 x 4-0 manual Two 2-6 x 4-0 manual

Two 2-6 x 4-0 manual
Three 1-6 x 2-6 offset
Two 1-6 x 2-0 offset
One 3-6 x 3-6 blower
Two expression

TREMOLOS

Install new electro-pneumatic tremolos.

PIPES

Install new pipes as indicated by organ specifications. Revoice all pipes being reused. Repack all wood pipe stoppers.

CABLES

Install new plastic covered cables between console and organ.

Install new action current wires between console, organ & DC organ power that

22

Tremolo

ACTION CURRENT	Reuse	present	DC	organ	power	mit	without	change.	
----------------	-------	---------	----	-------	-------	-----	---------	---------	--

BLOWER Reuse present 5 HP, Style 3-P-3328 motor and blower without change.

Install new motor-blower coupling leathers.

Install new 14" diameter flexible connection with draw bands.

GENERAL All parts specified above to be rebuilt to be returned to the factory of M. P. Möller, Inc. at Hagerstown, Maryland.

All parts from present instrument not required to complete this instrument become the property of M. P. Möller, Inc.

SPECIFICATIONS FOR CONSOLE AND ORGAN

		CONSOLE AND ORGAN
PEDA	JAL COMPASS AL COMPASS) PRESSURE TH	CC to C4, 61 notes CCC to G, 32 notes 4-1/2", Swell Bourdon & Pedal Posaune 5", Trompatte Hormonique 6" A-440 @ 70°F
		GREAT ORGAN - Unenclosed 10
2 3	8 4 4	Principalpresent Open Diapason pipes and action73 pipes Rohrflöte::85 pipes Octave
5	2-2/3	Nazard
6 7	2 1-3/5	Super Octave61 pipes Tierce#1-44 present 2 Fifteenth pipes #5-48, #45 up new pipes; present III 19th action
8 9 10	III-IV	Fourniturenew pipes; present 8 Gemshorn action
	g ^t	Trompette Harmonique (1)
		SWELL ORGAN - Enclosed 13
11 12	16 8	Bourdon
13	8	Gemshorn#1-12 present Great Gemshorn pipes; #13 up new pipes; present Open Diapason action
14	8	Gemshorn Celeste TCpresent Great Gemshorn pipes; present Gamba Celeste TC action
15 16	4	Principal73 pipes Spitzflöte73 pipes
17	Z IV-V	Blockflöte
19 20	8	Hauthoispresent Trumpet pipes and action
21	4	Clairon

R-138)	LUTHERAN CHURCH OF THE HOLY TRINITY, EPHRATA, PENNSYLVANIA	PAGE 4
		CHOIR ORGAN-Enclosed 6	
23 24	8	Holzgedecktnew pipes; present Flauto Traverso action Flauto Dolce#1-12 present Present Pipes, #13 up new pipes;	85 pipes
25 26 27	8 4 4	present Viola action	61 pipes 85 pipes 73 notes
28 29	2 1-1/3	Octavefrom #26	73 notes
30 31 32	8	Clarinetpresent pipes and action	61 notes 73 pipes
300	8	Trompette Harmonique men pipes and action (e draw know with Treat, not affected by coup	clerated pipes
33 34	32 16	Quinted Bass#1-12 as 10-2/3, from #35 Contrebasse#1-12 present Pedal Open Diapason, #13 up present Swell Open Diapason; #1-56 present	
35 36	16 16	Open Diapason action, #57 up new action Subbasspresent Bourdon pipes and action Bourdonfrom #11	32 pipes
37 38	8	Principal	32 notes
39 40	4 III	Mixture	32 notes
41 4/2 · 42	16 8 4	Posaume#1-32 present Trombone pipes and action, #33 up Trompert new pipes and action. Klarine#41#41#30a	
	* Peda	al Organ playable thru present relays, present and new switches.	
		COUPLERS	
43 44	Great to	SO SWOLL TO CHOKE TO	
45 46	Swell to		
47 48	Choir to		
49 50	Swell to	o Great 16 61 Swell Unison Off 62 Swell 4	
51 52 53	Choir to		
54	Choir to	o Great 4	•

Great	to Pedal		55	Swell to Choir 16
Great '	to Pedal	4	56	Swell to Choir
Swell :	to Pedal		57	Swell to Choir 4
Swell '	to Pedal	4	58	Great Unison Off
Choir	to Pedal		59	Great 4
Choir	to Pedal	4	60	Swell 16
Swell f	to Great	16	61	Swell Unison Off
Swell 1	to Great		62	Swell 4
Swell 1	to Great	4	63	Choir 16
Choir 1	to Great	16	64	Choir Unison Off
Choir	to Great		65	Choir 4
Choir t	to Great	4		

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
Toe Studs No. 1-2-3-4-5
Pistons No. 1-2-3-4-5
General Cancel

Affecting Great
Affecting Swell
Affecting Choir
Affecting Pedal (duplicated by manual pistons)
Affecting Full Organ (duplicated by manual pistons)

REVERSIBLES

Great to Pedal - manual piston and toe stud

Swell to Pedal - manual piston and toe stud

Choir to Pedal - manual piston and toe stud

Sforzando - manual piston and toe stud with indicator light

32 Quinted Bass - manual piston and toe stud (Present All Swells)

PEDAL MOVEMENTS

Balanced Expression Pedal - Swell Organ Balanced Expression Pedal - Choir Organ Balanced Crescendo Pedal with indicator light

ACCESSORIES

Concave, radiating pedal clavier
Organ bench with music shelf
Music rack with light
New pedal light
Present motor and blower
Present DC organ power unit