

M. P. MÖLLER Organ Factory

3-21/27

Pipe Organ No. 9055 Date October 30, 1956
 For FIRST METHODIST CHURCH, SARASOTA, FLORIDA
 Action Electro-pneumatic Console Detached
 Casing No. None Finish As per sample
 Decorations None Motor 5 H.P. - Style 3-P-3328
 Width of Key-bed Standard Stops & intra-manual couplers by draw
 Stop Controls knobs. Inter-manual by
tilting tablets.
 No. Manuals Three Wind Pressure Gt. 4", Sw., Ch., & Ped. 5"
 To be Completed 15 to 16 months after date Blower Pipe furnished by Purchaser

PITCH: A-440

SPECIFICATIONS

GENERAL: The church, at its expense, to make preparations in the building from plans
 by M. P. Moller, Inc. All freight charges are included in our proposal.

GREAT ORGAN (Unenclosed)

6+3

1.	16'	Quintaton.....	42.....	20 $\frac{1}{2}$	24 zinc..S.M....	61 pipes
2.	8'	Diapason.....	45.....	18 $\frac{1}{2}$	12 zinc..S.M....	61 pipes
3.	8'	Bourdon.....	50.....	21 $\frac{1}{2}$	12 zinc..S.M....	61 pipes
4.	4'	Principal.....	57.....	19 $\frac{1}{2}$	S.M....	61 pipes
5.	II Rks.	Mixture (12-15).....	2-A.....	19 $\frac{1}{2}$	S.M....	122 pipes
6.	III Rks.	*Furniture.....	Console only			
7.		Tremolo				
7A.		Chimes.....	Deagan "D"... (locate in Choir Expression Box).....			
			A to F...#22 to #42.....21 tubes			

SWELL ORGAN (Enclosed)

9+1

8.	8'	Gambe.....	52.....	18 $\frac{1}{2}$	12 zinc..S.M....	61 pipes
9.	8'	Gambe-Celeste (Low C).....	54.....	18 $\frac{1}{2}$	12 zinc..S.M....	61 pipes
10.	8'	Gedeckt.....	Reg. Stopped Flute.....Wood & metal. 61 pipes			
11.	4'	Octave Geigen.....	57.....	18 $\frac{1}{2}$	S.M....	61 pipes
12.	4'	Flute Harmonique.....	58.....		S.M....	61 pipes
13.	III Rks.	Plein Jeu.....	3-R-2.....	18 $\frac{1}{2}$	S.M....	183 pipes
14.	8'	Trompette.....	3".....			61 pipes
15.	4'	*Oboe.....	Console only			
16.		Tremolo				

CHOIR ORGAN (Enclosed)

4+2

17.	8'	Nason Gedeckt.....	Artiste Gedeckt.....wood & metal....61 pipes			
18.	8'	Dolcan.....	56-5/4.....	17 $\frac{1}{2}$	12 zinc..S.M....	61 pipes
19.	4'	Koppelflöte.....	64.....	20 $\frac{1}{2}$	S.M....	61 pipes
20.	2-2/3'	*Nasard.....	Console only			
21.	2'	Siffelöte.....	70-3/4.....	20 $\frac{1}{2}$	S.M....	61 pipes
22.		*Blank Knob.....	Console only			
23.		Tremolo				

PEDAL ORGAN

2

24.		*Blank Knob.....	Console only	
25.	16'	Sub Bass.....	Large Ped. Bdn.....	Low lip..Large Ears..56 pipes
26.	16'	Quintaton.....	from #1.....	32 notes
27.	8'	Principal.....	42.....19 $\frac{1}{2}$	17 zinc..C.M.....44 pipes
28.	8'	Sub Bass.....	from #26 #25.....	32 notes
29.	8'	Quintaton.....	from #1.....	32 notes
30.	4'	Super Octave.....	from #28 #27.....	32 notes
31.	4'	Sub Bass.....	from #26 #25.....	32 notes
32.		*Blank Knob.....	Console only	

*Indicates console preparations only

COUPLERS

33.	Great to Pedal	8'	44.	Choir to Great	16'
			45.	Choir to Great	8'
34.	Swell to Pedal	8'	46.	Choir to Great	4'
35.	Swell to Pedal	4'			
			47.	Swell	16'
36.	Choir to Pedal	8'	48.	Swell Unison Off	
37.	Choir to Pedal	4'	49.	Swell	4'
38.	Swell to Great	16'	50.	Choir	16'
39.	Swell to Great	8'	51.	Choir Unison Off	
40.	Swell to Great	4'	52.	Choir	4'
41.	Swell to Choir	16'	53.	Great Unison Off	
42.	Swell to Choir	8'	54.	Great	4'
43.	Swell to Choir	4'			

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5	Affecting stops of Swell Organ
Pistons No. 1-2-3-4-5	Affecting stops of Great Organ
Pistons No. 1-2-3-4-5	Affecting stops of Choir Organ
Pistons No. 1-2-3-4-5	Affecting stops of Pedal Organ
Pistons No. 1-2-3-4-5	Affecting stops and couplers of Full Organ
	(Generals) placed at left under Great Manual,
	numbered outward from center

PEDAL MOVEMENTS

Swell expression pedal with indicator light
 Choir expression pedal with indicator light
 Crescendo pedal with indicator light
 Sforzando pedal (reversible) with indicator light, duplicated by manual piston
 Great to Pedal (reversible) (duplicated by manual piston)
 Swell to Pedal (reversible) (duplicated by manual piston)
 Choir to Pedal (reversible) (duplicated by manual piston)

ACCESSORIES

Organ bench with music shelf

Concave and radiating pedal clavier - A.G.O. pattern

Castlelight - Console light

Slow speed electric motor, action power unit and blower in steel housing of ample capacity

On-off jamb switch for name shades