

M. P. MÖLLER Organ Factory

Pipe Organ No.	7114	Date	August 14, 1944
For	ST. ANDREW'S EPISCOPAL CHURCH, WILMINGTON, DELAWARE		
Action	Electro-pneumatic	Console	Detached
Casing No.	None	Finish	To approved sample
Decorations	Refinish Front Pipes	Motor	Electric Tablets
Width of Key-bed	Standard	Stop Controls	Draw Knobs & Tilting/
No. Manuals	2	Wind Pressure	Gt. 4" Sw. 4" Fed. 4"-6"
To be Completed	Soon as possible	Blower Pipe furnished by	Furchaser

PITCH: A-440

SPECIFICATIONS

Pipes of present organ to be used where adaptable to the following specifications. All such pipes, specified below as "Present" to be repaired and revoiced in the factory of M. P. Moller, Inc., and will be guaranteed to be in first class condition when installed in the new instrument. With the exception of the pipes mentioned above, the entire organ is to be new.

GREAT ORGAN

1	16'	Spitzprincipal.....new 40- $\frac{1}{2}$24 Zinc...S.M.....73	Pipes
2	8'	Principal.....new CC-40 - T.C. 56.....18-19 $\frac{1}{2}$ 12 Zinc SM..73	"
3	8'	Claribel Flute.....61 present New #1-#12 Mel. Bass #13- 3-3/4" x 3-3/16" O.D....73	"
4	8'	Dulciana.....new...56.....12 Zinc S.M.....73	"
5	4'	Octave.....61 present..56.....M.....73	"
6	4'	Harmonic Flute.....61 present..64.....M.....73	"
7	2-2/3'	Octave Quint.....new.....64.....S.M.....61	"
8	2'	Super Octave.....61 present..68.....M.....61	"
9	III-Rks.	Mixture.....new.....3 K.....S.M.....183	"
10		Chimes.....New action, present bells..G-G #20 - #44.....25	Bells
11		Tremulant	

SWELL ORGAN

12	8'	Geigen Principal...61 present....46...12 Zinc.....M.....73	Pipes
13	8'	Stopped Flute.....61 present CC-5-7/16" x 4-5/8" O.D.....73	"
14	8'	Salicional.....new...58.....12 Zinc...S. M.....73	"
15	8'	Voix Celeste T.C.....new.....58.....S. M.....61	"
16	4'	Octave Geigon.....61 present...60.....M.....73	"
17	4'	Hohl Flute.....61 present...C-3-3/4" x 3-1/4" O.D.....73	"
18	2'	Flautino.....61 present...70.....M.....61	"
19	III Rks.	Plein Jeu.....new 3 QS.M.....183	"
20	8'	Trumpet.....new 4 $\frac{1}{2}$ ".....73	"
21		Chimes.....From #10.....25	Notes
22		Tremulant	

PEDAL ORGAN

23	16'	Diapason.....12 present 30-40 Zinc...20 from #2...12 Pipes..20	Notes
24	16'	Bourdon...30 present CCC-12 $\frac{1}{2}$ x 10" O.D., CC-7-5/8" x 6-1/8 O.D.56	Pipes
25	16'	Lieblich Gedeckt CCC-7 $\frac{1}{4}$ " x 6-1/8" O.D...20 from #13..12 Pipes20	Notes
26	16'	Spitz Principal.....From #1.....32	"
27	8'	Octave.....new 44.....12 Zinc C.M.....44	Pipes
28	8'	Bourdon.....From #24.....32	Notes
29	8'	Stopped Flute.....From #13.....32	"
30	4'	Super Octave.....From #27.....32	"
31	4'	Flute.....From #24.....32	"
32	16'	Double Trumpet..new 8" - 4 $\frac{1}{2}$ "...20 From #20 6" W..12 Pipes....20	Notes

COUPLERS

33	Great to Pedal	40	Great Unison Separation
34	Great to Pedal 4'	41	Great 16'
35	Swell to Pedal	42	Great 4'
36	Swell to Pedal 4'	43	Swell Unison Separation
37	Swell to Great	44	Swell 16'
38	Swell to Great 16'	45	Swell 4'
39	Swell to Great 4'		

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4-5-6	Affecting Great Organ
Pistons No. 1-2-3-4-5-6	Affecting Swell Organ
Pistons No. 1-2-3-4-5	Affecting Pedal Organ (Duplicated by toe studs)
Pistons No. 1-2-3-4-5-6-7-8	Affecting Full Organ (Five of these duplicated by toe studs)
General Cancel Piston	

FEDAL MOVEMENTS

Great to Pedal Reversible
 Swell to Pedal Reversible
 Balanced Great Expression Pedal
 Balanced Swell Expression Pedal
 Balanced Crescendo Pedal
 Sforzando Pedal (duplicated by Manual piston)

ACCESSORIES

Crescendo Indicator
 Expression Indicator
 Volt Meter
 Sforzando Indicator
 Organ bench with music shelf (adjustable for height)
 Radiating, Concave Pedal Clavier
 Electric Blower, and current generator of ample capacity.
 Present Motor to be used.
 Signal light to operate on 110/220 volts A.C.
 Electric clock on console
 Music rack to be transparent plastic
 Console to be on rollers and moveable.