M. P. MÖLLER Organ Factory

Pipe Organ No	R-631	Date December 9, 1958
For	ST. PAUL®S LUTHERAN CHURCH,	CUMBERLAND, MD.
Action	Electro-Pneumatic	Console Present Detached
Casing No.	None	Finish Present N/C
Decorations	None	Motor Present motor & blower New DC
Width of Key-bed_	Standard	Stop Controls Present Stop Keys
No. Manuals	Three and Pedal	Wind Pressure well organ 5" Chair Organ 44"
To be Completed_	October 9, 1959	Stop Controls Present Stop Keys State Organ 45 " breat unindered Organ 5" Wind Pressure twile Organ 5" Chair Organ 45" Blower Pipe furnished by Purchaser

SPECIFICATIONS

FOR

REBUILDING PRESENT MOLLER ORGAN OFUS 4583 - 1926

* CONSOLE

Install new silver contacts on present stop keys and coupler controls, Install new silver contacts on combination pistons and manual pistons. Releather four I note combination primaries. Releather 27 note primary station and install new outside type magnets.

Recover 26 coupler pneumatics.

Recover four master combination pneumatics.

Install three new Expression roller switches with silver contacts. Install one new Crescendo roller switch with silver contacts. Install new rubber pads and binding on four pedal shoes. Refelt console and install new leather burrs and washers. Regulate and a djust console action.

Refelt pedal keyboard and install new rubber tips on wiper wires. Clean and polish console cabinet, organ bench and pedal keyboard.

MANUAL CHESTS

Releather 1303 manual pipe pouches. Install 1729 new stop action checks and eyelets. Install 402 new duplex shifters. Releather four 73 note primary stations and install new valves and new outside type magnets. Releather one 61 note primary station and install new valves and

new outside type magnets.

Releather 25 stop action primaries and install new outside type magnets.

OFFSET CHESTS

Install new action for Great 8 First Open Diapason #1 to #12 inc. Install new action for Great 8 Second Open Diapason #1 to #20 inc. Releather Swell 16 Bourdon unit action #1 to #97 inc. and install new outside type magnets. Releather Choir 8 Violin Diapason action #1 and #2 and install new

outside type magnets.

CONTACT BOXES

Install new contact box for Great 8 First Open Diapason #1 to #12 inc. Install new contact box for Great 8 Second Open Diapason #1 to #20 inc. Install new contact box for Choir 8 Violin Diapason #1 and #2. Recover one 73 note contact box for Swell Organ and install new silver wire contact blocks.

* CONSOLE

Provide 17 blank stop keys, install new combination action and new intermanual coupler arrangement above Swell Manual in usual manner according to specification changes listed below.

Repl by 3/30 SL 15 N. Smallwood St 21502

SWITCHES	Install	the	following	new	electro-pneumatic	switches	with	stop
	action							

0110			
Swell	16	Bourdon	73 notes
Swell	8	Gedeckt	73 notes
Swell	4	Flute d'Amour	73 notes
Swell	2-2/3	Flute Twelfth	61 notes
Swell	2	Flageolet	61 notes
Choir		Harp	49 notes
Echo		Chimes	21 notes

Install new tube and action for top F #42. CHITMES

> Releather 20 note action and install new outside type magnets. Recover 20 pneumatics

Releather 19 note action and install new outside type magnets. HARP

Recover 49 pneumatics.

Releather 16 Double Open Diapason action #1 to #44 inc. and PEDAL ORGAN

install new outside type magnets.

Releather 16 Bourdon action #1 to #lul inc. and install new outside

type magnets.

Install new 32 note pedal relay with six 32 note switches.

EXPRESSION Install new expression shades and action for Great-Choir organ.

Install new expression shades and action for Swell Organ.

Install new swell box partition as required.

Releather 8 note expression action for Echo Organ. Recover 8 shade and bumper pneumatics for Echo Organ.

Install new shade jacks and connecting rods for Echo Organ.

Releather one 2'-0"x hi-0" Manual reservoir and install new curtain RESERVOIRS

valve

Releather one 2'-6" x h'-0" Manual reservoir and install new curtain

Releather two 3'-0" x 5'-0" Manual reservoirs and install new curtain

valves

Releather two Pedal reservoirs and install new curtain valves.

Releather one 3'-6" x 4'-6" Blower reservoir and install new curtain

valves.

Releather one Chime reservoir. Releather one Harp reservoir.

Releather one shade reservoir from Echo Organo

TREMOLOS Install three new electro-pneumatic tremolos.

Chines

Clean and polish 25 present tutes. Recondition 25 present electric actions, relays, etc.

PIPES

Revoice the following reeds:

Great	8	Tuba
Swell	8	Oboe
Choir	8	Clarinet
Echo	8	Vox Humana

Install tuner slides on the following pipes:

Great	8	Doppel Flute	#62 to #73 inc.
Great	8	Concert Flute	#62 to #73 inc.
Swell	8	Viole d'Orchestre	#1 to #12 inc.
Swell	8	Aeoline	#1 to #12 inc.
Choir	8	Violin Diapason	#1 to //12 inc.
Echo	8	Echo Flute	#62 to #73 inc.
Echo	8	Salicional	#1 to #12 inc.

CABLES

Install new asbestos covered cables between console and organ.

BLOWER

Clean present blower and repair as required. Present motor to be used without change.

ACTION CURRENT

Install new 10-15 volt, 30 ampere DC organ power unit.

GENERAL

The entire organ to be returned to factory of M. P. Holler, Inc. at Hagerstown, Md. for rebuilding as specified above. Organ to be re-engineered and installed in new organ chambers.

SPECIFICATIONS OF CONSOLE AND ORGAN

MANUAL COMPASS	CC to Ch. 61 notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	4 110 0 700

PITCH

А-440 @ 70 F

GREAT OR GAN

anticonstanting control of the Care Care Care Care Care Care Care Car	
2 8 Second Open Diapason	61 Pipes 6. #16-12-00-6

SWELL ORGAN 6

10 11 12 13 14 15 16 17 18 19 20	16 8 8 8 8 8 8 4 2-2/3 2 8	Bourdon (unit)	ripes ripes
21 22 23 24 25 26 27 28 29 29 29 29 29 29 29 29 29 29 29 29 29	Blank Stop Ke	(Playable from Great manual - by nictors in left south)	lotes lipes lotes lipes lipes lipes lars
30 31 32 33 34 35	Blank Stop Kell	Echo Flute	ipes otes
37 38 39 40 41 42 42 42 42 42 42 42 42 42 42 42 42 42	16 8 8	Resultant from #38 and #39 Per Bourdon From #10 Per Bourdon From #38 Per Bourdon From #38 Per Bourdon From #38 Per Bourdon From #38 Per Bourdon From #39 Per	ipes ipes otes

COUPLERS

43	Great to Pedal	56	Great 4
lele	Great to Pedal 4	57	Choir to Swell 16
45	Swell to Pedal	58	Choir to Swell
46	Swell to Pedal 4	59	Choir to Swell 4
47	Choir to Pedal	60	Swell 16
48	Swell to Great 16	61	Swell Unison Off
49	Swell to Great	62	Swell 4
49	Swell to Great 4	63	Swell to Choir 16
51.	Choir to Great 16	64	Swell to Choir
52	Choir to Great	65	Swell to Choir 4
53	Choir to Great h	66	Choir 16
54	Great 16	67	Choir Unison Off
55	Great Unison Off	68	Choir 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2-3-4	Affecting Great and Echo Stops
Pistons No. 1-2-3-4	Affecting Swell Stops
Pistons No. 1-2-3-4	Affecting Choir Stops
Pistons No. 1-2-3-4	Affecting Pedal Stops
Pistons No. 1-2-3	Affecting Full Organ and Intu-manual couplers

PEDAL MOVEMENTS

•	app .	Great	to	Pedal	Reversible	

- 2 Balanced Expression Pedal for Great-Choir Organ (contacts, regular system)
 3 Balanced Expression Pedal for Swell Organ (contacts, regular system)
- 4 Balanced Expression Pedal for Echo Organ (8 contacts, regular system)
- 5 Balanced Crescendo Pedal with indicator light (green jewel)

ACCESSORIES

Present organ bench with music shelf

Present concave and radiating pedal keyboard

Present motor and blower. New 10-15 volts, 30 ampere DC organ power unit.