

M. P. MÖLLER Organ Factory

Pipe Organ No.	R-469	Date	May 4, 1953
For	CHRISTIAN CHURCH, BEAVER CREEK, MD.		
Action	Electro-Pneumatic	Console	Present Detached
Casing No.	Present - Supply Case Panel	Finish	To Match Present Finish
Decorations	Present - No Change	Motor	Present Motor & Blower. New Orgelestra
Width of Key-bed	Standard	Stop Controls	Present Stop-Keys
No. Manuals	Two & Pedal	Wind Pressure	No Change
To be Completed	Four months from above date	Blower Pipe furnished by	Present

SPECIFICATIONS

FOR

RELEATHERING & ELECTRIFYING PRESENT MOLLER ORGAN 4888 1927

CONSOLE

Rebuild and electrify present console as follows -

Rework present console cabinet to completely enclose mechanism.
(match existing finish and design.)

Install new coupler boards and related mechanism for 12 couplers.

Install new combination action for -

Pistons 1-2 Great and Pedal Stops.

Pistons 1-2 Swell and Pedal Stops.

Install new Great to Pedal reversible.

Install new Expression Pedal and contact roller.

Install new Crescendo Pedal and contact roller.

Refelt present pedal keys.

Rebuilt console to be extended approximately 10' from present case.

MANUAL CHEST

Releather 288 manual pipe pouches.

Releather and electrify two 61 note primary stations.

Install 549 stop action checks and eyelets.

Install 244 duplex shifters.

Releather and electrify 9 stop action controls.

OFFSET ACTION

Releather and electrify 8 Open Diapason action 1-12 inc.

Releather and electrify 8 Dulciana action 1-5 inc.

CONTACT BOX

Install new single conductor contact box for Great 8 Open Diapason 1-12 inc.

Install new single conductor contact box for Great 8 Dulciana 1-5 inc.

PEDAL CHEST

Releather and electrify 16 Bourdon action 1-32 inc.

EXPRESSION

Install new accordian type expression action.

Extend present swell box approximately 1'-0" to enclose entire organ,
except low notes of 8 Open Diapason which are on the existing organ case.

RESERVOIR	Releather one 2'-6" x 4'-0" reservoir and install new curtain valve. Releather present Pedal reservoir (two pressure). Install new leather flexible joints on wind trunks.
TREMOLO	Install new electro-pneumatic beater type tremolo.
PIPES	Install modern tuning slides on all metal pipes. Replace or repair pipes damaged by water. Tune and tone regulate organ.
CABLES	Install new asbestos covered cables between console and organ.
ACTION CURRENT	Install new 10-15 volt 10 ampere Orgelectra organ power unit.
CASE PANEL	Install new case panel of matching design and finish to enclose present console location in organ case. Move present case forward approximately 1'-0" and install two plain filler boards finished to match present case.

SPECIFICATIONS

FOR

CONSOLE & ORGAN

MANUAL COMPASS	CC to C4, 61 notes
PEDAL COMPASS	CCC to G, 32 notes
WIND PRESSURE	3-3/4"
PITCH	A-440 @ 70° F

GREAT ORGAN

1	8	Open Diapason.....	61 Pipes
2	8	Stopped Diapason.....	61 Pipes
3	8	Salicional.....	61 Pipes
4	8	Dulciana.....	61 Pipes
5	4	Flute Traverso.....	61 Pipes

SWELL ORGAN

6	8	Gedeckt.....from #2.....	61 Notes
7	8	Salicional.....from #3.....	61 Notes
8	8	Dulciana.....from #4.....	61 Notes
9	4	Flute.....from #5.....	61 Notes
10		Tremulant	

PEDAL ORGAN

* 11	16	Bourdon.....	32 Pipes
* 12	16	Lieblich Gedeckt.....from #11.....	32 Notes

COUPLERS

13	Great to Pedal
14	Swell to Pedal
15	Swell to Great 16
16	Swell to Great
17	Swell to Great 4
18	Great 16
19	Great 4
20	Swell 16
21	Swell 4

ADJUSTABLE COMBINATIONS

Pistons No. 1-2	Affecting Great and Pedal Stops
Pistons No. 1-2	Affecting Swell and Pedal Stops

PEDAL MOVEMENTS

- 1 - Great to Pedal Reversible
- 2 - Balanced Expression Pedal (8 contacts - reverse system)
- 3 - Balanced Crescendo Pedal

ACCESSORIES

Action current indicator light - White
Crescendo indicator light - Green

Present organ bench with music shelf
Present concave pedal keyboard

Present motor & blower. New orgelectra power unit.

MOLLER ORGAN OPUS - 4888 - 1927